

5.0 References

- Associated Transportation Engineers, 2013. Tajiguas Resource Recovery Project EIR, Santa Barbara, California, Traffic and Circulation Study, October 8.
- Bay Area Air Quality Management District (BAAQMD), 2008. Permit Handbook, Section 11.13, Tub Grinders, April. Downloaded from http://hank.baaqmd.gov/pmt/handbook/rev02/PH_00_05_11_13.pdf.
- Braunschweiger Umwelt-Biotechnologie GmbH (BUB), 2010. Bericht über die Emissionsmessungen an der - Kompostierungs-Anlage - Biogas-Anlagedes Abfallwirtschaftszentrums, Borgstedt [Bekon Study]. December.
- Bull, M., A. McIntyre, D. Hall, G. Allison, J. Redmore, J. Pullen, L. Caird, M. Stoaling, R. Fain, (2014). IAQM Guidance on the assessment of odour for planning, Institute of Air Quality Management, London. www.iaqm.co.uk/text/guidance/odour-guidance-2014. April.
- California Air Resources Board (ARB), 2006. OFFROAD2007 model. Downloaded from http://www.arb.ca.gov/msei/offroad/downloads/models/offroad2007_1215_exe.zip.
- 2013a. EMFAC2011 model online data. Accessed at <http://www.arb.ca.gov/emfac/>.
- 2013b. EMFAC2011-LDV model. Downloaded from http://www.arb.ca.gov/msei/emfac2011_ldv.htm.
- 2013c. EMFAC2011 Frequently Asked Questions. Accessed at http://www.arb.ca.gov/msei/emfac2011-faq.htm#emfac2011_web_db_qstn07.
- 2011a. OFFROAD2011 model. Downloaded from http://www.arb.ca.gov/msei/categories.htm#offroad_motor_vehicles.
- 2011b. The Carl Moyer Program Guidelines, Approved Revisions 2011, Approved April 2011. Downloaded from <http://www.arb.ca.gov/msprog/moyer/guidelines/current.htm>.
2009. AB 32 Climate Change Scoping Plan. May 11.
- California Air Pollution Control Officers Association (CAPCOA). 2009. Health Risk Assessments for Proposed Land Use Projects. July.
2011. Quantifying Greenhouse Gas Mitigation Measures.
- California Integrated Waste Management Board (CIWMB). 2008. Emissions Testing of Volatile Organic Compounds from Greenwaste Composting at the Modesto Compost Facility in the San Joaquin Valley. Accessed at <http://www.calrecycle.ca.gov/Publications/Documents/Organics/44207009.pdf>.
- California Office of Planning and Research. 2011. California Environmental Quality Act Statutes and Guidelines.
- California Senate Bill 97 - CEQA GHG Guidelines. 2009. CCR Title 14. Natural Resources Division 6. Resources Agency Chapter 3. Article 5. §15064.4.

- CalRecycle. 2011. Statewide Anaerobic Digester Facilities for the Treatment of Municipal Organic Solid Waste, Final Program Environmental Impact Report, SCH No. 2010042100.
- CH2M HILL Report. 2010. Odor Impact Evaluation for Cedar Grove Composting's Everett Facility. City of Everett, Washington.
- City of Santa Maria, 1995. Conditional Negative Declaration for Engel & Gray Composting Facility, E- 94-56. June 21, 1995.
2013. Final Subsequent Environmental Impacts Report for the Atlas Copco – Mafi Trench Project. November. Downloaded from <http://www.cityofsantamaria.org/3069.html>.
2010. Santa Maria Integrated Waste Management Facility Project Final EIR. April 2010.
2008. Addendum for Conditional Negative Declaration for Engel & Gray Composting Facility. July 3, 2008.
- Climate Registry. 2009. Electric Power Sector Protocol for the Voluntary Reporting Program, Version 1.0. Available at: http://www.theclimateregistry.org/downloads/2009/05/Electric-Power-Sector-Protocol_v1.0.pdf.
2013. 2013 Climate Registry Default Emission Factors, January. Downloaded from <http://www.theclimateregistry.org/downloads/2013/01/2013-Climate-Registry-Default-Emissions-Factors.pdf>.
- County of Santa Barbara. 2016. Final Subsequent Environmental Impact Report (Subsequent EIR), 12EIR-00000-00002. July 12.
2015. Board of Supervisors Adoption of the Energy and Climate Action Plan. May 19. Downloaded from <http://longrange.sbcountyplanning.org/programs/climateactionstrategy/climateaction.php>.
- 2013a. Energy and Climate Action Plan Summary Information. March. Downloaded from <http://longrange.sbcountyplanning.org/programs/climateactionstrategy/climateaction.php>.
- 2013b. Email from Joddi Leipner of RRWMD to Sean Wazlaw of AECOM on February 7, 2013 confirming that the Tajiguas Landfill has not received odor complaints in the past.
- 2013c. E-mail from Joddi Leipner, Senior Environmental Planner of RRWMD to Sara Head of AECOM. August 8.
2002. Final Environmental Impact Report, Tajiguas Landfill Expansion Project. State Clearing House Number 98041003, Santa Barbara County Number 01-EIR-5. July.
2001. Draft Environmental Impact Report, Tajiguas Landfill Expansion Project, Appendix E.8. State Clearing House Number 98041003, Santa Barbara County Number 01-EIR-5. October.
- County of Santa Barbara Environmental Health Services, 2007. Air Quality Impact Analysis, MarBorg C&D Recycling Facility Revised Permit -2007. August 29.
- County of Santa Barbara Planning and Development, 2008. Environmental Thresholds and Guidelines Manual, October. Greenhouse gas thresholds most recently updated in July 2015.
2010. Guidelines for the Implementation of the California Environmental Quality Act of 1970 As Proposed. June.

- County of Ventura Planning Division. 2010. Simi Valley Landfill and Recycling Center Expansion Project Final EIR.
- DiStefano, T. and L. Belenky. 2009. Life-Cycle Analysis of Energy and Greenhouse Gas Emissions from Anaerobic Biodegradation of Municipal Solid Waste, *J. Environ. Eng.*, 135(11), 1097–1105
- Doll, R. and R. Peto. 1981. The causes of cancer: quantitative estimates of avoidable risks of cancer in the United States today. *Journal of the National Cancer Institute*. 66(6):1191–1308.
- Drude, Kevin. 2009. Memorandum: Shell Hercules Slope Remediation/Stabilization Project, Case No. 09CDH-00000-00002, County of Santa Barbara Planning Department. September 4.
- Engel, B., 2013. Personal communication between Bob Engel (Engel and Gray) and Matt Ingamells (Padre Associates). March.
- Environ, 2011. California Emissions Estimator Model (CalEEMod), version 2011.1.1. Downloaded from <http://www.caleemod.com/>.
- Homans, W.J. and K. Fischer. 1992. A Composting Plant as An Odor Source. *Acta Horticulturae*, 302, 37–44.
- Intergovernmental Panel on Climate Change (IPCC). 2007. Synthesis Report Summary for Policymakers. Available at: http://www.ipcc.ch/publications_and_data/ar4/syr/en/spm.html.
- Kumar, Anuj, C.P. Alaimo, R. Horowitz, F.M. Mitloehner, M.J. Kleinman, and P.G. Green. 2011. Volatile organic compound emissions from green waste composting: Characterization and ozone formation, *Atmos. Environ.*, 45 (2011) 1841–1848.
- Nunez, F. 2006. California Global Warming Solutions Act; 2006. Assembly Bill No. 32, Chapter 488, Legislative Counsel's Digest: Sacramento, California.
- Office of Environmental Health Hazard Assessment (OEHHA). 2009. Technical Support Document for Describing Available Cancer Potency Factors, Appendix A: Hot Spots Unit Risk and Cancer Potency Values. June.
2017. Consolidated Table of OEHHA/ARB Approved Risk Assessment Health Values. February.
2015. Air Toxics Hotspots Program Guidance Manual for Preparation of Health Risk Assessments. August.
- PMC. 2015. Final Environmental Impact Report For the Energy and Climate Action Plan. SCH# 20144021021. May.
- RWDI. 2005. Final Report Odour Management in British Columbia: Review and Recommendations.
- San Joaquin Valley Air Pollution Control District, 2010. Compost VOC Emission Factors. September 15. Downloaded from <http://valleyair.org/Workshops/postings/2010/9-22-10-rule4566/SJVAPCD%20Compost%20VOC%20EF%20Report%209-15-10.pdf>.
- Santa Barbara County Air Pollution Control District and Santa Barbara County Association of Governments. 2011. 2010 Clean Air Plan. January.
- Santa Barbara County Air Pollution Control District. 2010a. Permit to Operate 9788, Final Part 70 Permit Renewal/Reevaluation 09788-R3. December 22, 2010.

- 2017a Email correspondence between Alex Economou, Air Quality Specialist, SBCAPCD, and Matt Dunn (AECOM).
- 2017b. Modeling Guidelines for Health Risk Assessments (APCD Form -15i). Last updated May, 2017.
- 2017c. Email correspondence between Michael F. Goldman, Engineering Division Manager of Santa Barbara County Air Pollution Control, and Matt Dunn (AECOM). April.
2015. Environmental Review Guidelines for Health Risk Assessments (APCD Form -15i). Last updated May, 2017.
- 2014a. Email correspondence between David Harris, SBCAPCD and Mary Kaplan, AECOM. June.
- 2014b. Email correspondence between David Harris, SBCAPCD and Joddi Leipner, RRWMD. July.
- 2011a. Scope and Content of Air Quality Sections in Environmental Documents. December.
- 2011b. Gasoline Station Health Risk Assessment Application Form 25T. <http://www.sbcapcd.org/eng/dl/appforms/apcd-25T.pdf>. Last updated September, 2011.
- Schmidt, C.E., T.R. Card, and B. Kiehl, 2009. Composting Trials Evaluate VOC Emissions Control. *BioCycle*, Vol. 50, No. 4, p.33. April.
- SCS Engineers with Cascadia. 2009. Waste Characterization Study for the Tajiguas Landfill. March.
- Spencer, R. and C. Alix, 2007. Compost Facility Odor Control. Solid Waste Association of North America New York State Chapter Odor Control at Solid Waste Management Facilities Specialty Seminar. Albany, New York. November 7.
- South Coast Air Quality Management District (SCAQMD). 1996. Source Test Report 96-0007/96-0008/96-0009, Conducted at San Joaquin Composting, Inc., Holloway Road, Lost Hills, California. March. Downloaded from http://www.aqmd.gov/rules/doc/r1133/sanjoaquin_source.pdf.
- U. S. Environmental Protection Agency (EPA). 1985. Guideline for Determination of Good Engineering Practice Stack Height. EPA Document No. EPA-450/4-80-023R. Office of Air Quality Planning and Standards, Research Triangle Park, North Carolina. June.
2017. Ambient Air Quality Data. Accessed at <https://www.epa.gov/outdoor-air-quality-data>.
2016. Guideline on Air Quality Models (Revised). Codified in the Appendix W to 40 CFR Part 51. Office of Air Quality Planning and Standards, Research Triangle Park, North Carolina. December.
2015. National Ambient Air Quality Standards for Ozone, Final Rule. October 1. Accessed at <http://www3.epa.gov/airquality/ozonepollution/actions.html#current>.
2012. Haul Road Workgroup Final Report Submission to EPA-OAQPS, memorandum dated March 2, 2012. Accessed at http://www.epa.gov/ttn/scram/reports/Haul_Road_Workgroup-Final_Report_Package-20120302.pdf.
- 2010a. Landfill Gas (LFG) Energy Project Development Handbook. Washington, DC. U.S. Government Printing Office. Retrieved from: http://www.epa.gov/lmop/documents/pdfs/pdh_chapter1.pdf.

- 2010b. Municipal Solid Waste in the United States: 2010 Facts and Figures. Downloaded from <http://www.epa.gov/osw/nonhaz/municipal/msw99.htm>.
- 2010c. Climate Change – Basic Information. Available at: <http://epa.gov/climatechange/basicinfo.html>.
2009. AERMOD Implementation Guide (AIG). Office of Air Quality Planning and Standards, Research Triangle Park, North Carolina. March.
- 2008a. Compilation of Air Pollutant Emission Factors (AP-42), Draft Section 2.4, Municipal Solid Waste Landfills. October. Downloaded from <http://www.epa.gov/ttn/chief/ap42/ch02/draft/d02s04.pdf>.
- 2006a. Compilation of Air Pollutant Emission Factors (AP-42), Section 13.2.2, Unpaved Roads. November. Downloaded from <http://www.epa.gov/ttn/chief/ap42/ch13/final/c13s0202.pdf>.
- 2006b. Compilation of Air Pollutant Emission Factors (AP-42), Section 13.2.2, Aggregate Handling and Storage Piles. November. Downloaded from <http://www.epa.gov/ttn/chief/ap42/ch13/final/c13s0204.pdf>.
- 2006c. TANKS Emission Estimation Software, Version 4.09D. October. Downloaded from <http://www.epa.gov/ttn/chief/software/tanks/index.html#order>.
2004. Compilation of Air Pollutant Emission Factors (AP-42), Section 11.19, Crushed Stone Processing and Pulverized Mineral Processing. August. Downloaded from <http://www.epa.gov/ttn/chief/ap42/ch13/final/c13s0201.pdf>.
2000. Compilation of Air Pollutant Emission Factors (AP-42), Section 3.2, Natural Gas Fired Reciprocating Engines. July. Downloaded from <http://www.epa.gov/ttn/chief/ap42/ch03/final/c03s02.pdf>.
1998. Compilation of Air Pollutant Emission Factors (AP-42), Section 11.9, Western Surface Coal Mining. October. Downloaded from <http://www.epa.gov/ttn/chief/ap42/ch11/final/c11s09.pdf>.
- van Harreveld, F., B.T. Rutjens, M.Rotteveel, L.F. Nordgren, J. van der Pligt, 2009. Ambivalence and decisional conflict as a cause of psychological discomfort: Feeling tense before jumping off the fence. *Journal of Experimental Social Psychology*, 45, 167–173.
- Ventura County Air Pollution Control District, 2001. AB2588 Combustion Emission Factors for Diesel Fuel Internal Combustion, May. <http://www.aqmd.gov/docs/default-source/permitting/toxics-emission-factors-from-combustion-process-.pdf?sfvrsn=0>.
2003. Ventura County Air Quality Assessment Guidelines. October.
- Western Regional Air Partnership, 2006. WRAP Fugitive Dust Handbook, September. Downloaded from http://www.wrapair.org/forums/dejf/fdh/content/fdhandbook_rev_06.pdf.

Appendix A Project Operation Emissions Calculations

Table 1

Criteria Pollutant Daily Emissions Summary without CSSR

Source	Emissions (lb/day)					
	CO	ROC	NOx	SOx	PM10	PM2.5
Onsite						
AD CHP Engines	54.62	20.51	20.81	0.00	19.64	19.64
Flare	0.25	0.00	0.10	13.62	0.05	0.05
MRF Facility Equipment	48.18	2.22	13.21	0.07	0.00	0.00
AD Facility Equipment	7.98	0.30	0.65	0.01	0.00	0.00
Equipment Outside MRF and AD Fac.	1.83	0.09	1.64	0.01	0.01	0.01
Composting Equipment Exhaust	8.25	0.38	0.82	0.02	0.02	0.02
Emergency Engine	0.69	0.04	0.13	0.00	0.01	0.01
Diesel Fuel Storage Tanks		0.02				
Material Handling Fugitive PM					5.91	0.89
Compost Screening Fugitive PM					0.06	0.00
Chipper/Grinder Fugitive PM					0.98	0.98
Motor Vehicle Fugitive PM					1.37	0.34
AD/MRF Fugitive ROC		3.50				
Windrow ROC		12.59				
Motor Vehicle Exhaust	0.12	0.03	0.06	0.00	0.00	0.00
Onsite Total	121.91	39.68	37.42	13.74	28.05	21.96
Offsite						
Motor Vehicle Exhaust	23.76	4.42	6.87	0.07	0.49	0.36
Motor Vehicle Fugitive PM					3.84	0.94
Offsite Total	23.76	4.42	6.87	0.07	4.33	1.30
Total	145.67	44.11	44.29	13.82	32.38	23.27

Table 2

Criteria Pollutant Annual Emissions Summary without CSSR

Source	Emissions (ton/year)					
	CO	ROC	NOx	SOx	PM10	PM2.5
Onsite						
AD CHP Engines	8.74	3.49	3.58	0.64	3.41	3.41
Flare	0.90	0.01	0.36	0.26	0.19	0.19
MRF Facility Equipment	7.49	0.35	2.05	0.01	0.00	0.00
AD Facility Equipment	0.83	0.03	0.07	0.00	0.00	0.00
Equipment Outside MRF and AD Fac.	0.28	0.01	0.26	0.00	0.00	0.00
Composting Equipment Exhaust	0.11	0.01	0.01	0.00	0.00	0.00
Emergency Engine	0.03	0.00	0.01	0.00	0.00	0.00
Diesel Fuel Storage Tanks		0.00				
Material Handling Fugitive PM					0.18	0.03
Compost Screening Fugitive PM					0.01	0.00
Chipper/Grinder Fugitive PM					0.15	0.15
Motor Vehicle Fugitive PM					0.21	0.05
AD/MRF Fugitive ROC		0.64				
Windrow ROC		2.30				
Motor Vehicle Exhaust	0.02	0.01	0.01	0.00	0.00	0.00
Onsite Total^a	18.41	6.84	6.34	0.91	4.15	3.83
Offsite						
Motor Vehicle Exhaust	3.69	0.69	1.07	0.01	0.08	0.06
Motor Vehicle Fugitive PM					0.60	0.15
Offsite Total	3.69	0.69	1.07	0.01	0.67	0.20
Total	22.11	7.53	7.41	0.93	4.82	4.03

Table 3

Criteria Pollutant Daily Emissions Summary with CSSR

Source	Emissions (lb/day)					
	CO	ROC	NOx	SOx	PM10	PM2.5
Onsite						
AD CHP Engines	54.62	20.51	20.81	0.00	19.64	19.64
Flare	0.25	0.00	0.10	13.62	0.05	0.05
MRF Facility Equipment	48.18	2.22	13.21	0.07	0.00	0.00
AD Facility Equipment	7.98	0.30	0.65	0.01	0.00	0.00
Equipment Outside MRF and AD Fac.	1.83	0.09	1.64	0.01	0.01	0.01
Composting Equipment Exhaust	8.25	0.38	0.82	0.02	0.02	0.02
Emergency Engine	0.69	0.04	0.13	0.00	0.01	0.01
Diesel Fuel Storage Tanks		0.02				
Material Handling Fugitive PM					5.91	0.89
Compost Screening Fugitive PM					0.06	0.00
Chipper/Grinder Fugitive PM					0.98	0.98
Motor Vehicle Fugitive PM					2.08	0.53
AD/MRF Fugitive ROC		3.50				
Windrow ROC		12.59				
Motor Vehicle Exhaust	0.19	0.06	0.14	0.00	0.00	0.00
Onsite Total	121.98	39.71	37.50	13.74	28.77	22.15
Offsite						
Motor Vehicle Exhaust	30.71	5.73	4.98	0.09	0.54	0.41
Motor Vehicle Fugitive PM					4.91	1.20
Offsite Total	30.71	5.73	4.98	0.09	5.45	1.62
Total	152.69	45.44	42.48	13.83	34.22	23.76

Table 4

Criteria Pollutant Annual Emissions Summary with CSSR

Source	Emissions (ton/year)					
	CO	ROC	NOx	SOx	PM10	PM2.5
Onsite						
AD CHP Engines	8.74	3.49	3.58	0.64	3.41	3.41
Flare	0.90	0.01	0.36	0.26	0.19	0.19
MRF Facility Equipment	7.49	0.35	2.05	0.01	0.00	0.00
AD Facility Equipment	0.83	0.03	0.07	0.00	0.00	0.00
Equipment Outside MRF and AD Fac.	0.28	0.01	0.26	0.00	0.00	0.00
Composting Equipment Exhaust	0.11	0.01	0.01	0.00	0.00	0.00
Emergency Engine	0.03	0.00	0.01	0.00	0.00	0.00
Diesel Fuel Storage Tanks		0.00				
Material Handling Fugitive PM					0.18	0.03
Compost Screening Fugitive PM					0.01	0.00
Chipper/Grinder Fugitive PM					0.15	0.15
Motor Vehicle Fugitive PM					0.32	0.08
AD/MRF Fugitive ROC		0.64				
Windrow ROC		2.30				
Motor Vehicle Exhaust	0.03	0.01	0.02	0.00	0.00	0.00
Onsite Total^a	18.42	6.85	6.36	0.91	4.27	3.86
Offsite						
Motor Vehicle Exhaust	4.77	0.89	0.77	0.01	0.08	0.06
Motor Vehicle Fugitive PM					0.76	0.19
Offsite Total	4.77	0.89	0.77	0.01	0.85	0.25
Total	23.20	7.74	7.13	0.93	5.11	4.11

**Table 5
Greenhouse Gas Annual Emissions Summary without CSSR**

Source	Emissions (MT/year) ^a			
	CO ₂	CH ₄	N ₂ O	CO ₂ e ^b
Onsite				
CHP Engines Combustion	8,899.71	0.21	0.03	8,912.91
CHP Engines Pass-through CO ₂	5,824.47			5,824.47
Flare Combustion	476.99	0.03	0.01	479.40
Flare Pass-through CO ₂	328.68			328.68
MRF Facility Equipment	1,122.79	0.06	0.03	1,132.90
AD Facility Equipment	118.93	0.01	0.00	120.00
Equipment Outside MRF and AD Fac.	76.21	0.00	0.00	76.89
Composting Equipment Exhaust	50.97	0.00	0.00	51.43
Motor Vehicle Exhaust	17.52	0.03	0.00	18.87
Onsite Total	16,916.27	0.34	0.07	16,945.55
Offsite				
Motor Vehicle Exhaust	1,560.81	2.38	0.22	1,685.56
Offsite Total	1,560.81	2.38	0.22	1,685.56
Total	18,477.07	2.71	0.29	18,631.11

^a Metric ton = 1,000 kilograms = pounds x 453.6 g/lb / 1,000,000 g/MT

^b CO₂e = CO₂-equivalent = CO₂ + 25 x CH₄ + 298 x N₂O

**Table 6
Greenhouse Gas Annual Emissions Summary with CSSR**

Source	Emissions (MT/year) ^a			
	CO ₂	CH ₄	N ₂ O	CO ₂ e ^b
Onsite				
CHP Engines Combustion	8,899.71	0.21	0.03	8,912.91
CHP Engines Pass-through CO ₂	5,824.47			5,824.47
Flare Combustion	476.99	0.03	0.01	479.40
Flare Pass-through CO ₂	328.68			328.68
MRF Facility Equipment	1,122.79	0.06	0.03	1,132.90
AD Facility Equipment	118.93	0.01	0.00	120.00
Equipment Outside MRF and AD Fac.	76.21	0.00	0.00	76.89
Composting Equipment Exhaust	50.97	0.00	0.00	51.43
Motor Vehicle Exhaust	33.82	0.03	0.00	35.60
Onsite Total	16,932.57	0.35	0.07	16,962.29
Offsite				
Motor Vehicle Exhaust	1,951.40	3.18	0.29	2,116.99
Offsite Total	1,951.40	3.18	0.29	2,116.99
Total	18,883.98	3.53	0.36	19,079.28

^a Metric ton = 1,000 kilograms = pounds x 453.6 g/lb / 1,000,000 g/MT

^b CO₂e = CO₂-equivalent = CO₂ + 25 x CH₄ + 298 x N₂O

Table 7 Emission Rates for Dispersion Modeling

Table 7-A Daily Emissions Inside MRF Facility - 7:00 a.m. - 11:00 p.m.

Time Period	Emissions (g/s)					
	CO	ROC	NOx	SOx	PM10	PM2.5
7:00 a.m. - 11:00 p.m.	3.64E-01	2.28E-02	9.04E-02	5.28E-04	5.55E-06	2.39E-06

Table 7-B Annual Average Emissions Inside MRF Facility - 7:00 a.m. - 11:00 p.m.

Time Period	Emissions (g/s)					
	CO	ROC	NOx	SOx	PM10	PM2.5
7:00 a.m. - 11:00 p.m.	3.10E-01	1.95E-02	7.70E-02	4.49E-04	4.73E-06	2.03E-06

Table 7-C Daily Emissions Inside MRF Facility - 11:00 p.m. - 7:00 a.m.

Time Period	Emissions (g/s)					
	CO	ROC	NOx	SOx	PM10	PM2.5
11:00 p.m. - 7:00 a.m.	3.04E-02	7.46E-03	2.74E-02	1.05E-04	1.65E-07	1.65E-07

Table 7-D Annual Average Emissions Inside MRF Facility - 11:00 p.m. - 7:00 a.m.

Time Period	Emissions (g/s)					
	CO	ROC	NOx	SOx	PM10	PM2.5
11:00 p.m. - 7:00 a.m.	2.59E-02	6.37E-03	2.33E-02	8.94E-05	1.40E-07	1.40E-07

Table 7-E Daily Emissions Inside AD Facility - 8:00 a.m. - 4:00 p.m.

Time Period	Emissions (g/s)					
	CO	ROC	NOx	SOx	PM10	PM2.5
8:00 a.m. - 4:00 p.m.	1.26E-01	1.12E-02	1.02E-02	1.84E-04	4.61E-06	1.13E-06

Table 7-F Annual Average Emissions Inside AD Facility - 8:00 a.m. - 4:00 p.m.

Time Period	Emissions (g/s)					
	CO	ROC	NOx	SOx	PM10	PM2.5
8:00 a.m. - 4:00 p.m.	7.16E-02	6.36E-03	5.81E-03	1.05E-04	2.63E-06	6.44E-07

Table 7-G Daily Emissions from MRF Facility Biofilter (BF_TIP) - 7:00 a.m. - 11:00 p.m. (Emissions Inside MRF Tipping Area)

Time Period	Emissions (g/s)						Area (m ²)	Night %
	CO	ROC	NOx	SOx	PM10	PM2.5		
7:00 a.m. - 11:00 p.m.	3.11E-01	1.43E-02	4.27E-02	3.57E-04	1.54E-06	1.54E-06	613.2	0.05

Emissions (g/s/m ²)						
CO	ROC	NOx	SOx	PM10	PM2.5	Area
5.07487E-04	3.31466E-05	6.97053E-05	5.82109E-07	2.50423E-09	2.50423E-09	613.2

BF_TIP | Night % 0.05

Table 7-H Annual Average Emissions from MRF Facility Biofilter (BF_TIP) - 7:00 a.m. - 11:00 p.m. (Emissions Inside MRF Tipping Area)

Time Period	Emissions (g/s)						Area (m ²)	Night %
	CO	ROC	NOx	SOx	PM10	PM2.5		
7:00 a.m. - 11:00 p.m.	2.65E-01	1.22E-02	3.64E-02	3.04E-04	1.31E-06	1.31E-06	613.2	0.05

Emissions (g/s/m ²)						
CO	ROC	NOx	SOx	PM10	PM2.5	Area
4.32407E-04	2.97003E-05	5.93927E-05	4.95986E-07	2.13374E-09	2.13374E-09	613.2

BF_TIP | Night % 0.05

Table 7-I Daily Emissions from MRF Facility Biofilter (BF_TIP) - 11:00 p.m. - 7:00 a.m. (Emissions Inside MRF Tipping Area)

Time Period	Emissions (g/s)						Area (m ²)	Night %
	CO	ROC	NOx	SOx	PM10	PM2.5		
11:00 p.m. - 7:00 a.m.	1.52E-02	7.20E-04	1.37E-02	5.29E-05	8.23E-08	8.23E-08	613.2	0.33

Emissions (g/s/m ²)						
CO	ROC	NOx	SOx	PM10	PM2.5	Area
2.48195E-05	1.16260E-05	2.23340E-05	8.56042E-08	1.34159E-10	1.34159E-10	613.2

BF_TIP | ROC Night % 0.33

Table 7-J Annual Average Emissions from MRF Facility Biofilter (BF_TIP) - 11:00 p.m. - 7:00 a.m. (Emissions Inside MRF Tipping Area)

Time Period	Emissions (g/s)						Area (m ²)	Night %
	CO	ROC	NOx	SOx	PM10	PM2.5		
11:00 p.m. - 7:00 a.m.	1.39E-02	6.13E-04	1.17E-02	4.47E-05	7.01E-08	7.01E-08	613.2	0.57

Emissions (g/s/m ²)						
CO	ROC	NOx	SOx	PM10	PM2.5	Area
2.11475E-05	1.08523E-05	1.90042E-05	7.29395E-08	1.14311E-10	1.14311E-10	613.2

BF_TIP | ROC Night % 0.57

Table 7-K Daily Emissions from AD Facility Biofilters (ADF1 & ADF2) - 8:00 a.m. - 4:00 p.m.

Time Period	Emissions (g/s)						Area (m ²)	Night %
	CO	ROC	NOx	SOx	PM10	PM2.5		
8:00 a.m. - 4:00 p.m.	1.20E-01	4.76E-03	1.02E-02	1.84E-04	5.10E-07	5.10E-07	838.0	0.55

Emissions (g/s/m ²)						
CO	ROC	NOx	SOx	PM10	PM2.5	Area
1.49982E-04	1.27209E-05	1.21627E-05	2.19226E-07	6.08037E-10	6.08037E-10	838.0

BF_ADF | ROC Night % 0.55

Table 7-L Annual Average Emissions from AD Facility Biofilters (ADF1 & ADF2) - 8:00 a.m. - 4:00 p.m.

Time Period	Emissions (g/s)						Area (m ²)	Night %
	CO	ROC	NOx	SOx	PM10	PM2.5		
8:00 a.m. - 4:00 p.m.	7.16E-02	2.71E-03	5.81E-03	1.05E-04	2.90E-07	2.90E-07	838.0	0.69

Emissions (g/s/m ²)						
CO	ROC	NOx	SOx	PM10	PM2.5	Area
8.54695E-05	1.02799E-05	6.92996E-06	1.24929E-07	3.46498E-10	3.46498E-10	838.0

BF_ADF | ROC Night % 0.69

Table 7-M Daily Emissions from MRF Facility Recycling Area Biofilter (BF_RECVC) - 7:00 a.m. - 11:00 p.m. (Emissions Inside MRF Recycling Area)

Time Period	Emissions (g/s)						Area (m ²)	Night %
	CO	ROC	NOx	SOx	PM10	PM2.5		
7:00 a.m. - 11:00 p.m.	5.30E-02	2.51E-03	4.76E-02	1.71E-04	2.87E-07	2.87E-07	429.2	0.29

Emissions (g/s/m ²)						
CO	ROC	NOx	SOx	PM10	PM2.5	Area
1.23539E-04	2.07747E-05	1.11015E-04	3.97448E-07	6.67761E-10	6.67761E-10	429.2

BF_RECVC | Night % 0.29

Table 7 Emission Rates for Dispersion Modeling

Table 7-N Annual Average Emissions from MRF Facility Recycling Area Biofilter (BF_RECYC) - 7:00 a.m. - 11:00 p.m. (Emissions inside MRF Recycling Area)

Time Period	Emissions (g/s)							Emissions (g/s/m ³)						
	CO	ROC	NOx	SOx	PM10	PM2.5	Area	CO	ROC	NOx	SOx	PM10	PM2.5	
7:00 a.m. - 11:00 p.m.	4.52E-03	2.14E-03	4.05E-02	1.45E-04	2.44E-07	2.44E-07	429.2	1.05259E-04	1.59102E-05	9.45911E-05	3.38648E-07	5.68969E-10	5.68969E-10	

BF_RECYC Night % 0.29

Table 7-O Daily Emissions from MRF Facility Recycling Area Biofilter (BF_RECYC) - 11:00 p.m. - 7:00 a.m. (Emissions inside MRF Recycling Area)

Time Period	Emissions (g/s)							Emissions (g/s/m ³)						
	CO	ROC	NOx	SOx	PM10	PM2.5	Area	CO	ROC	NOx	SOx	PM10	PM2.5	
11:00 p.m. - 7:00 a.m.	1.52E-02	7.20E-04	1.37E-02	5.25E-05	8.23E-08	8.23E-08	429.2	3.54564E-05	1.66387E-05	3.18628E-05	1.22292E-07	1.91656E-10	1.91656E-10	

BF_RECYC ROC Night % 0.80

Table 7-P Annual Average Emissions from MRF Facility Recycling Area Biofilter (BF_RECYC) - 11:00 p.m. - 7:00 a.m. (Emissions inside MRF Recycling Area)

Time Period	Emissions (g/s)							Emissions (g/s/m ³)						
	CO	ROC	NOx	SOx	PM10	PM2.5	Area	CO	ROC	NOx	SOx	PM10	PM2.5	
11:00 p.m. - 7:00 a.m.	1.30E-02	6.13E-04	1.17E-02	4.47E-05	7.01E-08	7.01E-08	429.2	3.02168E-05	1.63060E-05	2.71489E-05	1.04199E-07	1.63302E-10	1.63302E-10	

BF_RECYC ROC Night % 0.82

Table 7-Q Daily Emissions Outside MRF Facility Building (MRF_SWEEP)

Time Period	Emissions (g/s)							Emissions (g/s/m ³)						
	CO	ROC	NOx	SOx	PM10	PM2.5	Area	CO	ROC	NOx	SOx	PM10	PM2.5	
11:00 a.m. - 5:00 p.m.	1.92E-02	9.08E-04	1.73E-02	1.05E-04	1.04E-04	1.04E-04	12150.1	1.58011E-06	7.47349E-08	1.41994E-06	8.64011E-09	8.54113E-09	8.54113E-09	

MRF_SWEP1, MRF_SWEP2

Table 7-R Annual Average Hourly Emissions Outside MRF Facility Building (MRF_SWEEP)

Time Period	Emissions (g/s)							Emissions (g/s/m ³)						
	CO	ROC	NOx	SOx	PM10	PM2.5	Area	CO	ROC	NOx	SOx	PM10	PM2.5	
11:00 a.m. - 5:00 p.m.	1.64E-02	7.74E-04	1.47E-02	8.94E-05	8.84E-05	8.84E-05	12150.1	1.34634E-06	6.30782E-08	1.20989E-06	7.36184E-09	7.27751E-09	7.27751E-09	

MRF_SWEP1, MRF_SWEP2

Table 7-S Daily Emissions Outside AD Facility Building (AD_SWEEP)

Time Period	Emissions (g/s)							Emissions (g/s/m ³)						
	CO	ROC	NOx	SOx	PM10	PM2.5	Area	CO	ROC	NOx	SOx	PM10	PM2.5	
11:00 a.m. - 5:00 p.m.	1.92E-02	9.08E-04	1.73E-02	1.05E-04	1.04E-04	1.04E-04	3497.3	5.49E-06	2.60E-07	4.93E-06	3.00E-08	2.97E-08	2.97E-08	

AD_SWEEP

Table 7-T Annual Average Hourly Emissions Outside AD Facility Building (AD_SWEEP)

Time Period	Emissions (g/s)							Emissions (g/s/m ³)						
	CO	ROC	NOx	SOx	PM10	PM2.5	Area	CO	ROC	NOx	SOx	PM10	PM2.5	
11:00 a.m. - 5:00 p.m.	1.64E-02	7.74E-04	1.47E-02	8.94E-05	8.84E-05	8.84E-05	3497.3	4.677E-06	2.212E-07	4.203E-06	2.558E-08	2.528E-08	2.528E-08	

AD_SWEEP

Table 7-U Daily Exhaust Emissions from On-site Vehicles

Time Period	Segment	Emissions (g/s)							Emissions (g/s/volume)						
		CO	ROC	NOx	SOx	PM10	PM2.5	#	CO	ROC	NOx	SOx	PM10	PM2.5	
8:00 a.m. - 2:00 p.m.	MRF-Compost	2.48E-04	6.84E-05	1.94E-04	2.83E-06	6.07E-06	6.07E-06	49	5.05E-06	1.40E-06	3.97E-06	5.77E-09	7.29E-05	1.82E-05	
	MRF-Entrance	3.78E-03	1.22E-03	2.72E-03	3.10E-05	9.53E-05	9.34E-05	119	3.18E-05	1.02E-05	2.22E-05	2.61E-07	3.40E-04	8.72E-05	

Table 7-V Annual Average Exhaust Emissions from On-site Vehicles

Time Period	Segment	Emissions (g/s)							Emissions (g/s/volume)						
		CO	ROC	NOx	SOx	PM10	PM2.5	#	CO	ROC	NOx	SOx	PM10	PM2.5	
8:00 a.m. - 2:00 p.m.	MRF-Compost	2.11E-04	5.83E-05	1.66E-04	2.41E-06	5.17E-06	5.17E-06	49	4.31E-06	1.19E-06	3.38E-06	4.92E-08	6.21E-05	1.55E-05	
	MRF-Entrance	3.22E-03	1.04E-03	2.32E-03	2.64E-05	8.14E-05	7.95E-05	119	2.71E-05	8.74E-06	1.95E-05	2.22E-07	2.90E-04	7.43E-05	

Table 7-W Daily Emissions from AD 1.1MW CHP Engines

Time Period	Emissions, Each Engine (g/s)						
	CO	ROC	NOx	SOx	PM10	PM2.5	Area
12:00 a.m. - 12:00 a.m.	1.31E-01	5.24E-02	5.24E-02	9.79E-03	5.16E-02	5.16E-02	165-166

ADCHP1, ADCHP2

Table 7-Y Annual Average Hourly Emissions from AD 1.1MW CHP Engines

Time Period	Emissions, Each Engine (g/s)						
	CO	ROC	NOx	SOx	PM10	PM2.5	Area
12:00 a.m. - 12:00 a.m.	1.26E-01	5.01E-02	5.15E-02	9.24E-03	4.90E-02	4.90E-02	165-166

ADCHP1, ADCHP2

Table 7-Z Daily Emissions from AD Flare, Purging Only

Time Period	Emissions (g/s)						
	CO	ROC	NOx	SOx	PM10	PM2.5	Area
1 hour, everyday	3.11E-02	4.20E-04	1.24E-02	8.89E-03	6.53E-03	6.53E-03	ADFLARE

ADFLARE

Table 7-AA Daily Emissions from AD Flare, Purging and One AD 1.1 MW CHP Engine Off-line

Time Period	Emissions (g/s)						
	CO	ROC	NOx	SOx	PM10	PM2.5	Area
12:00 a.m. - 12:00 a.m.	2.50E-01	3.38E-03	1.02E-01	7.15E-02	5.25E-02	5.25E-02	ADFLARE

ADFLARE

Table 7 Emission Rates for Dispersion Modeling

Table 7-AB Daily Emissions from CHP Engine during SCR Start-Up (1 engine)

Time Period	Emissions, Each Engine (g/s)					
	CO	ROC	NOx	SOx	PM10	PM2.5
12:00 a.m. - 12:00 a.m.	7.21E-01	1.20E-01	1.57E-01	4.43E-03	5.16E-02	5.16E-03

ADCHP1, ADCHP2

Table 7-AC Daily Emissions from CHP Engine during SCR Burn-in (1 engine)

Time Period	Emissions, Each Engine (g/s)					
	CO	ROC	NOx	SOx	PM10	PM2.5
12:00 a.m. - 12:00 a.m.	1.31E-01	5.24E-02	1.57E-01	8.30E-04	5.16E-02	5.16E-03

ADCHP1, ADCHP2

Table 7-AD Annual Average Hourly Emissions from Flare

Time Period	Emissions (g/s)					
	CO	ROC	NOx	SOx	PM10	PM2.5
12:00 a.m. - 12:00 a.m.	2.59E-02	3.49E-04	1.04E-02	7.40E-03	5.43E-03	5.43E-03

ADFLARE

Table 7-AE Daily Emissions from Compost Area (Loader Exhaust, Material Transfers)

Time Period	Emissions (g/s)						Area (m ²)
	CO	ROC	NOx	SOx	PM10	PM2.5	
8:00 a.m. - 4:00 p.m.	6.28E-02	2.38E-03	5.10E-03	7.09E-05	9.64E-04	1.46E-04	1412.1

Table 7-AF Annual Average Hourly Emissions from Compost Area (Loader Exhaust, Material Transfers)

Time Period	Emissions (g/s)						Area (m ²)
	CO	ROC	NOx	SOx	PM10	PM2.5	
8:00 a.m. - 4:00 p.m.	5.35E-02	2.02E-03	4.34E-03	6.04E-05	8.22E-04	1.25E-04	1412.1

Table 7-AG Daily Exhaust Emissions from Windrow Turner

Time Period	Emissions (g/s)						Area (m ²)
	CO	ROC	NOx	SOx	PM10	PM2.5	
8:00 a.m. - 4:00 p.m.	6.71E-02	3.61E-03	7.74E-03	3.15E-04	3.87E-04	3.87E-04	18175.7

Table 7-AH Annual Average Hourly Emissions from Windrow Turner Exhaust

Time Period	Emissions (g/s)						Area (m ²)
	CO	ROC	NOx	SOx	PM10	PM2.5	
8:00 a.m. - 4:00 p.m.	9.56E-03	5.15E-04	1.10E-03	4.48E-05	5.51E-05	5.51E-05	18175.7

Table 7-AI Daily Fugitive PM Emissions from On-site Vehicles

Time Period	Segment	Emissions (g/s)		#	Emissions (g/s/vol)	
		PM10	PM2.5		PM10	PM2.5
8:00 a.m. - 2:00 p.m.	MRF-Compost	3.56E-03	8.65E-04	49	7.27E-05	1.81E-05
	MRF-Entrance	4.02E-02	1.01E-02	119	3.38E-04	8.53E-05

Table 7-AJ Annual Average Fugitive PM Emissions from On-site Vehicles

Time Period	Segment	Emissions (g/s)		#	Emissions (g/s/vol)	
		PM10	PM2.5		PM10	PM2.5
8:00 a.m. - 2:00 p.m.	MRF-Compost	3.04E-03	7.54E-04	49	6.20E-05	1.54E-05
	MRF-Entrance	3.43E-02	8.65E-03	119	2.88E-04	7.27E-05

Emissions (g/s/m³) for CDMPMAT Source

CO	ROC	NOx	SOx	PM10	PM2.5
4.45030E-05	1.68390E-08	3.60835E-05	5.01808E-08	6.82952E-07	1.03572E-07

Emissions (g/s/m³) for CDMPMAT Source

CO	ROC	NOx	SOx	PM10	PM2.5
3.79190E-05	1.43477E-06	3.07451E-05	4.27568E-08	5.81912E-07	8.82486E-08

Emissions (g/s/m³) for WINDROW Source

CO	ROC	NOx	SOx	PM10	PM2.5
3.69126E-06	1.98705E-07	4.25914E-07	1.73272E-08	5.03304E-06	7.80217E-07

Emissions (g/s/m³) for WINDROW Source

CO	ROC	NOx	SOx	PM10	PM2.5
5.26878E-07	2.83165E-08	6.06762E-08	2.46854E-09	7.74228E-07	1.19815E-07

Night %
0.95

Table 7 Emission Rates for Dispersion Modeling

Table 7-AK Daily Fugitive PM Emissions from Windrow Area Material Transfers

Time Period	Activity	Emissions (g/s)		SCREEN
		PM10	PM2.5	
8:00 a.m. - 4:00 p.m.	Digestate to Windrow	1.68E-03	2.54E-04	WINDROW
8:00 a.m. - 4:00 p.m.	Windrow Turning	8.94E-02	1.35E-02	

Table 7-AL Annual Average Hourly Fugitive PM Emissions from Windrow Area Material Transfers

Time Period	Activity	Emissions (g/s)		SCREEN
		PM10	PM2.5	
8:00 a.m. - 4:00 p.m.	Digestate to Windrow	1.28E-03	1.94E-04	WINDROW
8:00 a.m. - 4:00 p.m.	Windrow Turning	1.27E-02	1.93E-03	

Table 7-AM Daily Fugitive PM Emissions from Compost Screening

Time Period	Emissions (g/s)		SCREEN
	PM10	PM2.5	
8:00 a.m. - 4:00 p.m.	1.93E-03	2.11E-04	SCREEN

Table 7-AN Annual Average Hourly Fugitive PM Emissions from Compost Screen

Time Period	Emissions (g/s)		SCREEN
	PM10	PM2.5	
8:00 a.m. - 4:00 p.m.	1.64E-03	1.89E-04	SCREEN

Table 7-AO Daily Fugitive PM Emissions from Chipper/Grinder

Time Period	Emissions (g/s)		CHIPPER
	PM10	PM2.5	
7:00 a.m. - 8:30 a.m.	8.26E-02	8.26E-02	CHIPPER

Table 7-AP Annual Average Hourly Fugitive PM Emissions from Chipper/Grinder

Time Period	Emissions (g/s)		CHIPPER
	PM10	PM2.5	
7:00 a.m. - 8:30 a.m.	7.03E-02	7.03E-02	CHIPPER

Table 7 Emission Rates for Dispersion Modeling

Table 7-AQ Daily Emissions from 1.4 MW MRF CHP Engines

Time Period	Emissions, Each Engine (g/s)						
	CO	ROC	NOx	SOx	PM10	PM2.5	
12:00 a.m. - 12:00 a.m.	1.09E-01	6.23E-02	6.55E-02	1.04E-02	6.44E-02	6.44E-02	MRFCHP1, 2
	2.18E-01	1.25E-01	1.31E-01	2.08E-02	1.29E-03	1.29E-03	PAPERDRY (2 Engines) * 99% Eff Baghouses

Table 7-AR Annual Average Hourly Emissions from 1.4MW MRF CHP Engines

Time Period	Emissions, Each Engine (g/s)						
	CO	ROC	NOx	SOx	PM10	PM2.5	
12:00 a.m. - 12:00 a.m.	1.16E-01	6.05E-02	6.43E-02	1.00E-02	6.12E-02	6.12E-02	MRFCHP1, 2
	2.32E-01	1.21E-01	1.29E-01	2.00E-02	1.22E-03	1.22E-03	PAPERDRY (2 Engines) * 99% Eff Baghouses

Table 7-AS Daily Emissions from 1.4MW MRF CHP Engine during SCR Start-Up (1 engine)

Time Period	Emissions, Each Engine (g/s)						
	CO	ROC	NOx	SOx	PM10	PM2.5	
12:00 a.m. - 12:00 a.m.	8.74E-01	1.49E-01	1.97E-01	6.24E-03	6.44E-02	6.44E-02	MRFCHP1-2 (1 Engine in any hour)
	9.83E-01	2.11E-01	2.62E-01	1.66E-02	1.29E-03	1.29E-03	PAPERDRY (2 Engines) * 99% Eff Baghouses

Table 7-AT Daily Emissions from 1.4 MW MRF CHP Engine during SCR Burn-In (1 engine)

Time Period	Emissions, Each Engine (g/s)						
	CO	ROC	NOx	SOx	PM10	PM2.5	
12:00 a.m. - 12:00 a.m.	8.74E-01	1.49E-01	1.97E-01	5.29E-03	6.44E-02	6.44E-02	MRFCHP1-2 (1 Engine in any hour)
	9.83E-01	2.11E-01	2.62E-01	1.57E-02	1.29E-03	1.29E-03	PAPERDRY (2 Engines) * 99% Eff Baghouses

Table 7-AU Maximum Hourly Emissions from MRF Flare

Time Period	Emissions, Each Engine (g/s)						
	CO	ROC	NOx	SOx	PM10	PM2.5	
12:00 a.m. - 12:00 a.m.	3.10E-01	4.19E-03	1.24E-01	1.04E-02	6.52E-02	6.52E-02	MRFFLAR1

Table 7-AV Annual Average Hourly Emissions from MRF Flare

Time Period	Emissions (g/s)						
	CO	ROC	NOx	SOx	PM10	PM2.5	
12:00 a.m. - 12:00 a.m.	3.10E-02	4.19E-04	1.24E-02	1.04E-03	6.52E-03	6.52E-03	MRFFLAR1

e

e

e

e

Table 6a

CHP Engine Emissions with biogas/natural gas

Normal Operation, Both Engines Operating

Type	Engine Rating (hp)	Fuel Input @ Full Load (scfh) ^a	Heat Input @ Full Load (MMBtu/hr)	Number Engines	Daily Op. (hr/day)	Emission Factors (normal operation)									
						CO (g/bhp-hr) ^b	ROC (g/bhp-hr) ^b	NOx (g/bhp-hr) ^b	SOx (g/scf) ^c	PM10 (g/bhp-hr) ^d	PM2.5 (g/bhp-hr) ^d	Combust. CO ₂ (g/MMBtu) ^e	CH ₄ (g/MMBtu) ^f	N ₂ O (g/MMBtu) ^f	Pass-through CO ₂ (g/scf) ^g
Jenbacher/GE JMS416vB82	1,573	15,150	9.88	2	24	0.3	0.12	0.12	0.00135	0.118	0.118	53,020	1.0	0.10	18.47

Fuel heating value = 652 Btu/scf Based on Mustang estimate of 86.5% biogas at 587 Btu/scf and 13.5% natural gas at 1070 Btu/scf

Fuel sulfur = 18 ppmv Based on Mustang estimate of 86.5% biogas at 20 ppmv and 13.5% natural gas at 4.3 ppmv

Fuel CO₂ fraction = 0.357 Based on Mustang estimate of 86.5% biogas at 0.41 and 13.5% natural gas at 0.0154

^a Fuel input at full load [scfh] = Heat input at full load [MMBtu/hr] x 10⁶ [Btu/MMBtu] / Fuel heating value [Btu/scf]

^b Control system vendor specifications

^c SOx emission factor [g/scf] = Fuel sulfur [ppmv] x 10⁻⁶ x 64 [lb/lb-mole SO₂] / 385.5 [scf/lb-mole] x 453.6 g/lb

^d Bekon estimate for filterable PM is 0.09 g/bhp-hr. Filterable PM10 and PM2.5 assumed equal to filterable PM

Condensable PM emission factor for 4-stroke lean-burn natural gas fired engines from AP-42, Section 3.2 (Natural Gas-fired Reciprocating Internal Combustion Engines, 7/2000), Table 3.2-2

is 9.91 x 10⁻³ lb/MMBtu = 9.91 x 10⁻³ lb/MMBtu x 9.88 MMBtu/hr heat input / 1,573 hp engine rating x 453.6 g/lb = 0.0282 g/bhp-hr.

Total PM10 and PM2.5 emission factor = 0.09 g/bhp-hr filterable + 0.0282 g/bhp-hr condensable = 0.118 g/bhp-hr.

^e From Table C-1 of Title 40, Code of Federal Regulations, Subpart 98 for natural gas. Biogas assumed same as natural gas because heat content is primarily from methane. Does not include "pass-through" CO₂ from fuel.

^f From Table C-2 of Title 40, Code of Federal Regulations, Subpart 98 for natural gas. Biogas assumed same as natural gas because heat content is primarily from methane. Does not include "pass-through" CO₂ from fuel.

^g "Pass-through" CO₂ emission factor [g/scf] = Fuel CO₂ volume fraction [unitless] x 44 [lb/lb-mole CO₂] / 385.5 [scf/lb-mole] x 453.6 g/lb

Normal Operation, One Engine Operating and One Engine Down

Type	Engine Rating (hp)	Fuel Input @ Full Load (scfh) ^a	Heat Input @ Full Load (MMBtu/hr)	Number Engines	Daily Op. (hr/day)	Emission Factors (normal operation)									
						CO (g/bhp-hr) ^b	ROC (g/bhp-hr) ^b	NOx (g/bhp-hr) ^b	SOx (g/scf) ^c	PM10 (g/bhp-hr) ^d	PM2.5 (g/bhp-hr) ^d	Combust. CO ₂ (g/MMBtu) ^e	CH ₄ (g/MMBtu) ^f	N ₂ O (g/MMBtu) ^f	Pass-through CO ₂ (g/scf) ^g
Jenbacher/GE JMS416vB82	1,573	16,828	9.88	1	24	0.3	0.12	0.12	0.00151	0.118	0.118	53,020	1.0	0.10	21.23

Fuel heating value = 587 Btu/scf Based on Mustang estimate for 100% biogas

Fuel sulfur = 20 ppmv Based on Mustang estimate for 100% biogas

Fuel CO₂ fraction = 0.410 Based on Mustang estimate for 100% biogas

^a Fuel input at full load [scfh] = Heat input at full load [MMBtu/hr] x 10⁶ [Btu/MMBtu] / Biogas heating value [Btu/scf]

^b Control system vendor specifications

^c SOx emission factor [g/scf] = Fuel sulfur [ppmv] x 10⁻⁶ x 64 [lb/lb-mole SO₂] / 385.5 [scf/lb-mole] x 453.6 g/lb

^d Bekon estimate for filterable PM is 0.09 g/bhp-hr. Filterable PM10 and PM2.5 assumed equal to filterable PM

Condensable PM emission factor for 4-stroke lean-burn natural gas fired engines from AP-42, Section 3.2 (Natural Gas-fired Reciprocating Internal Combustion Engines, 7/2000), Table 3.2-2

is 9.91 x 10⁻³ lb/MMBtu = 9.91 x 10⁻³ lb/MMBtu x 9.88 MMBtu/hr heat input / 1,573 hp engine rating x 453.6 g/lb = 0.0282 g/bhp-hr.

Total PM10 and PM2.5 emission factor = 0.09 g/bhp-hr filterable + 0.0282 g/bhp-hr condensable = 0.118 g/bhp-hr.

^e From Table C-1 of Title 40, Code of Federal Regulations, Subpart 98 for natural gas. Biogas assumed same as natural gas because heat content is primarily from methane. Does not include "pass-through" CO₂ from fuel.

^f From Table C-2 of Title 40, Code of Federal Regulations, Subpart 98 for natural gas. Biogas assumed same as natural gas because heat content is primarily from methane. Does not include "pass-through" CO₂ from fuel.

^g "Pass-through" CO₂ emission factor [g/scf] = Fuel CO₂ volume fraction [unitless] x 44 [lb/lb-mole CO₂] / 385.5 [scf/lb-mole] x 453.6 g/lb

Table 8a CHP Engine Emissions with biogas/natural gas

Start-up

Fuel Input @ Full Load (scfh) ^a	Heat Input @ Full Load (MMBtu/hr)	Emission Factors (start-up)									
		CO (g/bhp-hr) ^b	ROC (g/bhp-hr) ^b	NOx (g/bhp-hr) ^b	SOx (g/scf) ^d	PM10 (g/bhp-hr) ^c	PM2.5 (g/bhp-hr) ^c	Combust. CO ₂ (g/MMBtu) ^e	CH ₄ (g/MMBtu) ^e	N ₂ O (g/MMBtu) ^e	Pass-through CO ₂ (g/scf) ^e
9,232	9.88	3	0.43	0.6	0.0032	0.11800	0.11800	53.020	1.0	0.10	0.80

Fuel heating value = 1,070 Btu/scf Based on 100% natural gas
 Fuel sulfur = 4.3 ppmv Based on 100% natural gas at 0.5 grains/100 scf
 Fuel CO₂ fraction = 0.0154 Based on 100% natural gas

^a Fuel input at full load [scfh] = Heat input at full load [MMBtu/hr] x 10⁶ [Btu/MMBtu] / Biogas heating value [Btu/scf]
^b Engine vendor specification
^c Same as during normal operation
^d SOx emission factor [g/scf] = Fuel sulfur [ppmv] x 10⁻⁶ x 64 [lb/lb-mole SO₂] / 385.5 [scf/lb-mole] x 453.6 g/lb
^e *Pass-through* CO₂ emission factor [g/scf] = Fuel CO₂ volume fraction [unitless] x 44 [lb/lb-mole CO₂] / 385.5 [scf/lb-mole] x 453.6 g/lb

Catalyst Burn-in

Fuel Input @ Full Load (scfh) ^a	Heat Input @ Full Load (MMBtu/hr)	Emission Factors (SCR catalyst burn-in)									
		CO (g/bhp-hr) ^b	ROC (g/bhp-hr) ^b	NOx (g/bhp-hr) ^c	SOx (g/scf) ^d	PM10 (g/bhp-hr) ^b	PM2.5 (g/bhp-hr) ^b	Combust. CO ₂ (g/MMBtu) ^e	CH ₄ (g/MMBtu) ^e	N ₂ O (g/MMBtu) ^e	Pass-through CO ₂ (g/scf) ^e
9,232	9.88	0.3	0.12	0.36	0.0032	0.11800	0.11800	53.020	1.0	0.10	0.80

Fuel heating value = 1,070 Btu/scf Based on 100% natural gas
 Fuel sulfur = 4.3 ppmv Based on 100% natural gas at 0.5 grains/100 scf
 Fuel CO₂ fraction = 0.0154 Based on 100% natural gas

^a Fuel input at full load [scfh] = Heat input at full load [MMBtu/hr] x 10⁶ [Btu/MMBtu] / Biogas heating value [Btu/scf]
^b Same as during normal operation
^c Based on average of 50 percent of normal NOx control efficiency
^d SOx emission factor [g/scf] = Fuel sulfur [ppmv] x 10⁻⁶ x 64 [lb/lb-mole SO₂] / 385.5 [scf/lb-mole] x 453.6 g/lb
^e *Pass-through* CO₂ emission factor [g/scf] = Fuel CO₂ volume fraction [unitless] x 44 [lb/lb-mole CO₂] / 385.5 [scf/lb-mole] x 453.6 g/lb

Hourly Emissions per Engine, Normal Operation, Both Engines Operating (lb/hr) ^a										
CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂	
1.04	0.42	0.42	0.04	0.41	0.41	1.15E+03	2.18E-02	2.18E-03	6.17E+02	

^a Except for SOx, CO₂, CH₄ and N₂O, Hourly emissions [lb/hr] = Engine rating [hp] x Emission factor [g/bhp-hr] / 453.6 [g/lb]
 SOx and pass-through CO₂ hourly emissions [lb/hr] = Biogas input [scfh] x Emission factor [g/scf] / 453.6 [g/lb]
 Combustion CO₂, CH₄ and N₂O hourly emissions [lb/hr] = Heat input [MMBtu/hr] x Emission factor [g/MMBtu] / 453.6 [g/lb]

Hourly Emissions per Engine, Normal Operation, One Engine Operating and One Engine Down (lb/hr) ^a										
CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂	
1.04	0.42	0.42	0.09	0.41	0.41	1.15E+03	2.18E-02	2.18E-03	7.87E+02	

^a Except for SOx, CO₂, CH₄ and N₂O, Hourly emissions [lb/hr] = Engine rating [hp] x Emission factor [g/bhp-hr] / 453.6 [g/lb]
 SOx and pass-through CO₂ hourly emissions [lb/hr] = Biogas input [scfh] x Emission factor [g/scf] / 453.6 [g/lb]
 Combustion CO₂, CH₄ and N₂O hourly emissions [lb/hr] = Heat input [MMBtu/hr] x Emission factor [g/MMBtu] / 453.6 [g/lb]

Table 8a CHP Engine Emissions with biogas/natural gas

Hourly Emissions per Engine, Start-Up (lb/hr) ^a										
CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂	
5.72	0.95	1.25	0.03	0.41	0.41	1.15E+03	2.18E-02	2.18E-03	3.25E+02	

^a Start-up is 30 minutes with no CO, ROC or NOx control by SCR/catalyst system. Emissions are for one-hour period that includes 30-minute start-up

Hourly Emissions per Engine, SCR Catalyst Burn-In (lb/hr) ^a										
CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂	
1.04	0.42	1.25	0.01	0.41	0.41	1.15E+03	2.18E-02	2.18E-03	1.62E+01	

Daily Emissions, both Engines Normal Operation (lb/day) ^a										
CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂	
49.94	19.97	19.97	2.16	19.64	19.64	5.54E+04	1.05E+00	1.05E-01	2.96E+04	

^a Daily emissions [lb/day] = Number engines x Daily operating time [hr/day] x Hourly emissions [lb/hr]

Daily Emissions, One Engine Normal Operation (lb/day) ^a										
CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂	
24.97	9.99	9.99	1.34	9.82	9.82	2.77E+04	5.23E-01	5.23E-02	1.89E+04	

^a Daily emissions [lb/day] = Number engines x Daily operating time [hr/day] x Hourly emissions [lb/hr]

Daily Emissions, both Engines Normal Operation plus one Start-up for One Engine (lb/day) ^a										
CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂	
54.62	20.51	20.81	2.14	19.64	19.64	5.54E+04	1.05E+00	1.05E-01	2.93E+04	

Annual Op. (hr/year-engine)	Annual Emissions, both Engines (lb/year) ^c										
	CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂	
Start-Up ^a	18	205.99	34.33	44.94	1.05	14.73	14.73	4.16E+04	7.84E-01	7.84E-02	1.17E+04
SCR Catalyst Burn-In ^b	120	249.68	99.87	299.62	1.58	98.21	98.21	2.77E+05	5.23E+00	5.23E-01	3.89E+03
Normal Operation, Both Eng. ^b	7,746	16,117.01	6,446.80	6,446.80	696.73	6,339.36	6,339.36	1.79E+07	3.37E+02	3.37E+01	9.56E+06
Normal Operation, One Eng. ^b	438	911.34	364.54	364.54	48.95	358.46	358.46	1.01E+06	1.91E+01	1.91E+00	6.90E+05
Total	8,322	17,484.02	6,945.54	7,155.90	748.30	6,810.76	6,810.76	1.92E+07	3.62E+02	3.62E+01	1.03E+07

^a Mustang estimate

^b Based on each engine operating 95% of the time, excluding start-up hours and SCR catalyst burn-in, with 5% downtime for maintenance or other reasons.

^c Annual emissions [lb/year] = Operating time [hr/year-engine] x Hourly emissions at full load [lb/hr-engine] x Number engines

Table 8b CHP Engine Emissions with biogas/propane

Normal Operation, Both Engines Operating

Type	Engine Rating (hp)	Fuel Input @ Full Load (scfh) ^a	Heat Input @ Full Load (MMBtu/hr)	Number Engines	Daily Op. (hr/day)	Emission Factors (normal operation)									
						CO (g/bhp-hr) ^b	ROC (g/bhp-hr) ^b	NOx (g/bhp-hr) ^b	SOx (g/scf) ^c	PM10 (g/bhp-hr) ^d	PM2.5 (g/bhp-hr) ^d	Combust. CO ₂ (g/MMBtu) ^e	CH ₄ (g/MMBtu) ^f	N ₂ O (g/MMBtu) ^f	Pass-through CO ₂ (g/scf) ^g
Jenbacher/GE JMS416vB82	1,573	11,704	9.88	2	24	0.3	0.12	0.12	0.00301	0.118	0.118	54,193	1.27	0.17	18.36

Fuel heating value = 844 Btu/scf Based on Mustang estimate of 86.5% biogas at 587 Btu/scf and 13.5% propane at 2,488 Btu/scf
 Fuel sulfur = 40 ppmv Based on Mustang estimate of 86.5% biogas at 20 ppmv and 13.5% propane at 168.1 ppmv
 Fuel CO₂ factor = 54,193 g/MMBtu Based on Mustang estimate of 86.5% biogas at and 13.5% propane^e
 Fuel CH₄ factor = 1.27 g/MMBtu Based on Mustang estimate of 86.5% biogas at and 13.5% propane^f
 Fuel N₂O factor = 0.17 g/MMBtu Based on Mustang estimate of 86.5% biogas at and 13.5% propane^f
 Fuel pass-through CO₂ fraction = 0.355 Based on Mustang estimate of 86.5% biogas at 0.41 and 13.5% propane at 0

^a Fuel input at full load [scfh] = Heat input at full load [MMBtu/hr] x 10⁶ [Btu/MMBtu] / Fuel heating value [Btu/scf]

^b Control system vendor specifications

^c SOx emission factor [g/scf] = Fuel sulfur [ppmv] x 10⁶ x 64 [lb/lb-mole SO₂] / 385.5 [scf/lb-mole] x 453.6 g/lb

^d Bekon estimate for filterable PM is 0.09 g/bhp-hr based on firing biogas and natural gas. Assumed similar for firing biogas and propane. Filterable PM10 and PM2.5 assumed equal to filterable PM.

Condensable PM emission factor for 4-stroke lean-burn natural gas fired engines from AP-42, Section 3.2 (Natural Gas-fired Reciprocating Internal Combustion Engines, 7/2000), Table 3.2-2

is 9.91 x 10⁻³ lb/MMBtu = 9.91 x 10⁻³ lb/MMBtu x 9.88 MMBtu/hr heat input / 1,573 hp engine rating x 453.6 g/lb = 0.0282 g/bhp-hr.

Total PM10 and PM2.5 emission factor = 0.09 g/bhp-hr filterable + 0.0282 g/bhp-hr condensable = 0.0118 g/bhp-hr.

^e From Table C-1 of Title 40, Code of Federal Regulations, Subpart 98. Biogas assumed same as natural gas because heat content is primarily from methane. Does not include "pass-through" CO₂ from fuel.

Propane based on Liquefied Petroleum Gases (LPG) fuel type.

^f From Table C-2 of Title 40, Code of Federal Regulations, Subpart 98. Biogas assumed same as natural gas because heat content is primarily from methane. Propane based on Petroleum fuel type.

^g "Pass-through" CO₂ emission factor [g/scf] = Fuel CO₂ volume fraction [unitless] x 44 [lb/lb-mole CO₂] / 385.5 [scf/lb-mole] x 453.6 g/lb

Normal Operation, One Engine Operating and One Engine Down

Type	Engine Rating (hp)	Fuel Input @ Full Load (scfh) ^a	Heat Input @ Full Load (MMBtu/hr)	Number Engines	Daily Op. (hr/day)	Emission Factors (normal operation)									
						CO (g/bhp-hr) ^b	ROC (g/bhp-hr) ^b	NOx (g/bhp-hr) ^b	SOx (g/scf) ^c	PM10 (g/bhp-hr) ^d	PM2.5 (g/bhp-hr) ^d	Combust. CO ₂ (g/MMBtu) ^e	CH ₄ (g/MMBtu) ^f	N ₂ O (g/MMBtu) ^f	Pass-through CO ₂ (g/scf) ^g
Jenbacher/GE JMS416vB82	1,573	16,828	9.88	1	24	0.3	0.12	0.12	0.00151	0.118	0.118	53,020	1.0	0.10	21.23

Fuel heating value = 587 Btu/scf Based on Mustang estimate for 100% biogas

Fuel sulfur = 20 ppmv Based on Mustang estimate for 100% biogas

Fuel CO₂ fraction = 0.410 Based on Mustang estimate for 100% biogas

^a Fuel input at full load [scfh] = Heat input at full load [MMBtu/hr] x 10⁶ [Btu/MMBtu] / Biogas heating value [Btu/scf]

^b Control system vendor specifications

^c SOx emission factor [g/scf] = Fuel sulfur [ppmv] x 10⁶ x 64 [lb/lb-mole SO₂] / 385.5 [scf/lb-mole] x 453.6 g/lb

^d Bekon estimate for filterable PM is 0.09 g/bhp-hr. Filterable PM10 and PM2.5 assumed equal to filterable PM

Condensable PM emission factor for 4-stroke lean-burn natural gas fired engines from AP-42, Section 3.2 (Natural Gas-fired Reciprocating Internal Combustion Engines, 7/2000), Table 3.2-2

is 9.91 x 10⁻³ lb/MMBtu = 9.91 x 10⁻³ lb/MMBtu x 9.88 MMBtu/hr heat input / 1,573 hp engine rating x 453.6 g/lb = 0.0282 g/bhp-hr.

Total PM10 and PM2.5 emission factor = 0.09 g/bhp-hr filterable + 0.0282 g/bhp-hr condensable = 0.0118 g/bhp-hr.

^e From Table C-1 of Title 40, Code of Federal Regulations, Subpart 98 for natural gas. Biogas assumed same as natural gas because heat content is primarily from methane. Does not include "pass-through" CO₂ from fuel.

^f From Table C-2 of Title 40, Code of Federal Regulations, Subpart 98 for natural gas. Biogas assumed same as natural gas because heat content is primarily from methane. Does not include "pass-through" CO₂ from fuel.

^g "Pass-through" CO₂ emission factor [g/scf] = Fuel CO₂ volume fraction [unitless] x 44 [lb/lb-mole CO₂] / 385.5 [scf/lb-mole] x 453.6 g/lb

Table 8b CHP Engine Emissions with biogas/propane

Start-up

Fuel Input @ Full Load (scfh) ^a	Heat Input @ Full Load (MMBtu/hr)	Emission Factors (start-up)										
		CO (g/bhp-hr) ^b	ROC (g/bhp-hr) ^b	NOx (g/bhp-hr) ^b	SOx (g/scf) ^d	PM10 (g/bhp-hr) ^c	PM2.5 (g/bhp-hr) ^c	Combust. CO ₂ (g/MMBtu) ^e	CH ₄ (g/MMBtu) ^f	N ₂ O (g/MMBtu) ^f	Pass-through CO ₂ (g/scf) ^g	
3,970	9.88	3	0.86	0.6	0.01266	0.11800	0.11800	61.710	3.0	0.60	0.00	

Fuel heating value = 2,488 Btu/scf Based on 100% propane
 Fuel sulfur = 168.1 ppmv Based on 100% propane at 123 ppmw
 Fuel CO₂ fraction = 0 Based on 100% propane

^a Fuel input at full load [scfh] = Heat input at full load [MMBtu/hr] x 10⁶ [Btu/MMBtu] / Biogas heating value [Btu/scf]
^b Engine vendor specification for natural gas fuel, assumed same for propane fuel except double for uncontrolled ROC.
^c Same as during normal operation
^d SOx emission factor [g/scf] = Fuel sulfur [ppmv] x 10⁻⁶ x 64 [lb/lb-mole SO₂] / 385.5 [scf/lb-mole] x 453.6 g/lb
^e From Table C-1 of Title 40, Code of Federal Regulations, Subpart 98. Propane based on Liquefied Petroleum Gases (LPG) fuel type.
^f From Table C-2 of Title 40, Code of Federal Regulations, Subpart 98. Propane based on Petroleum fuel type.
^g "Pass-through" CO₂ not expected with 100% propane/LPG fuel

Catalyst Burn-in

Fuel Input @ Full Load (scfh) ^a	Heat Input @ Full Load (MMBtu/hr)	Emission Factors (SCR catalyst burn-in)										
		CO (g/bhp-hr) ^b	ROC (g/bhp-hr) ^b	NOx (g/bhp-hr) ^c	SOx (g/scf) ^d	PM10 (g/bhp-hr) ^e	PM2.5 (g/bhp-hr) ^e	Combust. CO ₂ (g/MMBtu) ^f	CH ₄ (g/MMBtu) ^f	N ₂ O (g/MMBtu) ^f	Pass-through CO ₂ (g/scf) ^g	
3,970	9.88	0.31	0.12	0.36	0.01266	0.11800	0.11800	61.710	3.0	0.60	0.00	

Fuel heating value = 2,488 Btu/scf Based on 100% propane
 Fuel sulfur = 168.1 ppmv Based on 100% propane at 123 ppmw
 Fuel CO₂ fraction = 0 Based on 100% propane

^a Fuel input at full load [scfh] = Heat input at full load [MMBtu/hr] x 10⁶ [Btu/MMBtu] / Biogas heating value [Btu/scf]
^b Same as during normal operation
^c Based on average of 50 percent of normal NOx control efficiency
^d SOx emission factor [g/scf] = Fuel sulfur [ppmv] x 10⁻⁶ x 64 [lb/lb-mole SO₂] / 385.5 [scf/lb-mole] x 453.6 g/lb
^e From Table C-1 of Title 40, Code of Federal Regulations, Subpart 98. Propane based on Liquefied Petroleum Gases (LPG) fuel type.
^f From Table C-2 of Title 40, Code of Federal Regulations, Subpart 98. Propane based on Petroleum fuel type.
^g "Pass-through" CO₂ not expected with 100% propane/LPG fuel

Hourly Emissions per Engine, Normal Operation, Both Engines Operating (lb/hr)^a

CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂
1.04	0.42	0.42	0.08	0.41	0.41	1.18E+03	2.77E-02	3.65E-03	4.74E+02

^a Except for SOx, CO₂, CH₄ and N₂O, Hourly emissions [lb/hr] = Engine rating [hp] x Emission factor [g/bhp-hr] / 453.6 [g/lb]
 SOx and pass-through CO₂ hourly emissions [lb/hr] = Biogas input [scfh] x Emission factor [g/scf] / 453.6 [g/lb]
 Combustion CO₂, CH₄ and N₂O hourly emissions [lb/hr] = Heat input [MMBtu/hr] x Emission factor [g/MMBtu] / 453.6 [g/lb]

Hourly Emissions per Engine, Normal Operation, One Engine Operating and One Engine Down (lb/hr)^a

CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂
1.04	0.42	0.42	0.06	0.41	0.41	1.15E+03	2.18E-02	2.18E-03	7.87E+02

^a Except for SOx, CO₂, CH₄ and N₂O, Hourly emissions [lb/hr] = Engine rating [hp] x Emission factor [g/bhp-hr] / 453.6 [g/lb]
 SOx and pass-through CO₂ hourly emissions [lb/hr] = Biogas input [scfh] x Emission factor [g/scf] / 453.6 [g/lb]
 Combustion CO₂, CH₄ and N₂O hourly emissions [lb/hr] = Heat input [MMBtu/hr] x Emission factor [g/MMBtu] / 453.6 [g/lb]

Table 8b CHP Engine Emissions with biogas/propane

Hourly Emissions per Engine, Start-Up (lb/hr) ^a										
CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂	
5.72	1.70	1.25	0.15	0.41	0.41	1.18E+03	2.77E-02	3.65E-03	2.37E+02	

^a Start-up is 30 minutes with no CO, ROC or NOx control by SCR/catalyst system. Emissions are for one-hour period that includes 30-minute start-up

Hourly Emissions per Engine, SCR Catalyst Burn-In (lb/hr) ^a										
CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂	
1.04	0.42	1.25	0.11	0.41	0.41	1.18E+03	2.77E-02	3.65E-03	0.00E+00	

Daily Emissions, both Engines Normal Operation (lb/day) ^a										
CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂	
49.94	19.97	19.97	3.73	19.64	19.64	5.66E+04	1.33E+00	1.75E-01	2.27E+04	

^a Daily emissions [lb/day] = Number engines x Daily operating time [hr/day] x Hourly emissions [lb/hr]

Daily Emissions, One Engine Normal Operation (lb/day) ^a										
CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂	
24.97	9.99	9.99	1.34	9.82	9.82	2.77E+04	5.23E-01	5.23E-02	1.89E+04	

^a Daily emissions [lb/day] = Number engines x Daily operating time [hr/day] x Hourly emissions [lb/hr]

Daily Emissions, both Engines Normal Operation plus one Start-up for One Engine (lb/day) ^a										
CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂	
54.62	21.26	20.81	3.80	19.64	19.64	5.66E+04	1.33E+00	1.75E-01	2.25E+04	

Annual Op. (hr/year-engine)	Annual Emissions, both Engines (lb/year) ^c										
	CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂	
Start-Up ^a	18	205.99	61.17	44.94	5.39	14.73	14.73	4.25E+04	9.96E-01	1.31E-01	8.53E+03
SCR Catalyst Burn-In ^a	120	249.68	99.87	299.62	26.59	98.21	98.21	2.83E+05	6.64E+00	8.75E-01	0.00E+00
Normal Operation, Both Eng. ^b	7,746	16,117.01	6,446.80	6,446.80	1,203.87	6,339.36	6,339.36	1.83E+07	4.28E+02	5.65E+01	7.34E+06
Normal Operation, One Eng. ^b	438	911.34	364.54	364.54	48.95	358.46	358.46	1.01E+06	1.91E+01	1.91E+00	6.90E+05
Total	8,322	17,484.02	6,972.38	7,155.90	1,284.79	6,810.76	6,810.76	1.96E+07	4.55E+02	5.94E+01	8.04E+06

^a Mustang estimate

^b Based on each engine operating 95% of the time, excluding start-up hours and SCR catalyst burn-in, with 5% downtime for maintenance or other reasons.

^c Annual emissions [lb/year] = Operating time [hr/year-engine] x Hourly emissions at full load [lb/hr-engine] x Number engines

Table Bc CHP Engine Emissions

Normal Operation, Both Engines Operating

Type	Engine Rating (hp)	Fuel Input @ Full Load (scfh) ^a	Heat Input @ Full Load (MMBtu/hr)	Number Engines	Daily Op. (hr/day)	Emission Factors (normal operation)									
						CO (g/bhp-hr) ^b	ROC (g/bhp-hr) ^b	NOx (g/bhp-hr) ^b	SOx (g/scf) ^c	PM10 (g/bhp-hr) ^d	PM2.5 (g/bhp-hr) ^d	Combust. CO ₂ (g/MMBtu) ^e	CH ₄ (g/MMBtu) ^f	N ₂ O (g/MMBtu) ^f	Pass-through CO ₂ (g/scf) ^g
Jenbacher/GE JMS416vB82	1,573	17,002	9.88	2	24	0.3	0.12	0.12	0.00153	0.118	0.118	53,020	1.0	0.10	20.89

Fuel heating value = 581 Btu/scf Based on Mustang estimate of 86.5% biogas at 587 Btu/scf and 13.5% landfill gas at 545 Btu/scf
 Fuel sulfur = 20 ppmv Based on Mustang estimate of 86.5% biogas at 20 ppmv and 13.5% landfill gas at 22 ppmv
 Fuel CO₂ fraction = 0.404 Based on Mustang estimate of 86.5% biogas at 0.41 and 13.5% landfill gas at 36.23%

- ^a Fuel input at full load [scfh] = Heat input at full load [MMBtu/hr] x 10⁶ [Btu/MMBtu] / Fuel heating value [Btu/scf]
- ^b Control system vendor specifications
- ^c SOx emission factor [g/scf] = Fuel sulfur [ppmv] x 10⁻⁶ x 64 [lb/lb-mole SO₂] / 385.5 [scf/lb-mole] x 453.6 g/lb
- ^d Bekon estimate for filterable PM is 0.09 g/bhp-hr. Filterable PM10 and PM2.5 assumed equal to filterable PM
- Condensable PM emission factor for 4-stroke lean-burn natural gas fired engines from AP-42, Section 3.2 (Natural Gas-fired Reciprocating Internal Combustion Engines, 7/2000), Table 3.2-2 is 9.91 x 10⁻³ lb/MMBtu = 9.91 x 10⁻³ lb/MMBtu x 9.88 MMBtu/hr heat input / 1,573 hp engine rating x 453.6 g/lb = 0.0282 g/bhp-hr. Total PM10 and PM2.5 emission factor = 0.09 g/bhp-hr filterable + 0.0282 g/bhp-hr condensable = 0.118 g/bhp-hr.
- ^e From Table C-1 of Title 40, Code of Federal Regulations, Subpart 98 for natural gas. Biogas assumed same as natural gas because heat content is primarily from methane. Does not include "pass-through" CO₂ from fuel.
- ^f From Table C-2 of Title 40, Code of Federal Regulations, Subpart 98 for natural gas. Biogas assumed same as natural gas because heat content is primarily from methane. Does not include "pass-through" CO₂ from fuel.
- ^g "Pass-through" CO₂ emission factor [g/scf] = Fuel CO₂ volume fraction [unitless] x 44 [lb/lb-mole CO₂] / 385.5 [scf/lb-mole] x 453.6 g/lb

Normal Operation, One Engine Operating and One Engine Down

Type	Engine Rating (hp)	Fuel Input @ Full Load (scfh) ^a	Heat Input @ Full Load (MMBtu/hr)	Number Engines	Daily Op. (hr/day)	Emission Factors (normal operation)									
						CO (g/bhp-hr) ^b	ROC (g/bhp-hr) ^b	NOx (g/bhp-hr) ^b	SOx (g/scf) ^c	PM10 (g/bhp-hr) ^d	PM2.5 (g/bhp-hr) ^d	Combust. CO ₂ (g/MMBtu) ^e	CH ₄ (g/MMBtu) ^f	N ₂ O (g/MMBtu) ^f	Pass-through CO ₂ (g/scf) ^g
Jenbacher/GE JMS416vB82	1,573	16,828	9.88	1	24	0.3	0.12	0.12	0.00151	0.118	0.118	53,020	1.0	0.10	21.23

Fuel heating value = 587 Btu/scf Based on Mustang estimate for 100% biogas
 Fuel sulfur = 20 ppmv Based on Mustang estimate for 100% biogas
 Fuel CO₂ fraction = 0.410 Based on Mustang estimate for 100% biogas

- ^a Fuel input at full load [scfh] = Heat input at full load [MMBtu/hr] x 10⁶ [Btu/MMBtu] / Biogas heating value [Btu/scf]
- ^b Control system vendor specifications
- ^c SOx emission factor [g/scf] = Fuel sulfur [ppmv] x 10⁻⁶ x 64 [lb/lb-mole SO₂] / 385.5 [scf/lb-mole] x 453.6 g/lb
- ^d Bekon estimate for filterable PM is 0.09 g/bhp-hr. Filterable PM10 and PM2.5 assumed equal to filterable PM
- Condensable PM emission factor for 4-stroke lean-burn natural gas fired engines from AP-42, Section 3.2 (Natural Gas-fired Reciprocating Internal Combustion Engines, 7/2000), Table 3.2-2 is 9.91 x 10⁻³ lb/MMBtu = 9.91 x 10⁻³ lb/MMBtu x 9.88 MMBtu/hr heat input / 1,573 hp engine rating x 453.6 g/lb = 0.0282 g/bhp-hr. Total PM10 and PM2.5 emission factor = 0.09 g/bhp-hr filterable + 0.0282 g/bhp-hr condensable = 0.118 g/bhp-hr.
- ^e From Table C-1 of Title 40, Code of Federal Regulations, Subpart 98 for natural gas. Biogas assumed same as natural gas because heat content is primarily from methane. Does not include "pass-through" CO₂ from fuel.
- ^f From Table C-2 of Title 40, Code of Federal Regulations, Subpart 98 for natural gas. Biogas assumed same as natural gas because heat content is primarily from methane. Does not include "pass-through" CO₂ from fuel.
- ^g "Pass-through" CO₂ emission factor [g/scf] = Fuel CO₂ volume fraction [unitless] x 44 [lb/lb-mole CO₂] / 385.5 [scf/lb-mole] x 453.6 g/lb

Table 8c CHP Engine Emissions

Fuel Input @ Full Load (scfh) ^a	Heat Input @ Full Load (MMBtu/hr)	Emission Factors (start-up)									
		CO (g/bhp-hr) ^b	ROC (g/bhp-hr) ^b	NOx (g/bhp-hr) ^b	SOx (g/scf) ^d	PM10 (g/bhp-hr) ^e	PM2.5 (g/bhp-hr) ^e	Combust. CO ₂ (g/MMBtu) ^f	CH ₄ (g/MMBtu) ^f	N ₂ O (g/MMBtu) ^f	Pass-through CO ₂ (g/scf) ^g
9,232	9.88	3	0.43	0.6	0.00032	0.11800	0.11800	53.020	1.0	0.10	0.80
Fuel heating value =		1,070 Btu/scf		Based on 100% natural gas							
Fuel sulfur =		4.3 ppmv		Based on 100% natural gas at 0.5 grains/100 scf							
Fuel CO ₂ fraction =		0.0154		Based on 100% natural gas							
^a Fuel input at full load [scfh] = Heat input at full load [MMBtu/hr] x 10 ⁶ [Btu/MMBtu] / Biogas heating value [Btu/scf]											
^b Engine vendor specification											
^c Same as during normal operation											
^d SOx emission factor [g/scf] = Fuel sulfur [ppmv] x 10 ⁻⁶ x 64 [lb/lb-mole SO ₂] / 385.5 [scf/lb-mole] x 453.6 g/lb											
^e "Pass-through" CO ₂ emission factor [g/scf] = Fuel CO ₂ volume fraction [unitless] x 44 [lb/lb-mole CO ₂] / 385.5 [scf/lb-mole] x 453.6 g/lb											

Fuel Input @ Full Load (scfh) ^a	Heat Input @ Full Load (MMBtu/hr)	Emission Factors (SCR catalyst burn-in)									
		CO (g/bhp-hr) ^b	ROC (g/bhp-hr) ^b	NOx (g/bhp-hr) ^c	SOx (g/scf) ^d	PM10 (g/bhp-hr) ^e	PM2.5 (g/bhp-hr) ^e	Combust. CO ₂ (g/MMBtu) ^f	CH ₄ (g/MMBtu) ^f	N ₂ O (g/MMBtu) ^f	Pass-through CO ₂ (g/scf) ^g
9,232	9.88	0.3	0.12	0.36	0.00032	0.11800	0.11800	53.020	1.0	0.10	0.80
Fuel heating value =		1,070 Btu/scf		Based on 100% natural gas							
Fuel sulfur =		4.3 ppmv		Based on 100% natural gas at 0.5 grains/100 scf							
Fuel CO ₂ fraction =		0.0154		Based on 100% natural gas							
^a Fuel input at full load [scfh] = Heat input at full load [MMBtu/hr] x 10 ⁶ [Btu/MMBtu] / Biogas heating value [Btu/scf]											
^b Same as during normal operation											
^c Based on average of 50 percent of normal NOx control efficiency											
^d SOx emission factor [g/scf] = Fuel sulfur [ppmv] x 10 ⁻⁶ x 64 [lb/lb-mole SO ₂] / 385.5 [scf/lb-mole] x 453.6 g/lb											
^e "Pass-through" CO ₂ emission factor [g/scf] = Fuel CO ₂ volume fraction [unitless] x 44 [lb/lb-mole CO ₂] / 385.5 [scf/lb-mole] x 453.6 g/lb											

Hourly Emissions per Engine, Normal Operation, Both Engines Operating (lb/hr) ^a										
CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂	
1.04	0.42	0.42	0.06	0.41	0.41	1.15E+03	2.18E-02	2.18E-03	7.83E+02	
1.04	0.42	0.42	0.08	0.41	0.41	1.18E+03	2.77E-02	3.65E-03	4.74E+02	
1.04	0.42	0.42	0.08	0.41	0.41	1.18E+03	2.77E-02	3.65E-03	7.83E+02	

Hourly Emissions per Engine, Normal Operation, One Engine Operating and One Engine Down (lb/hr) ^a										
CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂	
1.04	0.42	0.42	0.06	0.41	0.41	1.15E+03	2.18E-02	2.18E-03	7.87E+02	
1.04	0.42	0.42	0.06	0.41	0.41	1.15E+03	2.18E-02	2.18E-03	7.87E+02	
1.04	0.42	0.42	0.06	0.41	0.41	1.15E+03	2.18E-02	2.18E-03	7.87E+02	

Table 8c

CHP Engine Emissions

Hourly Emissions per Engine, Start-Up (lb/hr) ^a										
CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂	
5.72	0.95	1.25	0.04	0.41	0.41	1.15E+03	2.18E-02	2.18E-03	4.08E+02	
5.72	1.70	1.25	0.15	0.41	0.41	1.18E+03	2.77E-02	3.65E-03	2.37E+02	
5.72	1.70	1.25	0.15	0.41	0.41	1.18E+03	2.77E-02	3.65E-03	4.08E+02	

Maximum case for engine startup lb/hr

^a Start-up is 30 minutes with no CO, ROC or NOx control by SCR/catalyst system. Emissions are for one-hour period that includes 30-minute start-up

Hourly Emissions per Engine, SCR Catalyst Burn-in (lb/hr) ^a										
CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂	
1.04	0.42	1.25	0.01	0.41	0.41	1.15E+03	2.18E-02	2.18E-03	1.62E+01	
1.04	0.42	1.25	0.11	0.41	0.41	1.18E+03	2.77E-02	3.65E-03	0.00E+00	
1.04	0.42	1.25	0.11	0.41	0.41	1.18E+03	2.77E-02	3.65E-03	1.62E+01	

Maximum case for SCR burn-in lb/hr

Daily Emissions, both Engines Normal Operation (lb/day) ^a										
CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂	
49.94	19.97	19.97	2.75	19.64	19.64	5.54E+04	1.05E+00	1.05E-01	3.76E+04	
49.94	19.97	19.97	3.73	19.64	19.64	5.66E+04	1.33E+00	1.75E-01	2.27E+04	
49.94	19.97	19.97	3.73	19.64	19.64	5.66E+04	1.33E+00	1.75E-01	3.76E+04	

Max. case for Normal Op. 2 eng. lb/day

Table 8c

CHP Engine Emissions

Daily Emissions, One Engine Normal Operation (lb/day) ^a										
CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂	
24.97	9.99	9.99	1.34	9.82	9.82	2.77E+04	5.23E-01	5.23E-02	1.89E+04	
24.97	9.99	9.99	1.34	9.82	9.82	2.77E+04	5.23E-01	5.23E-02	1.89E+04	
24.97	9.99	9.99	1.34	9.82	9.82	2.77E+04	5.23E-01	5.23E-02	1.89E+04	

Max. case for Normal Op. 1 eng. lb/day

Daily Emissions, both Engines Normal Operation plus one Start-up for One Engine (lb/day) ^a										
CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂	
54.62	20.51	20.81	2.72	19.64	19.64	5.54E+04	1.05E+00	1.05E-01	3.72E+04	
54.62	21.26	20.81	3.80	19.64	19.64	5.66E+04	1.33E+00	1.75E-01	3.72E+04	
54.62	21.26	20.81	3.80	19.64	19.64	5.66E+04	1.33E+00	1.75E-01	3.72E+04	

Maximum case for Normal Op. + 1 SU

Annual Op. (hr/year-engine)	Annual Emissions, both Engines (lb/year) ^a										
	CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂	
Start-Up ^b	18	205.99	61.17	44.94	5.39	14.73	14.73	42,485.71	1.00	0.13	14,680.38
SCR Catalyst Burn-In ^c	120	249.68	99.87	299.62	26.59	98.21	98.21	2,83E+05	6.64E+00	8.75E-01	3,89E+03
Normal Operation, Both Eng. ^b	7,746	16,117.01	6,446.80	6,446.80	1,203.87	6,339.36	6,339.36	1.83E+07	4.28E+02	5.65E+01	1.21E+07
Normal Operation, One Eng. ^b	438	911.34	364.54	364.54	48.95	358.46	358.46	1.01E+06	1.91E+01	1.91E+00	6.90E+05
Total	8,322	17,484.02	6,972.38	7,155.90	1,284.79	6,810.76	6,810.76	1.96E+07	4.55E+02	5.94E+01	1.28E+07

^a Mustang estimate

^b Based on each engine operating 95% of the time, excluding start-up hours and SCR catalyst burn-in, with 5% downtime for maintenance or other reasons.

^c Annual emissions [lb/year] = Operating time [hr/year-engine] x Hourly emissions at full load [lb/hr-engine] x Number engines based on maximum emissions by operational case

from the biogas/natural gas case										
205.99	34.33	44.94	1.05	14.73	14.73	41,566.00	0.78	0.08	11,687.69	
249.68	99.87	299.62	1.58	98.21	98.21	2.77E+05	5.23E+00	5.23E-01	3.89E+03	
16,117.01	6,446.80	6,446.80	696.73	6,339.36	6,339.36	1.79E+07	3.37E+02	3.37E+01	9.56E+06	
911.34	364.54	364.54	48.95	358.46	358.46	1.01E+06	1.91E+01	1.91E+00	6.90E+05	
17,484.02	6,945.54	7,155.90	748.30	6,810.76	6,810.76	1.92E+07	3.62E+02	3.62E+01	1.03E+07	
0.00	26.84	0.00	4.34	0.00	0.00	919.71	0.21	0.05	2,992.69	
0.00	0.00	0.00	25.01	0.00	0.00	6,131.42	1.41	0.35	0.00	
0.00	0.00	0.00	507.14	0.00	0.00	395,782.88	91.09	22.77	2,575,708.76	
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
0.00	26.84	0.00	536.49	0.00	0.00	402,834.01	92.71	23.18	2,578,701.46	

Compound	CAS Number	MRF/AD Tank		Clear Diesel		Red Diesel		Gasoline Tank	
		Hourly Emission Rate (lb/hr)	Annual Emission Rate (lb/yr)	Hourly Emission Rate (lb/hr)	Annual Emission Rate (lb/yr)	Hourly Emission Rate (lb/hr)	Annual Emission Rate (lb/yr)	Hourly Emission Rate (lb/hr)	Annual Emission Rate (lb/yr)
Benzene	71432	1.14E-06	0.01	1.14E-06	0.01	2.28E-06	0.02	5.82E-05	0.51
Ethylbenzene	100414	2.28E-06	0.02	1.14E-06	0.01	3.42E-06	0.03	4.57E-06	0.04
n-Hexane	110543	1.14E-06	0.01	1.14E-06	0.01	1.14E-06	0.01	5.25E-05	0.46
Toluene	108883	1.83E-05	0.16	1.14E-06	0.01	2.51E-05	0.22	6.39E-05	0.56
1,2,4-Trimethylbenzene	95636	3.65E-05	0.32	1.14E-06	0.01	4.91E-05	0.43	1.14E-06	0.01
m-Xylene	108383	4.68E-05	0.41	1.14E-06	0.01	6.28E-05	0.55	1.71E-05	0.15

Diesel

g/s

8.00E-04 7.01

1.01E-04

Table 6d MRF CHP Engine Emissions with biogas/propane

Normal Operation, Both Engines Operating

Type	Engine Rating (hp)	Fuel Input @ Full Load (scfh) ^a	Heat Input @ Full Load (MMBtu/hr)	Number Engines	Daily Op. (hr/day)	Emission Factors (normal operation)									
						CO (g/bhp-hr) ^b	ROC (g/bhp-hr) ^b	NOx (g/bhp-hr) ^b	SOx (g/scf) ^c	PM10 (g/bhp-hr) ^d	PM2.5 (g/bhp-hr) ^d	Combust. CO ₂ (g/MMBtu) ^e	CH ₄ (g/MMBtu) ^f	N ₂ O (g/MMBtu) ^f	Pass-through CO ₂ (g/scf) ^g
Jenbacher/GE JMS420B82	1,966	15,264	12.32	2	24	0.2	0.114	0.12	0.00314	0.118	0.118	54,193	1.27	0.17	16.23

Fuel heating value = 807 Btu/scf Based on Mustang estimate of 86.5% landfill gas at 545 Btu/scf and 13.5% propane at 2,488 Btu/scf
 Fuel sulfur = 42 ppmv Based on Mustang estimate of 86.5% landfill gas at 22 ppmv and 13.5% propane at 168.1 ppmv
 Fuel CO₂ factor = 54,193 g/MMBtu Based on Mustang estimate of 86.5% landfill gas at and 13.5% propane^h
 Fuel CH₄ factor = 1.27 g/MMBtu Based on Mustang estimate of 86.5% landfill gas at and 13.5% propaneⁱ
 Fuel N₂O factor = 0.17 g/MMBtu Based on Mustang estimate of 86.5% landfill gas at and 13.5% propane^j
 Fuel pass-through CO₂ fraction = 0.313 Based on Mustang estimate of 86.5% landfill gas at 0.3623 and 13.5% propane at 0

^a Fuel input at full load [scfh] = Heat input at full load [MMBtu/hr] x 10⁶ [Btu/MMBtu] / Fuel heating value [Btu/scf]

^b Control system vendor specifications

^c SOx emission factor [g/scf] = Fuel sulfur [ppmv] x 10⁻⁶ x 64 [lb/lb-mole SO₂] / 385.5 [scf/lb-mole] x 453.6 g/lb

^d Bekon estimate for filterable PM is 0.09 g/bhp-hr based on firing biogas and natural gas. Assumed similar for firing biogas and propane. Filterable PM10 and PM2.5 assumed equal to filterable PM. Condensable PM emission factor for 4-stroke lean-burn natural gas fired engines from AP-42, Section 3.2 (Natural Gas-fired Reciprocating Internal Combustion Engines, 7/2000), Table 3.2-2 is 9.91 x 10⁻³ lb/MMBtu = 9.91 x 10⁻³ lb/MMBtu x 9.88 MMBtu/hr heat input / 1,573 hp engine rating x 453.6 g/lb = 0.0282 g/bhp-hr. Total PM10 and PM2.5 emission factor = 0.09 g/bhp-hr filterable + 0.0282 g/bhp-hr condensable = 0.118 g/bhp-hr.

^e From Table C-1 of Title 40, Code of Federal Regulations, Subpart 98. Biogas assumed same as natural gas because heat content is primarily from methane. Does not include "pass-through" CO₂ from fuel. Propane based on Liquefied Petroleum Gases (LPG) fuel type.

^f From Table C-2 of Title 40, Code of Federal Regulations, Subpart 98. Biogas assumed same as natural gas because heat content is primarily from methane. Propane based on Petroleum fuel type.

^g "Pass-through" CO₂ emission factor [g/scf] = Fuel CO₂ volume fraction [unitless] x 44 [lb/lb-mole CO₂] / 385.5 [scf/lb-mole] x 453.6 g/lb

Normal Operation, One Engine Operating and One Engine Down

Type	Engine Rating (hp)	Fuel Input @ Full Load (scfh) ^a	Heat Input @ Full Load (MMBtu/hr)	Number Engines	Daily Op. (hr/day)	Emission Factors (normal operation)									
						CO (g/bhp-hr) ^b	ROC (g/bhp-hr) ^b	NOx (g/bhp-hr) ^b	SOx (g/scf) ^c	PM10 (g/bhp-hr) ^d	PM2.5 (g/bhp-hr) ^d	Combust. CO ₂ (g/MMBtu) ^e	CH ₄ (g/MMBtu) ^f	N ₂ O (g/MMBtu) ^f	Pass-through CO ₂ (g/scf) ^g
Jenbacher/GE JMS420B82	1,966	22,602	12.32	1	24	0.2	0.114	0.12	0.00166	0.118	0.118	53,020	1.0	0.10	18.75

Fuel heating value = 545 Btu/scf Based on Mustang estimate for 100% landfill gas
 Fuel sulfur = 22 ppmv Based on Mustang estimate for 100% landfill gas
 Fuel CO₂ fraction = 0.362 Based on Mustang estimate for 100% landfill gas

^a Fuel input at full load [scfh] = Heat input at full load [MMBtu/hr] x 10⁶ [Btu/MMBtu] / Biogas heating value [Btu/scf]

^b Control system vendor specifications

^c SOx emission factor [g/scf] = Fuel sulfur [ppmv] x 10⁻⁶ x 64 [lb/lb-mole SO₂] / 385.5 [scf/lb-mole] x 453.6 g/lb

^d Bekon estimate for filterable PM is 0.09 g/bhp-hr. Filterable PM10 and PM2.5 assumed equal to filterable PM. Condensable PM emission factor for 4-stroke lean-burn natural gas fired engines from AP-42, Section 3.2 (Natural Gas-fired Reciprocating Internal Combustion Engines, 7/2000), Table 3.2-2 is 9.91 x 10⁻³ lb/MMBtu = 9.91 x 10⁻³ lb/MMBtu x 9.88 MMBtu/hr heat input / 1,573 hp engine rating x 453.6 g/lb = 0.0282 g/bhp-hr. Total PM10 and PM2.5 emission factor = 0.09 g/bhp-hr filterable + 0.0282 g/bhp-hr condensable = 0.118 g/bhp-hr.

^e From Table C-1 of Title 40, Code of Federal Regulations, Subpart 98 for natural gas. Biogas assumed same as natural gas because heat content is primarily from methane. Does not include "pass-through" CO₂ from fuel.

^f From Table C-2 of Title 40, Code of Federal Regulations, Subpart 98 for natural gas. Biogas assumed same as natural gas because heat content is primarily from methane. Does not include "pass-through" CO₂ from fuel.

^g "Pass-through" CO₂ emission factor [g/scf] = Fuel CO₂ volume fraction [unitless] x 44 [lb/lb-mole CO₂] / 385.5 [scf/lb-mole] x 453.6 g/lb

Table 8d MRF CHP Engine Emissions with biogas/propane

Start-up

Fuel Input @ Full Load (scfh) ^a	Heat Input @ Full Load (MMBtu/hr)	Emission Factors (start-up)									
		CO (g/bhp-hr) ^b	ROC (g/bhp-hr) ^b	NOx (g/bhp-hr) ^b	SOx (g/scf) ^d	PM10 (g/bhp-hr) ^c	PM2.5 (g/bhp-hr) ^e	Combust. CO ₂ (g/MMBtu) ^f	CH ₄ (g/MMBtu) ^g	N ₂ O (g/MMBtu) ^h	Pass-through CO ₂ (g/scf) ⁱ
4,951	12.32	0.2	0.114	0.12	0.01266	0.11800	0.11800	61.710	3.0	0.60	0.00
Fuel heating value =		2,488 Btu/scf		Based on 100% propane							
Fuel sulfur =		168.1 ppmv		Based on 100% propane at 123 ppmw							
Fuel CO ₂ fraction =		0		Based on 100% propane							
^a Fuel input at full load [scfh] = Heat input at full load [MMBtu/hr] x 10 ⁶ [Btu/MMBtu] / Biogas heating value [Btu/scf] ^b Engine vendor specification for natural gas fuel, assumed same for propane fuel except double for uncontrolled ROC. ^c Same as during normal operation ^d SOx emission factor [g/scf] = Fuel sulfur [ppmv] x 10 ⁻⁶ x 64 [lb/lb-mole SO ₂] / 385.5 [scf/lb-mole] x 453.6 g/lb ^e From Table C-1 of Title 40, Code of Federal Regulations, Subpart 98. Propane based on Liquefied Petroleum Gases (LPG) fuel type. ^f From Table C-2 of Title 40, Code of Federal Regulations, Subpart 98. Propane based on Petroleum fuel type. ^g "Pass-through" CO ₂ not expected with 100% propane/LPG fuel											

Catalyst Burn-In

Fuel Input @ Full Load (scfh) ^a	Heat Input @ Full Load (MMBtu/hr)	Emission Factors (SCR catalyst burn-in)									
		CO (g/bhp-hr) ^b	ROC (g/bhp-hr) ^b	NOx (g/bhp-hr) ^c	SOx (g/scf) ^d	PM10 (g/bhp-hr) ^e	PM2.5 (g/bhp-hr) ^e	Combust. CO ₂ (g/MMBtu) ^f	CH ₄ (g/MMBtu) ^g	N ₂ O (g/MMBtu) ^h	Pass-through CO ₂ (g/scf) ⁱ
4,951	12.32	0.2	0.114	0.12	0.01266	0.11800	0.11800	61.710	3.0	0.60	0.00
Fuel heating value =		2,488 Btu/scf		Based on 100% propane							
Fuel sulfur =		168.1 ppmv		Based on 100% propane at 123 ppmw							
Fuel CO ₂ fraction =		0		Based on 100% propane							
^a Fuel input at full load [scfh] = Heat input at full load [MMBtu/hr] x 10 ⁶ [Btu/MMBtu] / Biogas heating value [Btu/scf] ^b Same as during normal operation ^c Based on average of 50 percent of normal NOx control efficiency ^d SOx emission factor [g/scf] = Fuel sulfur [ppmv] x 10 ⁻⁶ x 64 [lb/lb-mole SO ₂] / 385.5 [scf/lb-mole] x 453.6 g/lb ^e From Table C-1 of Title 40, Code of Federal Regulations, Subpart 98. Propane based on Liquefied Petroleum Gases (LPG) fuel type. ^f From Table C-2 of Title 40, Code of Federal Regulations, Subpart 98. Propane based on Petroleum fuel type. ^g "Pass-through" CO ₂ not expected with 100% propane/LPG fuel											

Hourly Emissions per Engine, Normal Operation, Both Engines Operating (lb/hr)^a

CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂
0.87	0.49	0.52	0.11	0.51	0.51	1.47E+03	3.45E-02	4.55E-03	5.46E+02

^a Except for SOx, CO₂, CH₄ and N₂O, Hourly emissions [lb/hr] = Engine rating [hp] x Emission factor [g/bhp-hr] / 453.6 [g/lb]
 SOx and pass-through CO₂ hourly emissions [lb/hr] = Biogas input [scfh] x Emission factor [g/scf] / 453.6 [g/lb]
 Combustion CO₂, CH₄ and N₂O hourly emissions [lb/hr] = Heat input [MMBtu/hr] x Emission factor [g/MMBtu] / 453.6 [g/lb]

Hourly Emissions per Engine, Normal Operation, One Engine Operating and One Engine Down (lb/hr)^a

CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂
0.87	0.49	0.52	0.08	0.51	0.51	1.44E+03	2.72E-02	2.72E-03	9.35E+02

^a Except for SOx, CO₂, CH₄ and N₂O, Hourly emissions [lb/hr] = Engine rating [hp] x Emission factor [g/bhp-hr] / 453.6 [g/lb]
 SOx and pass-through CO₂ hourly emissions [lb/hr] = Biogas input [scfh] x Emission factor [g/scf] / 453.6 [g/lb]
 Combustion CO₂, CH₄ and N₂O hourly emissions [lb/hr] = Heat input [MMBtu/hr] x Emission factor [g/MMBtu] / 453.6 [g/lb]

Table 8d

MRF CHP Engine Emissions with biogas/propane

Hourly Emissions per Engine, Start-Up (lb/hr) ^a										
CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂	
0.87	0.49	0.52	0.19	0.51	0.51	1.47E+03	3.45E-02	4.55E-03	2.73E+02	

^a Start-up is 30 minutes with no CO, ROC or NOx control by SCR/catalyst system. Emissions are for one-hour period that includes 30-minute start-up

Hourly Emissions per Engine, SCR Catalyst Burn-In (lb/hr) ^a										
CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂	
0.87	0.49	0.52	0.14	0.51	0.51	1.47E+03	3.45E-02	4.55E-03	0.00E+00	

Daily Emissions, both Engines Normal Operation (lb/day) ^a										
CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂	
41.61	23.72	24.97	5.08	24.55	24.55	7.06E+04	1.66E+00	2.18E-01	2.62E+04	

^a Daily emissions [lb/day] = Number engines x Daily operating time [hr/day] x Hourly emissions [lb/hr]

Daily Emissions, One Engine Normal Operation (lb/day) ^a										
CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂	
20.80	11.86	12.48	1.98	12.27	12.27	3.46E+04	6.52E-01	6.52E-02	2.24E+04	

^a Daily emissions [lb/day] = Number engines x Daily operating time [hr/day] x Hourly emissions [lb/hr]

Daily Emissions, both Engines Normal Operation plus one Start-up for One Engine (lb/day) ^a										
CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂	
41.61	23.72	24.97	5.16	24.55	24.55	7.06E+04	1.66E+00	2.18E-01	2.59E+04	

Annual Op. (hr/year-engine)	Annual Emissions, both Engines (lb/year) ^c										
	CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂	
Start-Up ^a	18	31.21	17.79	18.72	6.88	18.41	18.41	5.30E+04	1.24E+00	1.64E-01	9.83E+03
SCR Catalyst Burn-In ^a	120	208.04	118.58	124.83	33.16	122.74	122.74	3.53E+05	8.28E+00	1.09E+00	0.00E+00
Normal Operation, Both Eng. ^b	7,748	13,429.13	7,654.61	8,057.48	1,637.99	7,923.19	7,923.19	2.28E+07	5.34E+02	7.05E+01	8.46E+06
Normal Operation, One Eng. ^b	438	759.35	432.83	455.61	72.31	448.02	448.02	1.26E+06	2.38E+01	2.38E+00	8.19E+05
Total	8,322	14,427.74	8,223.81	8,656.64	1,750.34	8,512.36	8,512.36	2.45E+07	5.68E+02	7.41E+01	9.29E+06

^a Mustang estimate

^b Based on each engine operating 95% of the time, excluding start-up hours and SCR catalyst burn-in, with 5% downtime for maintenance or other reasons.

^c Annual emissions [lb/year] = Operating time [hr/year-engine] x Hourly emissions at full load [lb/hr-engine] x Number engines

Table 8e

MRF CHP Engine Emissions

Hourly Emissions per Engine, Normal Operation, Both Engines Operating (lb/hr) ^a										
	CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂
Operating with landfill gas	0.87	0.49	0.52	0.08	0.51	0.51	1.44E+03	2.72E-02	2.72E-03	9.35E+02
Operating with NG/propane	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Maximum case for Normal Op. lb/hr	0.87	0.49	0.52	0.08	0.51	0.51	1.44E+03	2.72E-02	2.72E-03	9.35E+02

Hourly Emissions per Engine, Normal Operation, One Engine Operating and One Engine Down (lb/hr) ^a										
	CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂
Operating with landfill gas	0.87	0.49	0.52	0.08	0.51	0.51	1.44E+03	2.72E-02	2.72E-03	9.35E+02
Operating with NG/propane	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Max. case for Normal Op. 1 engine lb/hr	0.87	0.49	0.52	0.08	0.51	0.51	1.44E+03	2.72E-02	2.72E-03	9.35E+02

Hourly Emissions per Engine, Start-Up (lb/hr) ^a										
	CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂
Operating with landfill gas	6.93	1.18	1.56	0.05	0.51	0.51	1.44E+03	2.72E-02	2.72E-03	4.88E+02
Operating with NG/propane	0.87	0.49	0.52	0.19	0.51	0.51	1.47E+03	3.45E-02	4.55E-03	2.73E+02
Maximum case for engine startup lb/hr	6.93	1.18	1.56	0.19	0.51	0.51	1.47E+03	3.45E-02	4.55E-03	4.88E+02

^a Start-up is 30 minutes with no CO, ROC or NOx control by SCR/catalyst system. Emissions are for one-hour period that includes 30-minute start-up

Hourly Emissions per Engine, SCR Catalyst Burn-In (lb/hr) ^a										
	CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂
Operating with landfill gas	6.93	1.18	1.56	0.04	0.51	0.51	115619.95	2.18	0.22	469.04
Operating with NG/propane	0.87	0.49	0.52	0.14	0.51	0.51	1471.67	0.03	0.00	0.00
Maximum case for SCR burn-in lb/hr	6.93	1.18	1.56	0.14	0.51	0.51	1.16E+05	2.18E+00	2.18E-01	4.69E+02

Daily Emissions, both Engines Normal Operation (lb/day) ^a										
	CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂
Operating with landfill gas	41.61	23.72	24.97	3.96	24.55	24.55	6.91E+04	1.30E+00	1.30E-01	4.49E+04
Operating with NG/propane	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Max. case for Normal Op. 2 eng. lb/day	41.61	23.72	24.97	3.96	24.55	24.55	6.91E+04	1.30E+00	1.30E-01	4.49E+04

Table 8e

MRF CHP Engine Emissions

		Daily Emissions, One Engine Normal Operation (lb/day) ^a									
		CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂
Operating with landfill gas		20.80	11.86	12.48	1.98	12.27	12.27	3.46E+04	6.52E-01	6.52E-02	2.24E+04
		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Maximum case for Normal Op. 1 eng. lb/day		20.80	11.86	12.48	1.98	12.27	12.27	3.46E+04	6.52E-01	6.52E-02	2.24E+04

		Daily Emissions, both Engines Normal Operation plus one Start-up for One Engine (lb/day) ^a									
		CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂
Operating with landfill gas		47.68	24.40	26.01	3.93	24.55	24.55	6.91E+04	1.30E+00	1.30E-01	4.44E+04
		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Maximum case for Normal Op. + 1 SU		47.68	24.40	26.01	3.93	24.55	24.55	6.91E+04	1.30E+00	1.30E-01	4.44E+04

		Annual Emissions, both Engines (lb/year) ^c									
Annual Op. (hr/year-engine)		CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂
Start-Up ^a	18	249.65	42.44	56.17	6.88	18.41	18.41	52,980.26	1.24	0.16	17,551.83
SCR Catalyst Burn-In ^a	120	1,664.34	282.94	374.48	33.16	122.74	122.74	2.77E+07	5.23E+02	5.23E+01	1.13E+05
Normal Operation, Both Eng. ^b	7,746	13,429.13	7,654.61	8,057.48	1,278.88	7,923.19	7,923.19	2.23E+07	4.21E+02	4.21E+01	1.45E+07
Normal Operation, One Eng. ^b	438	759.35	432.83	455.61	72.31	448.02	448.02	1.26E+06	2.38E+01	2.38E+00	8.19E+05
Total	8,322	16,102.48	8,412.82	8,943.74	1,391.23	8,512.36	8,512.36	5.14E+07	9.69E+02	9.69E+01	1.54E+07

^a Mustang estimate^b Based on each engine operating 95% of the time, excluding start-up hours and SCR catalyst burn-in, with 5% downtime for maintenance or other reasons.^c Annual emissions [lb/year] = Operating time [hr/year-engine] x Hourly emissions at full load [lb/hr-engine] x Number engines based on maximum emissions by operational case

Table 9a AD Flare Emissions

Type	Heat Input (MMBtu/hr) ^a	Biogas Flow Rate (scfh) ^a	Daily Op. (hr/day)	Emission Factors									
				CO (lb/MMBtu) ^b	ROC (lb/MMBtu) ^c	NOx (lb/MMBtu) ^b	SOx (g/scf) ^d	PM10 (lb/MMBtu) ^b	PM2.5 (lb/MMBtu) ^b	Combust. CO ₂ (g/MMBtu) ^e	CH ₄ (g/MMBtu) ^f	N ₂ O (g/MMBtu) ^f	Pass- through CO ₂ (g/scf) ^g
John Zink ZTOF	1.23	2,125	1	0.2	0.0027	0.08	0.01506	0.042	0.042	53,020	3.2	0.63	21.23

Biogas sulfur = 200 ppmv

Biogas CO₂ fraction = 0.41 Conservative estimate

^a Heat input assumed to be 1/16 of heat input to two CHP engines when purging one digester. Biogas flow rate assumed to be 1/16 of biogas to two CHP engines.

^b Manufacturer's specifications

^c From SBCAPCD Rule 359

^d SOx emission factor [g/scf] = Biogas sulfur [ppmv] x 10⁻⁶ x 64 [lb/lb-mole SO₂] / 385.5 [scf/lb-mole] x 453.6 g/lb

^e From Table C-1 of Title 40, Code of Federal Regulations, Subpart 98 for natural gas. Biogas assumed same as natural gas because heat content is primarily from methane. Does not include "pass-through" CO₂ from biogas.

^f From Table C-2 of Title 40, Code of Federal Regulations, Subpart 98 for natural gas. Biogas assumed same as natural gas because heat content is primarily from methane. Does not include "pass-through" CO₂ from biogas.

^g "Pass-through" CO₂ emission factor [g/scf] = Biogas CO₂ volume fraction [unitless] x 44 [lb/lb-mole CO₂] / 385.5 [scf/lb-mole] x 453.6 g/lb

Heat Input (MMBtu/hr) ^a	Biogas Flow Rate (scfh) ^a	Digester Purging Hourly Emissions ^b									
		CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass- through CO ₂
1.23	2,125	0.25	0.00	0.10	0.07	0.05	0.05	144.33	0.01	0.00	99.45

^a Heat input assumed to be 1/16 of heat input to two CHP engines when purging one digester. Biogas flow rate assumed to be 1/16 of biogas to two CHP engines.

^b Except for SOx and pass-through CO₂, Hourly emissions [lb/hr] = Heat input [MMBtu/hr] x Emission factor [lb/MMBtu]

SOx and pass-through CO₂ hourly emissions [lb/hr] = Biogas input [scfh] x Emission factor [g/scf] / 453.6 [g/lb]

Daily Op. (hr/day)	Digester Purging Daily Emissions ^a									
	CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass- through CO ₂
1	0.25	0.00	0.10	0.07	0.05	0.05	144.33	0.01	0.00	99.45

^a Daily emissions [lb/day] = Daily operating time [hr/day] x Hourly emissions [lb/hr]

Annual Op. (hr/year)	Digester Purging Annual Emissions ^a									
	CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass- through CO ₂
278	68.65	0.93	27.46	19.62	14.42	14.42	40,122.73	2.42	0.48	27,647.75

^a Annual emissions [lb/year] = Annual op. [hr/year] x Hourly emissions [lb/hr]

Table 9a AD Flare Emissions

Heat Input (MMBtu/hr) ^a	Flow Rate (scfh) ^a	Hourly Flaring Emissions for One Engine Off-Line ^b									
		CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂
9.88	17,002	1.98	0.03	0.79	0.56	0.41	0.41	1,154.61	0.07	0.01	795.62

^a Heat input assumed to be heat input to two CHP engines. Flow rate assumed to be biogas flow rate to two CHP engines.

^b Except for SOx and pass-through CO₂, Hourly emissions [lb/hr] = Heat input [MMBtu/hr] x Emission factor [lb/MMBtu]
 SOx and pass-through CO₂ hourly emissions [lb/hr] = Biogas input [scfh] x Emission factor [g/scf] / 453.6 [g/lb]

Daily Op. (hr/day)	Daily Flaring Emissions for One Engine Off-Line ^a										
	CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂	
24	47.41	0.64	18.97	13.55	9.96	9.96	27,710.66	1.67	0.33	19,094.85	

^a Daily emissions [lb/day] = Daily operating time [hr/day] x Hourly emissions [lb/hr]

Annual Op. (hr/year)	Annual Flaring Emissions for Engines Off-Line ^a										
	CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂	
876	1,730.63	23.36	692.25	494.52	363.43	363.43	1,011,439.26	61.04	12.02	696,962.07	

^a Annual operating hours assumes each engine is off-line 5% of the time during a year (438 hrs/engine)

^b Annual emissions [lb/year] = Annual op. [hr/year] x Hourly emissions [lb/hr]

Table 9b MRF Flare Emissions

753 SCFM

Type	Heat Input (MMBtu/hr) ^a	Landfill Gas Flow Rate (scfh) ^a	Daily Op. (hr/day)	Emission Factors									
				CO (lb/MMBtu) ^b	ROC (lb/MMBtu) ^c	NOx (lb/MMBtu) ^b	SOx (g/scf) ^d	PM10 (lb/MMBtu) ^b	PM2.5 (lb/MMBtu) ^b	Combust. CO ₂ (g/MMBtu) ^e	CH ₄ (g/MMBtu) ^f	N ₂ O (g/MMBtu) ^g	Pass-through CO ₂ (g/scf) ^h
John Zink ZTOF	24.64	45,204	1	0.2	0.0027	0.08	0.00166	0.042	0.042	53,020	3.2	0.63	18.76

Landfill gas sulfur = 22 ppmv
 Landfill gas CO₂ fraction = 0.3623 Conservative estimate

^a Heat input assumed to be 1/16 of heat input to two CHP engines when purging one digester.

^b Manufacturer's specifications

^c From SBCAPCD Rule 359

^d SOx emission factor [g/scf] = Biogas sulfur [ppmv] x 10⁻⁶ x 64 [lb/lb-mole SO₂] / 385.5 [scf/lb-mole] x 453.6 g/lb

^e From Table C-1 of Title 40, Code of Federal Regulations, Subpart 98 for natural gas. Biogas assumed same as natural gas because heat content is primarily from methane. Does not include "pass-through" CO₂ from biogas.

^f From Table C-2 of Title 40, Code of Federal Regulations, Subpart 98 for natural gas. Biogas assumed same as natural gas because heat content is primarily from methane. Does not include "pass-through" CO₂ from biogas.

^g "Pass-through" CO₂ emission factor [g/scf] = Biogas CO₂ volume fraction [unitless] x 44 [lb/lb-mole CO₂] / 385.5 [scf/lb-mole] x 453.6 g/lb

Heat Input (MMBtu/hr) ^a	Flow Rate (scfh) ^a	Hourly Flaring Emissions for One Engine Off-Line (lb/hr) ^b									
		CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂
12.32	22,602	2.46	0.03	0.99	0.08	0.52	0.52	1,439.82	0.09	0.02	934.63

^a Heat input assumed to be heat input to two CHP engines. Flow rate assumed to be biogas flow rate to two CHP engines.

^b Except for SOx and pass-through CO₂, Hourly emissions [lb/hr] = Heat input [MMBtu/hr] x Emission factor [lb/MMBtu]

SOx and pass-through CO₂ hourly emissions [lb/hr] = Biogas input [scfh] x Emission factor [g/scf] / 453.6 [g/lb]

Daily Op. (hr/day)	Daily Flaring Emissions for One Engine Off-Line (lb/day) ^a									
	CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂
24	59.13	0.80	23.65	1.98	12.42	12.42	34,555.57	2.09	0.41	22,431.15

^a Daily emissions [lb/day] = Daily operating time [hr/day] x Hourly emissions [lb/hr]

Annual Op. (hr/year)	Annual Flaring Emissions for Engines Off-Line (lb/year) ^a									
	CO	ROC	NOx	SOx	PM10	PM2.5	Combust. CO ₂	CH ₄	N ₂ O	Pass-through CO ₂
876	2,158.11	29.13	863.25	72.31	453.20	453.20	1,261,278.47	76.12	14.99	818,737.03

^a Annual operating hours assumes each engine is off-line 5% of the time during a year (438 hrs/engine)

^b Annual emissions [lb/year] = Annual op. [hr/year] x Hourly emissions [lb/hr]

Table 10 Emergency Generator Testing Emissions

Equipment	Horsepower	Hours/Day	Fuel Use (gal/hr)	Emission Factors (g/bhp-hr) ^a					Emission Factors (g/gal)		
				CO	ROC	NOx	PM10 ^b	PM2.5 ^b	CO ₂ ^c	CH ₄ ^d	N ₂ O ^d
Caterpillar D 150-8 150 ekW	239	0.5	11.3	2.6	0.14	0.5	0.02	0.02	10,210	0.41	0.083

^a Emission factors are Tier 4 emission standards.

^b PM10 and PM2.5 assumed to be same as PM emission standards.

^c From Table C-1 of Title 40, Code of Federal Regulations, Subpart 98 for No. 2 distillate fuel oil.

^d From Table C-2 of Title 40, Code of Federal Regulations, Subpart 98 for No. 2 distillate fuel oil.

Equipment	Load Factor	Emission Rates (lb/hr)								
		CO ^a	ROC ^a	NOx ^a	SOx ^b	PM10 ^a	PM2.5 ^a	CO ₂ ^c	CH ₄ ^c	N ₂ O ^c
Caterpillar D 150-8 150 ekW	1	1.373	0.074	0.264	0.002	0.011	0.011	254.35	0.01	0.00

Diesel Fuel Density = 6.943

Diesel Fuel Sulfur = 15 ppmw

^a Emission Rate [lb/hr] = Emission Factor [g/bhp-hr] x Engine Horsepower [hp] x Load Factor [unitless] / 453.6 [g/lb]

^b Emission Rate [lb/hr] = Fuel Use [gal/hr] x Fuel Density [lb/gal] x Fuel Sulfur [ppmw] x 10⁻⁶ x 2 [lb SO₂/lb S]

^c Emission Rate [lb/hr] = Emission Factor [g/gal] x Fuel Use [gal/hr] / 453.6 [g/lb]

Equipment	Daily Emissions (lb/day) ^a								
	CO	ROC	NOx	SOx	PM10	PM2.5	CO ₂	CH ₄	N ₂ O
Caterpillar D 150-8 150 ekW	0.69	0.04	0.13	0.00	0.01	0.01	127.17	0.01	0.00

^a Daily Emissions [lb/day] = Hourly Emissions [lb/hr-unit] x Operating Time [hr/day]

Equipment	Annual Op. (hr/year)	Annual Emissions (lb/year) ^a								
		CO	ROC	NOx	SOx	PM10	PM2.5	CO ₂	CH ₄	N ₂ O
Caterpillar D 150-8 150 ekW	50	68.63	3.70	13.20	0.12	0.53	5.53	12,717.48	0.51	0.10

^a Annual Emissions [lb/day] = Hourly Emissions [lb/hr-unit] x Operating Time [hr/year]

ST (g/s) 1.7295E-01 9.3127E-03 3.3259E-02 2.9656E-04 1.3304E-03 1.3304E-03
 Ann (g/s) 1.8983E-04 1.6927E-06 7.5933E-06 7.5933E-06

Table 11a Materials Recovery Facility and Anaerobic Digester Facility Equipment Diesel Fuel Storage Tank Emissions

TANKS 4.0 Report

TANKS 4.0.9d
Emissions Report - Detail Format
Tank Identification and Physical Characteristics

Identification
 User Identification: MRF/AD Tank
 City: Santa Barbara
 State: California
 Company: Mustang
 Type of Tank: Horizontal Tank
 Description: Diesel Storage tank for MRF & AD equipment.

Tank Dimensions
 Shell Length (ft): 27.00
 Diameter (ft): 8.00
 Volume (gallons): 10,000.00
 Turnovers: 24.00
 Net Throughput (gal/yr): 240,000.00
 Is Tank Heated (y/n): N
 Is Tank Underground (y/n): N

Paint Characteristics
 Shell Color/Shade: White/White
 Shell Condition: Good

Breather Vent Settings
 Vacuum Settings (psig): -0.03
 Pressure Settings (psig): 0.03

Meteorological Data used in Emissions Calculations: Santa Barbara, California (Avg Atmospheric Pressure = 14.65 psia)

Table 11a Materials Recovery Facility and Anaerobic Digester Facility Equipment Diesel Fuel Storage Tank Emissions

TANKS 4.0 Report

Page 2 of 5

**TANKS 4.0.9d
Emissions Report - Detail Format
Liquid Contents of Storage Tank**

**MRF/AD Tank - Horizontal Tank
Santa Barbara, California**

Material/Component	Month	Daily Liquid Ref. Temperature (deg F)			Liquid Pump Temp (deg F)	Vapor Pressure (psia)			Vapor Mol Weight	Liquid Mass Fract.	Vapor Mass Fract.	Mol Weight	Rele. to Vapor Pressure Calculations
		Avg	Min	Max		Avg	Min	Max					
diesel	All	51.25	52.71	60.00	59.12	0.0046	0.0086	0.0082	130.0500	0.0100	0.0450	188.00	Option 1: V=50 = 8065.57*7.0 = 564590
1,2,4-Trichlorobenzene						0.0216	0.0172	0.0209	120.1900	0.0100	0.0450	126.19	Option 2: A=7.04360, B=1073.207, C=2.09534
Benzene						1.1568	1.0350	1.4952	78.1100	0.0001	0.0021	78.11	Option 2: A=0.001, B=1211.000, C=220.70
Dibenzofuran						0.1136	0.0233	0.1372	156.1700	0.0001	0.0031	156.17	Option 2: A=0.075, B=1424.250, C=210.21
Hexamethylnitrosamine (H)						3.5762	1.7095	2.2907	86.1700	0.0000	0.0000	86.17	Option 2: A=0.016, B=1121.17, C=228.41
Toluene						0.1436	0.2856	0.6073	92.1300	0.0003	0.0073	92.13	Option 2: A=0.054, B=1544.8, C=219.48
Undersulfur Compounds						0.0046	0.0083	0.0066	134.4772	0.0004	0.0074	186.00	
Xylenes (m-p)						0.0046	0.0076	0.1148	106.1700	0.0029	0.0381	106.17	Option 2: A=7.009, B=1462.260, C=215.11

Table 11a Materials Recovery Facility and Anaerobic Digester Facility Equipment Diesel Fuel Storage Tank Emissions

TANKS 4.0 Report

TANKS 4.0.9d
Emissions Report - Detail Format
Detail Calculations (AP-42)

MRF/AD Tank - Horizontal Tank
Santa Barbara, California

Annual Emission Calculations	
Working Losses (lb)	19420
Vapor Space Volume (cu ft)	854.4362
Vapor Density (lb/cu ft)	0.0002
Vapor Space Expansion Factor	0.0002
Worked Vapor Saturation Factor	0.9998
Tank Vapor Space Volume	854.4362
Vapor Space Volume (cu ft)	854.4362
Tank Diameter (ft)	8.0000
Effective Diameter (ft)	16.0000
Vapor Space Depth (ft)	-4.0000
Tank Shell Length (ft)	37.0000
Vapor Density (lb/cu ft)	0.0002
Vapor Molecular Weight (lb/lb-moles)	136.0000
Vapor Pressure at Daily Average Liquid Surface Temperature (psia)	0.0004
Daily Avg. Liquid Surface Temp. (deg. F)	226.9532
Daily Average Ambient Temp. (deg. F)	59.1125
Ideal Gas Constant (R)	10.731
Shell Coeff. (1/deg. F)	0.163025
Liquid Bulk Temperature (deg. F)	5.1750
Tank Floor Solar Absorption (Btu/sq ft)	1.605000
Factor (Btu/sq ft)	
Vapor Space Expansion Factor	0.0002
Daily Vapor Temperature Range (deg. F)	22.2381
Daily Vapor Pressure Range (psia)	0.0002
Wobbe Index (Btu/cubic foot)	0.0002
Vapor Pressure at Daily Average Liquid Surface Temperature (psia)	0.0002
Vapor Pressure at Daily Minimum Liquid Surface Temperature (psia)	0.0002
Vapor Pressure at Daily Maximum Liquid Surface Temperature (psia)	0.0002
Daily Avg. Liquid Surface Temp. (deg. F)	226.9532
Daily Min. Liquid Surface Temp. (deg. F)	216.3512
Daily Max. Liquid Surface Temp. (deg. F)	236.5552
Daily Ambient Temp. (deg. F)	20.3300
Worked Vapor Saturation Factor	0.9998
Vapor Pressure at Daily Average Liquid Surface Temperature (psia)	0.0002
Vapor Space Coeff. (ft)	4.0000
Vapor Molecular Weight (lb/lb-moles)	136.0000
Vapor Pressure at Daily Average Liquid Surface Temperature (psia)	0.0002
Annual Fuel Throughput (gal/yr.)	240.000000
Annual Turnover	74.0000
Turnover Factor	1.0000
Tank Diameter (ft)	8.0000
Working Loss Coefficient	1.0000
Total Losses (lb)	7.6000

Table 11a Materials Recovery Facility and Anaerobic Digester Facility Equipment Diesel Fuel Storage Tank Emissions

TANKS 4.0 Report

Page 4 of 5

**TANKS 4.0.9d
Emissions Report - Detail Format
Individual Tank Emission Totals**

Emissions Report for: Annual

**MRFAD Tank - Horizontal Tank
Santa Barbara, California**

Component	Losses (lb)		Total Emissions
	Working Loss	Breathing Loss	
Diesel	5.07	1.94	7.01
Benzene	0.01	0.00	0.01
Toluene	0.12	0.05	0.16
Ethylbenzene	0.02	0.01	0.02
Xylene (m)	0.29	0.11	0.41
1,2,4-Trimethylbenzene	0.23	0.09	0.32
Unidentified Components	4.39	1.68	6.08
Hexane (n)	0.00	0.00	0.00

Table 11b Emergency Generator Diesel Fuel Storage Tank Emissions
TANKS 4.0 Report

TANKS 4.0.9d
Emissions Report - Detail Format
Tank Identification and Physical Characteristics

Identification
 User Identification: Emergency Generator Tank
 City: California
 State: California
 Company:
 Type of Tank: Horizontal Tank
 Description: Diesel tank in skid for emergency generator

Tank Dimensions
 Shell Length (ft): 13.00
 Diameter (ft): 3.00
 Volume (gallons): 402.00
 Turnovers: 2.50
 Net Throughput (gal/yr): 1,005.00
 Is Tank Heated (y/n): N
 Is Tank Underground (y/n): N

Paint Characteristics
 Shell Color/Shade: Gray/Medium
 Shell Condition: Good

Breather Vent Settings
 Vacuum Settings (psig): -0.03
 Pressure Settings (psig): 0.03

Meteorological Data used in Emissions Calculations: Santa Barbara, California (Avg Atmospheric Pressure = 14.65 psia)

TANKS 4.0.9d
Emissions Report - Detail Format
Liquid Contents of Storage Tank

Emergency Generator Tank - Horizontal Tank

Mixture Component	Month	Daily Liquid Cup Temperature (deg F)			Liquid Bulk Temp (deg F)	Vapor Pressure (psia)			Vapor Mol. Weight	Liquid Mass Fract.	Vapor Mass Fract.	Mol. Weight	Basis for Vapor Pressure Calculations
		Avg	Min	Max		Avg	Min	Max					
Distillate Fuel oil no. 2	All	69.43	58.16	80.79	62.19	0.0089	0.0061	0.0123	130.0000			188.00	Option 1: VP60 = 0.005 VP70 = 0.00

Table 11b Emergency Generator Diesel Fuel Storage Tank Emissions
TANKS 40 Renort

Emergency Generator Tank - Horizontal Tank

Annual Emission Calculations	
Standing Losses (lb):	0.3547
Vapor Space Volume (cu ft):	55.5297
Vapor Density (lb/cu ft):	0.0022
Vapor Space Expansion Factor:	0.0818
Vented Vapor Saturation Factor:	0.9993
Tank Vapor Space Volume	
Vapor Space Volume (cu ft):	55.5297
Tank Diameter (ft):	3.0000
Effective Diameter (ft):	7.0455
Vapor Space Outage (ft):	1.5000
Tank Shell Length (ft):	13.0000
Vapor Density	
Vapor Density (lb/cu ft):	0.0022
Vapor Molecular Weight (lb/lb-mole):	130.0000
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):	0.0089
Daily Avg. Liquid Surface Temp. (deg. R):	529.1455
Daily Average Ambient Temp. (deg. F):	59.1125
Ideal Gas Constant R (psia cu ft / (lb-mol-deg R)):	10.731
Liquid Bulk Temperature (deg. R):	521.8825
Tank Paint Solar Absorptance (Shell):	0.6500
Daily Total Solar Insolation Factor (Btu/sqft day):	1,605.0000
Vapor Space Expansion Factor	
Vapor Space Expansion Factor:	0.0818
Daily Vapor Temperature Range (deg. R):	45.2503
Daily Vapor Pressure Range (psia):	0.0052
Breather Vent Press. Setting Range (psia):	0.0000
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):	0.0089
Vapor Pressure at Daily Minimum Liquid Surface Temperature (psia):	0.0061
Vapor Pressure at Daily Maximum Liquid Surface Temperature (psia):	0.0123
Daily Avg. Liquid Surface Temp. (deg. R):	529.1455
Daily Min. Liquid Surface Temp. (deg. R):	517.8329
Daily Max. Liquid Surface Temp. (deg. R):	540.4581
Daily Ambient Temp. Range (deg. R):	20.3250
Vented Vapor Saturation Factor	
Vented Vapor Saturation Factor:	0.9993
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):	0.0089
Vapor Space Outage (ft):	1.5000
Working Losses (lb)	
Working Losses (lb):	0.0276
Vapor Molecular Weight (lb/lb-mole):	130.0000
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):	0.0089
Annual Net Throughput (gal/yr.):	1,005.0000
Annual Turnovers:	2.5000
Turnover Factor:	1.0000
Tank Diameter (ft):	3.0000
Working Loss Product Factor:	1.0000
Total Losses (lb) :	0.3823

TANKS 4.0.9d
Emissions Report - Detail Format
Individual Tank Emission Totals

Emissions Report for: Annual

Emergency Generator Tank - Horizontal Tank

Components	Losses(lbs)		Total Emissions
	Working Loss	Breathing Loss	
Distillate fuel oil no. 2	0.03	0.35	0.38

TANKS 4.0.9d
Emissions Report - Detail Format
Individual Tank Emission Totals

Emissions Report for: Annual

Emergency Generator Tank - Horizontal Tank

Components	Losses(lbs)		Total Emissions
	Working Loss	Breathing Loss	
Hexane (-n)	0.00	0.00	0.00
Benzene	0.00	0.00	0.00
Toluene	0.00	0.01	0.01
Ethylbenzene	0.00	0.00	0.00
Distillate fuel oil no. 2	0.03	0.35	0.38
Xylene (-m)	0.00	0.02	0.02
1,2,4-Trimethylbenzene	0.00	0.02	0.02
Unidentified Components	0.02	0.31	0.33

Table 12 Equipment Exhaust Emissions

Equipment	Horsepower	Number	Hours/Day	Fuel Use (gal/hr)	Emission Stds.	Emission Factors (g/bhp-hr) ^a					Emission Factor [g/gal]		
						CO	ROC ^b	NOx ^b	PM10 ^c	PM2.5 ^c	CO ₂ ^d	CH ₄ ^e	N ₂ O ^e
Materials Recovery Facility Building													
Caterpillar M322D Material Handler	173	1	16	2.7	Tier 4	3.7	0.14	0.3	0.015	0.015	10,210	0.58	0.26
CAT 966 M Loader	311	2	16	3.1	Tier 4	2.7	0.14	0.3	0.015	0.015	10,210	0.58	0.26
CAT 938 K Loader	169	1	16	2.7	Tier 4	3.7	0.14	0.3	0.015	0.015	10,210	0.58	0.26
CAT 2P-6000 Forklift	61	3	16	1.5	Tier 4	3.7	0.18	3.33	0.02	0.02	10,210	0.58	0.26
Tennant 800 Sweeper	65	1	24	4	Tier 4	3.7	0.18	3.33	0.02	0.02	10,210	0.58	0.26
Anaerobic Digestion Facility Building													
CAT 938 M Loader	169	2	8	3.5	Tier 4	3.7	0.14	0.3	0.015	0.015	10,210	0.58	0.26
Outside MRF Facility Building													
Tennant M30 Scrubber-Sweeper	41	1	6	4	Tier 4	3.7	0.18	3.33	0.02	0.02	10,210	0.58	0.26
Outside AD Facility Building													
Tennant M30 Scrubber-Sweeper	41	1	6	4	Tier 4	3.7	0.18	3.33	0.02	0.02	10,210	0.58	0.26
Composting Area													
CAT 938 K Loader	169	1	8	2.7	Tier 4	3.7	0.14	0.3	0.015	0.015	10,210	0.58	0.26
Backhus A55 Windrow Turner	235	1	8	12	Tier 4	2.6	0.14	0.3	0.015	0.015	10,210	0.58	0.26

^a Emission factors assumed the same as emission standards.

^b Where standard is for NMHC+NOx (Volvo L20F, Toyota forklifts and Tennant sweeper), emissions assumed to be 5 percent ROC and 95 percent NOx, from Table D-25 of 2011 Carl Moyer Program Guidelines - <http://www.arb.ca.gov/msprog/moyer/guidelines/current.htm>

^c PM10 and PM2.5 assumed to be same as PM emission standards.

^d From Table C-1 of Title 40, Code of Federal Regulations, Subpart 98 for No. 2 distillate fuel oil.

^e CH₄ and N₂O from Table 13.7 of 2013 Climate Action Registry Default Emission Factors, downloaded from <http://www.theclimateregistry.org/downloads/2013/01/2013-Climat-Registry-Default-Emissions-Factors.pdf>

Equipment	Load Factor ^c	Emission Rates Each Unit (lb/hr)								
		CO ^a	ROC ^a	NOx ^a	SOx ^b	PM10 ^{b,d}	PM2.5 ^{b,d}	CO ₂ ^e	CH ₄ ^e	N ₂ O ^e
Materials Recovery Facility Building										
Caterpillar M322D Material Handler	0.3618	0.511	0.019	0.041	0.00056	2.07E-06	2.07E-06	60.77	3.45E-03	1.55E-03
CAT 966 M Loader	0.3618	0.670	0.035	0.074	0.00065	3.72E-06	3.72E-06	69.78	3.96E-03	1.78E-03
CAT 938 K Loader	0.3618	0.499	0.019	0.040	0.00056	2.02E-06	2.02E-06	60.77	3.45E-03	1.55E-03
CAT 2P-6000 Forklift	0.201	0.100	0.005	0.090	0.00031	5.41E-07	5.41E-07	33.76	1.92E-03	8.60E-04
Tennant 800 Sweeper	0.4556	0.242	0.011	0.217	0.00083	1.31E-06	1.31E-06	90.04	5.11E-03	2.29E-03
Anaerobic Digestion Facility Building										
CAT 938 M Loader	0.3618	0.499	0.019	0.040	0.00073	2.02E-06	2.02E-06	78.78	4.48E-03	2.01E-03
Outside MRF Facility Building										
Tennant M30 Scrubber-Sweeper	0.4556	0.152	0.007	0.137	0.00083	8.24E-04	8.24E-04	90.04	5.11E-03	2.29E-03
Outside AD Facility Building										
Tennant M30 Scrubber-Sweeper	0.4556	0.152	0.007	0.137	0.00083	8.24E-04	8.24E-04	90.04	5.11E-03	2.29E-03
Composting Area										
CAT 938 K Loader	0.3618	0.499	0.019	0.040	0.00056	2.02E-06	2.02E-06	60.77	3.45E-03	1.55E-03
Backhus A55 Windrow Turner	0.3953	0.532	0.029	0.061	0.00250	0.00307	0.00307	270.11	1.53E-02	6.88E-03

Diesel Fuel Density =

6.943 lb/gal

Diesel Fuel Sulfur =

15 ppmw

^a Emission Rate [lb/hr] = Emission Factor [g/bhp-hr] x Engine Horsepower [hp] x Load Factor [unitless] / 453.6 [g/lb]

^b Emission Rate [lb/hr] = Fuel Use [gal/hr] x Fuel Density [lb/gal] x Fuel Sulfur [ppmw] x 10⁻⁶ x 2 [lb SO₂/lb S]

^c From OFFROAD 2011 model

Table 12 Equipment Exhaust Emissions

^d PM10 and PM2.5 emissions from buildings controlled by dust collectors with 99.9 percent control efficiency

^e Emission rate [lb/hr] = Fuel use [gal/hr] x Emission factor [g/gal] / 453.6 [lb/gal]

Equipment	Daily Emissions (lb/day) ^a								
	CO	ROC	NOx	SOx	PM10	PM2.5	CO ₂	CH ₄	N ₂ O
Materials Recovery Facility Building									
Caterpillar M322D Material Handler	8.17	0.31	0.66	0.01	3.31E-05	3.31E-05	972.38	0.06	0.02
CAT 966 M Loader	21.43	1.11	2.38	0.02	1.19E-04	1.19E-04	2,232.87	0.13	0.06
CAT 938 K Loader	7.98	0.30	0.65	0.01	3.24E-05	3.24E-05	972.38	0.06	0.02
CAT 2P-6000 Forklift	4.80	0.23	4.31	0.01	2.59E-05	2.59E-05	1,620.63	0.09	0.04
Tennant 800 Sweeper	5.80	0.27	5.21	0.02	3.13E-05	3.13E-05	2,160.85	0.12	0.06
Total	48.18	2.22	13.21	0.07	2.42E-04	2.42E-04	7,959.12	0.45	0.20
Anaerobic Digestion Facility Building									
CAT 938 M Loader	7.98	0.30	0.65	0.01	3.24E-05	3.24E-05	1,260.49	0.07	0.03
Total	7.98	0.30	0.65	0.01	0.00	0.00	1,260.49	0.07	0.03
Outside MRF Facility Building									
Tennant M30 Scrubber-Sweeper	0.91	0.04	0.82	5.00E-03	4.94E-03	4.94E-03	540.21	0.03	0.01
Total	0.91	0.04	0.82	0.00	0.00	0.00	540.21	0.03	0.01
Outside AD Facility Building									
Tennant M30 Scrubber-Sweeper	0.91	0.04	0.82	5.00E-03	4.94E-03	4.94E-03	540.21	0.03	0.01
Total	0.91	0.04	0.82	0.00	0.00	0.00	540.21	0.03	0.01
Composting Area									
CAT 938 K Loader	3.99	0.15	0.32	4.50E-03	1.62E-05	1.62E-05	486.19	0.03	0.01
Backhus A55 Windrow Turner	4.26	0.23	0.49	0.02	0.02	0.02	2,160.85	0.12	0.06
Total	8.25	0.38	0.82	0.02	0.02	0.02	2,647.04	0.15	0.07

^a Daily Emissions [lb/day] = Hourly Emissions [lb/hr-unit] x Number Units x Operating Time [hr/day]

Equipment	Days/Year	Annual Emissions (lb/year) ^a								
		CO	ROC	NOx	SOx	PM10	PM2.5	CO ₂	CH ₄	N ₂ O
Materials Recovery Facility Building										
Caterpillar M322D Material Handler	311	2,540.53	96.13	205.99	2.80	0.01	0.01	3.02E+05	17.18	7.70
CAT 966 M Loader	311	6,665.46	345.62	740.61	6.43	0.04	0.04	6.94E+05	39.45	17.68
CAT 938 K Loader	311	2,481.79	93.91	201.23	2.80	0.01	0.01	3.02E+05	17.18	7.70
CAT 2P-6000 Forklift	311	1,492.99	70.61	1,341.67	4.66	0.01	0.01	5.04E+05	28.63	12.83
Tennant 800 Sweeper	311	1,803.01	85.28	1,620.27	6.22	0.01	0.01	6.72E+05	38.18	17.11
Total		14,983.77	691.54	4,109.76	22.91	0.08	0.08	2.48E+06	140.61	63.03
Anaerobic Digestion Facility Building										
CAT 938 M Loader	208	1,659.84	62.80	134.58	2.43	0.01	0.01	2.62E+05	14.89	6.68
Total		1,659.84	62.80	134.58	2.43	0.01	0.01	2.62E+05	14.89	6.68
Outside MRF Facility Building										
Tennant M30 Scrubber-Sweeper	311	284.32	13.45	255.50	1.55	1.54	1.54	1.68E+05	9.54	4.28
Total		284.32	13.45	255.50	1.55	1.54	1.54	1.68E+05	9.54	4.28
Outside AD Facility Building										
Tennant M30 Scrubber-Sweeper	311	284.32	13.45	255.50	1.55	1.54	1.54	1.68E+05	9.54	4.28
Total		284.32	13.45	255.50	1.55	1.54	1.54	1.68E+05	9.54	4.28
Composting Area										
CAT 938 K Loader	311	1,240.89	46.95	100.61	1.40	0.01	0.01	1.51E+05	8.59	3.85

Table 12

Equipment Exhaust Emissions

Backhus A55 Windrow Turner	52	221.51	11.93	25.56	1.04	1.28	1.28	1.12E+05	6.38	2.86
Total		221.51	11.93	25.56	1.04	1.28	1.28	1.12E+05	6.38	2.86

^a Annual Emissions [lb/year] = Daily Emissions [lb/day] x Operating Days [days/year]

Table 13 On-Site Motor Vehicle Exhaust Emissions without CSSR

Vehicle	Use	Fuel	Segment	Mileage (mpg) ^c	Round-Trip Dist. (mi)	Round-Trips/Day	Miles/Day	Fuel Use (gal/day) ^d
Freightliner Tractor	Compost Export ^a	CNG	MRF-Compost	6	0.90	4	3.61	0.60
Freightliner Tractor	Compost Export ^b	CNG	MRF-Entrance	6	2.23	4	8.92	1.49
Freightliner Tractor	Recycleables to POLA ^b	CNG	MRF-Entrance	6	2.23	13	28.99	4.83
Ford F350 XL	Utility truck and trailer	Diesel	MRF-Compost	14	0.90	6	5.41	0.39
Ford F350 XL	Utility truck and trailer	Diesel	MRF-Entrance	14	2.23	6	13.38	0.96

^a Round trips/day = 25,760 tons/yr / 311 op. days/yr / 22 tons/trip = 3.8 trips/day rounded up to 4 trips/day

^b Round trips/day = 90,000 tons/yr / 311 op. days/yr / 22 tons/trip = 13.2 one-way trips/day rounded to 13

^c Mileage for Freightliner Tractor is diesel-equivalent

^d Fuel use [gal/day] = Daily mileage (miles/day) / Mileage [mpg]

Vehicle	Use	Emission Factors (g/ml)								
		CO ^a	ROC ^b	NOx ^b	SOx ^c	PM10 ^b	PM2.5 ^b	CO ₂ ^d	CH ₄ ^e	N ₂ O ^{f,g}
Freightliner Tractor	Compost Export	1.23E+00	3.70E-01	4.60E-01	6.80E-03	2.90E-02	2.90E-02	1.13E+03	1.97E+00	1.75E-01
Freightliner Tractor	Recycleables to POLA	1.23E+00	3.70E-01	4.60E-01	6.80E-03	2.90E-02	2.90E-02	1.13E+03	1.97E+00	1.75E-01
Ford F350 XL	Utility truck and trailer	1.71E-01	2.63E-02	4.69E-01	6.75E-03	4.90E-03	4.90E-03	4.93E+02	1.00E-03	2.37E-02

Diesel Fuel HV = 128,450 Btu/gal

Natural Gas HV = 1,020 Btu/scf

Natural Gas S = 0.5 grains/100 scf

Diesel Fuel Density = 6.943 lb/gal

Diesel Fuel Sulfur = 15 ppmw

Natural Gas CO₂ EF = 0.054 Kg/scf

from Table 13.1 of 2013 Climate Action Registry Default Emission Factors, downloaded from <http://www.theclimaterestory.org/downloads/2013/01/2013-Cliamte-Registry-Default-Emissions-Factors.pdf>

^a Freightliner tractor is 2010 and later model year standard in g/bhp-hr converted to g/ml using conversion factor from Table D-25 of 2011 Carl Moyer Program Guidelines - <http://www.arb.ca.gov/msprog/moyer/guidelines/current.htm>
Ford F350 XL is from EMFAC2011 emission rates for 2017 model year light heavy-duty truck 2 in Santa Barbara County at 45 mph in calendar year 2017 <http://www.arb.ca.gov/emfac/>

^b Freightliner tractor is 2010 and later model year standard from Table D-1a of 2011 Carl Moyer Program Guidelines - <http://www.arb.ca.gov/msprog/moyer/guidelines/current.htm>
Ford F350 XL is from EMFAC2011 emission rates for 2017 model year light heavy-duty truck 2 in Santa Barbara County at 45 mph in calendar year 2017 <http://www.arb.ca.gov/emfac/>

^c Freightliner tractor calculated from (1/diesel-equivalent mpg) x diesel fuel heating value (Btu/gal) / natural gas heating value (Btu/scf) x natural gas sulfur content (grains/100 scf) / 100 / 7,000 (grains/lb) x 453.6 (g/lb) x 2 (g SO₂/g S)
Ford F350 XL calculated from (1/diesel mpg) x diesel fuel density (lb/gal) x diesel fuel sulfur (ppmw) x 10⁻⁶ x 453.6 (g/lb) x 2 (g SO₂/g S)

^d Freightliner tractor calculated from (1/diesel-equivalent mpg) x diesel fuel heating value (Btu/gal) / natural gas heating value (Btu/scf) x natural gas CO₂ EF (kg/scf) x 1,000 (g/kg)
CO₂ emission factor from Table 13.1 of 2013 Climate Action Registry Default Emission Factors, downloaded from <http://www.theclimaterestory.org/downloads/2013/01/2013-Cliamte-Registry-Default-Emissions-Factors.pdf>
Ford F350 XL is from EMFAC2011 emission rates for 2017 model year light heavy-duty truck 2 in Santa Barbara County at 45 mph in calendar year 2017 <http://www.arb.ca.gov/emfac/>

^e Freightliner Tractor from Table 13.6 of 2013 Climate Action Registry Default Emission Factors, downloaded from <http://www.theclimaterestory.org/downloads/2013/01/2013-Cliamte-Registry-Default-Emissions-Factors.pdf>
Ford F350 XL is from EMFAC2011 emission rates for 2017 model year light heavy-duty truck 2 in Santa Barbara County at 45 mph in calendar year 2017 <http://www.arb.ca.gov/emfac/>

^f Emission factor for Ford F350 XL calculated as 0.3316 [g/gal] / mileage [mpg]; see: http://www.arb.ca.gov/msei/emfac2011-faq.htm#emfac2011_web_db_qstn07

Table 13 On-Site Motor Vehicle Exhaust Emissions without CSSR

Vehicle	Use	Segment	Daily Emissions (lb/day) ^a								
			CO	ROC	NOx	SOx	PM10	PM2.5	CO ₂	CH ₄	N ₂ O
Freightliner Tractor	Compost Export	MRF-Compost	9.76E-03	2.94E-03	3.66E-03	5.41E-05	2.31E-04	2.31E-04	9.02E+00	1.56E-02	1.39E-03
Freightliner Tractor	Compost Export	MRF-Entrance	2.41E-02	7.28E-03	9.05E-03	1.34E-04	5.70E-04	5.70E-04	2.23E+01	3.87E-02	3.44E-03
Freightliner Tractor	Recycleables to POLA	MRF-Entrance	7.84E-02	2.36E-02	2.94E-02	4.35E-04	1.85E-03	1.85E-03	7.24E+01	1.26E-01	1.12E-02
Ford F350 XL	Utility truck and trailer	MRF-Compost	2.04E-03	3.14E-04	5.60E-03	8.05E-05	5.85E-05	5.85E-05	5.88E+00	1.19E-05	2.83E-04
Ford F350 XL	Utility truck and trailer	MRF-Entrance	5.04E-03	7.76E-04	1.38E-02	1.99E-04	1.45E-04	1.45E-04	1.45E+01	2.95E-05	6.99E-04
Total			1.19E-01	3.50E-02	6.15E-02	9.02E-04	2.86E-03	2.86E-03	1.24E+02	1.80E-01	1.70E-02

^a Daily emissions [lb/day] = Miles/day x Emission factor [g/mi] / 453.6 [g/lb]

Vehicle	Use	Segment	Days/Year	Annual Emissions (lb/year) ^a								
				CO	ROC	NOx	SOx	PM10	PM2.5	CO ₂	CH ₄	N ₂ O
Freightliner Tractor	Compost Export	MRF-Compost	311	3.03	0.92	1.14	0.02	0.07	0.07	2,803.69	4.86	0.43
Freightliner Tractor	Compost Export	MRF-Entrance	311	7.50	2.26	2.81	0.04	0.18	0.18	6,931.52	12.02	1.07
Freightliner Tractor	Recycleables to POLA	MRF-Entrance	311	24.38	7.35	9.14	0.14	0.58	0.58	22,527.45	39.08	3.48
Ford F350 XL	Utility truck and trailer	MRF-Compost	311	0.63	0.10	1.74	0.03	0.02	0.02	1,829.51	0.00	0.09
Ford F350 XL	Utility truck and trailer	MRF-Entrance	311	1.57	0.24	4.30	0.06	0.04	0.04	4,523.06	0.01	0.22
Total				37.12	10.87	19.14	0.28	0.89	0.89	38,615.23	55.98	5.29

^a Annual emissions [lb/year] = Daily emissions [lb/day] x Operating days/year

Table 14 On-Site Motor Vehicle Exhaust Emissions with CSSR

Vehicle	Use	Fuel	Segment	Mileage (mpg) ^a	Round-Trip Dist. (mi)	Round-Trips/Day	Miles/Day	Fuel Use (gal/day) ^e
Freightliner Tractor	Compost Export ^a	CNG	MRF-Compost	6	0.90	4	3.61	0.60
Freightliner Tractor	Compost Export ^b	CNG	MRF-Entranca	6	2.23	4	8.92	1.49
Freightliner Tractor	Recycleables to POLA ^c	CNG	MRF-Entranca	6	2.23	18	40.14	6.69
Tractor/Trailer	CSSR Import ^c	Diesel	MRF-Entranca	6	2.23	7	15.61	2.60
Ford F350 XL	Utility truck and trailer	Diesel	MRF-Compost	14	0.90	6	5.41	0.39
Ford F350 XL	Utility truck and trailer	Diesel	MRF-Entranca	14	2.23	6	13.38	0.86

^a Round trips/day = 25,760 tons/yr / 311 op. days/yr / 22 tons/trip = 3.8 trips/day rounded up to 4 trips/day

^b Round trips/day = 126,000 tons/yr / 311 op. days/yr / 22 tons/trip = 18.4 round trips/day rounded to 18

^c Trips/day are from Project Traffic Study.

^d Mileage for Freightliner Tractor is diesel-equivalent

^e Fuel use [gal/day] = Daily mileage [miles/day] / Mileage [mpg]

Vehicle	Use	Emission Factors (g/mi)								
		CO ^a	ROC ^b	NO _x ^b	SO _x ^c	PM10 ^b	PM2.5 ^b	CO ₂ ^a	CH ₄ ^a	N ₂ O ^{a,d}
Freightliner Tractor	Compost Export	1.23E+00	3.70E-01	4.60E-01	6.80E-03	2.90E-02	2.90E-02	1.13E+03	1.97E+00	1.75E-01
Freightliner Tractor	Recycleables to POLA	1.23E+00	3.70E-01	4.60E-01	6.80E-03	2.90E-02	2.90E-02	1.13E+03	1.97E+00	1.75E-01
Tractor/Trailer	CSSR Import	1.23E+00	5.04E-01	1.91E+00	1.57E-02	3.66E-02	3.39E-02	2.55E+03	1.00E-03	5.53E-02
Ford F350 XL	Utility truck and trailer	1.71E-01	2.63E-02	4.69E-01	6.75E-03	4.90E-03	4.90E-03	4.93E+02	1.00E-03	2.37E-02

Diesel Fuel HV = 128,450 Btu/gal

Natural Gas HV = 1,020 Btu/scf

Natural Gas S = 0.5 grains/100 scf

Diesel Fuel Density = 6.943 lb/gal

Diesel Fuel Sulfur = 15 ppmw

Natural Gas CO₂, EF = 0.054 Kg/scf

from Table 13.1 of 2013 Climate Action Registry Default Emission Factors, downloaded from

<http://www.theclimaterestory.org/downloads/2013/01/2013.Climate.Registry.Default.Emissions.Factors.pdf>

^a Freightliner tractor is 2010 and later model year standard in g/bhp-hr converted to g/mi using conversion factor from Table D-28 of 2011 Carl Moyer Program Guidelines - <http://www.arb.ca.gov/msprog/moyer/guidelines/current.htm>

Tractor/trailer is from EMFAC2011 emission rates for T7 trucks in Santa Barbara County

at 15 mph in calendar year 2017 <http://www.arb.ca.gov/emfac/>

Ford F350 XL is from EMFAC2011 emission rates for 2017 model year light heavy-duty truck 2 in Santa Barbara County

at 45 mph in calendar year 2017 <http://www.arb.ca.gov/emfac/>

^b Freightliner tractor is 2010 and later model year standard from Table D-1a of 2011 Carl Moyer Program Guidelines -

<http://www.arb.ca.gov/msprog/moyer/guidelines/current.htm>

Tractor/trailer is from EMFAC2011 emission rates for T7 trucks in Santa Barbara County

at 15 mph in calendar year 2017 <http://www.arb.ca.gov/emfac/>

Ford F350 XL is from EMFAC2011 emission rates for 2017 model year light heavy-duty truck 2 in Santa Barbara County

at 45 mph in calendar year 2017 <http://www.arb.ca.gov/emfac/>

^c Freightliner tractor calculated from (1/diesel-equivalent mpg) x diesel fuel heating value (Btu/gal) /

natural gas heating value (Btu/scf) x natural gas sulfur content (grains/100 scf) / 100 / 7,000 (grains/lb) x 453.6 (g/lb) x 2 (g SO₂/g S)

Ford F350 XL and Tractor/trailer calculated from (1/diesel mpg) x diesel fuel density (lb/gal) x diesel fuel sulfur (ppmw) x 10⁻⁶ x 453.6 (g/lb) x 2(g SO₂/g S)

^d Freightliner tractor calculated from (1/diesel-equivalent mpg) x diesel fuel heating value (Btu/gal) /

natural gas heating value (Btu/scf) x natural gas CO₂, EF (kg/scf) x 1,000 (g/kg)

CO₂ emission factor from Table 13.1 of 2013 Climate Action Registry Default Emission Factors, downloaded from

<http://www.theclimaterestory.org/downloads/2013/01/2013.Climate.Registry.Default.Emissions.Factors.pdf>

Tractor/trailer is from EMFAC2011 emission rates for T7 trucks in Santa Barbara County

at 15 mph in calendar year 2017 <http://www.arb.ca.gov/emfac/>

Ford F350 XL is from EMFAC2011 emission rates for 2017 model year light heavy-duty truck 2 in Santa Barbara County

at 45 mph in calendar year 2017 <http://www.arb.ca.gov/emfac/>

^e Freightliner Tractor from Table 13.6 of 2013 Climate Action Registry Default Emission Factors, downloaded from

<http://www.theclimaterestory.org/downloads/2013/01/2013.Climate.Registry.Default.Emissions.Factors.pdf>

Tractor/trailer is from EMFAC2011 emission rates for T7 trucks in Santa Barbara County

at 15 mph in calendar year 2017 <http://www.arb.ca.gov/emfac/>

Ford F350 XL is from EMFAC2011 emission rates for 2017 model year light heavy-duty truck 2 in Santa Barbara County

at 45 mph in calendar year 2017 <http://www.arb.ca.gov/emfac/>

^f Emission factor for Ford F350 XL calculated as 0.3316 [g/gal] / mileage [mpg]; see:

http://www.arb.ca.gov/msel/emfac2011-faq.htm#emfac2011_web_db_qstn07

Table 14 On-Site Motor Vehicle Exhaust Emissions with CSSR

Vehicle	Use	Segment	Daily Emissions (lb/day) ^a								
			CO	ROC	NOx	SOx	PM10	PM2.5	CO ₂	CH ₄	N ₂ O
Freightliner Tractor	Compost Export	MRF-Compost	9.76E-03	2.94E-03	3.66E-03	5.41E-05	2.31E-04	2.31E-04	9.02E+00	1.56E-02	1.39E-03
Freightliner Tractor	Compost Export	MRF-Entrance	2.41E-02	7.28E-03	9.05E-03	1.34E-04	5.70E-04	5.70E-04	2.23E+01	3.87E-02	3.44E-03
Freightliner Tractor	Recycleables to POLA	MRF-Entrance	1.09E-01	3.27E-02	4.07E-02	6.02E-04	2.57E-03	2.57E-03	1.00E+02	1.74E-01	1.55E-02
Tractor/Trailer	CSSR Import	MRF-Entrance	4.22E-02	1.73E-02	6.59E-02	5.42E-04	1.27E-03	1.17E-03	8.77E+01	3.44E-05	1.90E-03
Ford F350 XL	Utility truck and trailer	MRF-Compost	2.04E-03	3.14E-04	5.60E-03	8.05E-05	5.85E-05	5.85E-05	5.88E+00	1.19E-05	2.83E-04
Ford F350 XL	Utility truck and trailer	MRF-Entrance	5.04E-03	7.76E-04	1.38E-02	1.99E-04	1.45E-04	1.45E-04	1.45E+01	2.95E-05	6.99E-04
Total			1.92E-01	6.14E-02	1.39E-01	1.61E-03	4.84E-03	4.74E-03	2.40E+02	2.28E-01	2.32E-02

^a Daily emissions [lb/day] = Miles/day x Emission factor [g/mi] / 453.6 [g/lb]

Vehicle	Use	Segment	Days/Year	Annual Emissions (lb/year) ^a								
				CO	ROC	NOx	SOx	PM10	PM2.5	CO ₂	CH ₄	N ₂ O
Freightliner Tractor	Compost Export	MRF-Compost	311	3.03	0.92	1.14	0.02	0.07	0.07	2,803.69	4.86	0.43
Freightliner Tractor	Compost Export	MRF-Entrance	311	7.50	2.26	2.81	0.04	0.18	0.18	6,931.52	12.02	1.07
Freightliner Tractor	Recycleables to POLA	MRF-Entrance	311	33.76	10.18	12.65	0.19	0.80	0.80	31,191.85	54.11	4.82
Tractor/Trailer	CSSR Import	MRF-Entrance	311	13.13	5.39	20.49	0.17	0.39	0.36	27,284.63	0.01	0.59
Ford F350 XL	Utility truck and trailer	MRF-Compost	311	0.63	0.10	1.74	0.03	0.02	0.02	1,829.51	0.00	0.09
Ford F350 XL	Utility truck and trailer	MRF-Entrance	311	1.57	0.24	4.30	0.06	0.04	0.04	4,523.06	0.01	0.22
Total				59.62	19.09	43.15	0.50	1.50	1.47	74,564.26	71.02	7.22

^a Annual emissions [lb/year] = Daily emissions [lb/day] x Operating days/year

Table 15 Off-Site Motor Vehicle Exhaust Emissions without CSSR

Vehicle	Use	Fuel	One-Way Trips/Day	Mileage (mpg) ^d	One-Way Trip Dist. (mi)	Miles/Day
Freightliner Tractors	Compost to North County ^a	CNG	8	6	57	456
Freightliner Tractors	Recycleables to POLA ^b	CNG	26	6	131	3,406
Pick-up Trucks (Ford 250 XL)	Miscellaneous ^c	Diesel	8	19	25	200
Worker Commuting	From the North ^e	Gasoline	45	22	37	1,665
Worker Commuting	From the South ^e	Gasoline	5	22	15	75

^a Round trips/day = 25,760 tons/yr / 311 op. days/yr / 22 tons/trip = 3.8 one-way trips/day x 2 = 7.6 one-way trips/day rounded up to 8

^b Round trips/day = 90,000 tons/yr / 311 op. days/yr / 22 tons/trip = 13.2 one-way trips/day x 2 = 26.4 one-way trips/day rounded to 26

^c Round trips/day are Mustang estimates

^d Except for Freightliner Tractor, calculated by dividing EMFAC2011 calculated total daily fuel use in Santa Barbara County in 2017 by total miles in Santa Barbara County
Mileage for Freightliner Tractor is diesel-equivalent, Mustang estimate

^e Trips/day are from Project Traffic Study

Vehicle	Use	EMFAC Vehicle Class	Emission Factors (g/mi)								
			CO ^{a,b}	ROC ^{a,c}	NO _x ^{a,c}	SO _x ^{a,d}	PM10 ^{a,c}	PM2.5 ^{a,c}	CO ₂ ^{a,e}	CH ₄ ^{a,f}	N ₂ O ^{a,g}
Freightliner Tractors	Compost to North County	N/A	1.17E+00	3.70E-01	4.60E-01	6.80E-03	2.90E-02	2.90E-02	1.13E+03	1.97E+00	1.75E-01
Freightliner Tractors	Recycleables to POLA	N/A	1.17E+00	3.70E-01	4.60E-01	6.80E-03	2.90E-02	2.90E-02	1.13E+03	1.97E+00	1.75E-01
Pick-up Trucks (Ford 250 XL)	Miscellaneous	LHD1	1.22E+00	2.23E-01	3.57E+00	5.02E-03	1.38E-01	8.12E-02	4.99E+02	1.22E-02	1.73E-02
Worker Commuting	From the North	LDT1	3.46E+00	3.06E-01	3.59E-01	3.81E-03	4.83E-02	2.10E-02	3.11E+02	2.52E-02	1.49E-02
Worker Commuting	From the South	LDT1	3.46E+00	3.06E-01	3.59E-01	3.81E-03	4.83E-02	2.10E-02	3.11E+02	2.52E-02	1.49E-02

Diesel Fuel HV = 128,450 Btu/gal

Natural Gas HV = 1,020 Btu/scf

Natural Gas S = 0.5 grains/100 scf

Diesel Fuel Density = 6.943 lb/gal

Diesel Fuel Sulfur = 15 ppmw

Natural Gas CO₂ EF = 0.054 Kg/scf from Table 13.1 of 2013 Climate Action Registry Default Emission Factors, downloaded from

<http://www.theclimaterestry.org/downloads/2013/01/2013-Climat-Registry-Default-Emissions-Factors.pdf>

^a Except for Freightliner Tractor, calculated by dividing EMFAC2011 calculated total daily emissions in Santa Barbara County in 2017 by total miles in Santa Barbara County

^b Freightliner tractor calculated by dividing EMFAC2011 calculated total daily CO emissions from 2017 model year T7 tractors in Santa Barbara County in 2017 by total miles in Santa Barbara County

^c Freightliner tractor is 2010 and later model year standard from Table D-1a of 2011 Carl Moyer Program Guidelines - <http://www.arb.ca.gov/msprog/moyer/guidelines/current.htm>

^d Freightliner tractor calculated from (1/diesel-equivalent mpg) x diesel fuel heating value (Btu/gal) / natural gas heating value (Btu/scf) x natural gas sulfur content (grains/100 scf) / 100 / 7,000 (grains/lb) x 453.6 (g/lb) x 2 (g SO₂/g S)

^e Freightliner tractor calculated from (1/diesel-equivalent mpg) x diesel fuel heating value (Btu/gal) / natural gas heating value (Btu/scf) x natural gas CO₂ EF (Kg/scf) x 1,000 (g/Kg)

^f Freightliner Tractor from Table 13.6 of 2013 Climate Action Registry Default Emission Factors, downloaded from <http://www.theclimaterestry.org/downloads/2013/01/2013-Climat-Registry-Default-Emissions-Factors.pdf>

^g Emission factor for gasoline calculated from 0.0416 x NO_x emission factor; emission factor for diesel calculated as 0.3316 g/gal; see: http://www.arb.ca.gov/msei/emfac2011-faq.htm#emfac2011_web_db_qstn07

Table 15

Off-Site Motor Vehicle Exhaust Emissions without CSSR

Vehicle	Use	Daily Emissions (lb/day) ^a								
		CO	ROC	NOx	SOx	PM10	PM2.5	CO ₂	CH ₄	N ₂ O
Freightliner Tractors	Compost to North County	1.17	0.37	0.46	0.01	0.03	0.03	1,139.38	1.98	0.18
Freightliner Tractors	Recycleables to POLA	8.76	2.78	3.45	0.05	0.22	0.22	8,510.36	14.76	1.31
Pick-up Trucks (Ford 250 XL)	Miscellaneous	0.54	0.10	1.57	0.00	0.06	0.04	220.21	0.01	0.01
Worker Commuting	From the North	12.72	1.12	1.32	0.01	0.18	0.08	1,142.67	0.09	0.05
Worker Commuting	From the South	0.57	0.05	0.06	0.00	0.01	0.00	51.47	0.00	0.00
Total		23.76	4.42	6.87	0.07	0.49	0.36	11,064.08	16.84	1.55

^a Daily emissions [lb/day] = Miles/day x Emission factor [g/mi] / 453.6 [g/lb]

Vehicle	Use	Op. Days/yr	Annual Emissions (lb/year) ^a								
			CO	ROC	NOx	SOx	PM10	PM2.5	CO ₂	CH ₄	N ₂ O
Freightliner Tractors	Compost to North County	311	364.69	115.68	143.82	2.13	9.07	9.07	354,346.90	614.66	54.71
Freightliner Tractors	Recycleables to POLA	311	2,723.97	864.04	1,074.21	15.88	67.72	67.72	2,646,722.64	4,591.09	408.67
Pick-up Trucks (Ford 250 XL)	Miscellaneous	311	167.22	30.62	489.43	0.69	18.90	11.14	68,483.80	1.67	2.37
Worker Commuting	From the North	311	3,955.46	349.49	409.44	4.35	55.17	23.98	355,369.04	28.77	17.03
Worker Commuting	From the South	311	178.17	15.74	18.44	0.20	2.49	1.08	16,007.61	1.30	0.77
Total			7,389.51	1,375.57	2,135.35	23.24	153.34	112.98	3,440,929.99	5,237.48	483.55

^a Annual emissions [lb/year] = Daily emissions [lb/day] x Operating days/year

Off-Site Motor Vehicle Fugitive PM Emissions

Emission Factors for Vehicles on Off-Site Paved Roads

Parameter	Value	Comments
Road silt loading (g/m ²)	0.1	CalEEMod default
Onroad vehicles average weight (tons)	2.4	CalEEMod Default for Santa Barbara County
PM10 emission factor (lb/mile)	6.61E-04	0.0022 x (silt loading [g/m ²]) ^{0.91} x (average vehicle weight) ^{1.02} from AP-42 Section 13.2.1, Paved Roads(01/11)
PM2.5 emission factor (lb/mile)	1.62E-04	0.00054 x (silt loading [g/m ²]) ^{0.91} x (average vehicle weight) ^{1.02} from AP-42 Section 13.2.1, Paved Roads(01/11)

Vehicle	Use	Miles/Day	Op. Days/yr	Daily Emissions (lb/day) ^a		Annual Emissions (lb/year) ^b	
				PM10	PM2.5	PM10	PM2.5
Freightliner Tractors	Compost to North County	456	311	0.30	0.07	93.75	23.01
Freightliner Tractors	Recycleables to POLA	3,406	311	2.25	0.55	700.23	171.88
Pick-up Trucks (Ford 250 XL)	Miscellaneous	200	311	0.13	0.03	41.12	10.09
Worker Commuting	From the North	1,665	311	1.10	0.27	342.30	84.02
Worker Commuting	From the South	75	311	0.05	0.01	15.42	3.78
Total				3.84	0.94	1,192.82	292.78

^a Daily emissions [lb/day] = Miles/day x Emission factor [lb/mi]

^b Annual emissions [lb/year] = Daily emissions [lb/day] x Operating days/year

Table 16 Off-Site Motor Vehicle Exhaust Emissions with CSSR

Vehicle	Use	Fuel	One-Way Trips/Day	Mileage (mpg) ^d	One-Way Trip Dist. (mi)	Miles/Day
Freightliner Tractors	Compost to North County ^a	CNG	8	6	57	456
Freightliner Tractors	Recycleables to POLA ^b	CNG	36	6	131	4,716
Tractor/Trailer	CSSR from SCRTS to Tajiguas instead of Gold Coast ^c	Diesel	14	6	-17	-238
Pick-up Trucks (Ford 250 XL)	Miscellaneous ^e	Diesel	8	19	25	200
Worker Commuting	From the North ^f	Gasoline	59	22	37	2,183
Worker Commuting	From the South ^f	Gasoline	7	22	15	105

^a Round trips/day = 25,760 tons/yr / 311 op. days/yr / 22 tons/trip = 3.8 one-way trips/day x 2 = 7.6 one-way trips/day rounded up to 8

^b Round trips/day = 126,000 tons/yr / 311 op. days/yr / 22 tons/trip = 18.4 one-way trips/day x 2 = 36.8 one-way trips/day rounded to 36

^c Round trips/day are Mustang estimates

^d Except for Freightliner Tractor, calculated by dividing EMFAC2011 calculated total daily fuel use in Santa Barbara County in 2017 by total miles in Santa Barbara County
Mileage for Freightliner Tractor is diesel-equivalent, Mustang estimate

^e Trips/day are from Project Traffic Study. Mileage is difference between SCRTS to Tajiguas (22 mi.) and SCRTS to Gold Coast (39 mi.)

^f Trips/day are from Project Traffic Study

Vehicle	Use	EMFAC Vehicle Class	Emission Factors (g/mi)								
			CO ^{a,b}	ROC ^{a,c}	NO _x ^{a,c}	SO _x ^{a,d}	PM10 ^{a,c}	PM2.5 ^{a,c}	CO ₂ ^{a,b}	CH ₄ ^{a,f}	N ₂ O ^g
Freightliner Tractors	Compost to North County	N/A	1.17E+00	3.70E-01	4.60E-01	6.80E-03	2.90E-02	2.90E-02	1.13E+03	1.97E+00	1.75E-01
Freightliner Tractors	Recycleables to POLA	N/A	1.17E+00	3.70E-01	4.60E-01	6.80E-03	2.90E-02	2.90E-02	1.13E+03	1.97E+00	1.75E-01
Tractor/Trailer	CSSR from SCRTS to Tajiguas instead of Gold Coast	T7 tractor	1.16E+00	2.53E-01	6.95E+00	1.69E-02	1.80E-01	1.11E-01	1.68E+03	1.38E-02	5.81E-02
Pick-up Trucks (Ford F250 XL)	Miscellaneous	LHD1	1.22E+00	2.23E-01	3.57E+00	5.02E-03	1.38E-01	8.12E-02	4.99E+02	1.22E-02	1.73E-02
Worker Commuting	From the North	LDT1	3.46E+00	3.06E-01	3.59E-01	3.81E-03	4.83E-02	2.10E-02	3.11E+02	2.52E-02	1.49E-02
Worker Commuting	From the South	LDT1	3.46E+00	3.06E-01	3.59E-01	3.81E-03	4.83E-02	2.10E-02	3.11E+02	2.52E-02	1.49E-02

Diesel Fuel HV = 128,450 Btu/gal

Natural Gas HV = 1,020 Btu/scf

Natural Gas S = 0.5 grains/100 scf

Diesel Fuel Density = 6.943 lb/gal

Diesel Fuel Sulfur = 15 ppmw

Natural Gas CO₂ EF = 0.054 Kg/scf from Table 13.1 of 2013 Climate Action Registry Default Emission Factors, downloaded from

<http://www.theclimaterestry.org/downloads/2013/01/2013-Climate-Registry-Default-Emissions-Factors.pdf>

^a Except for Freightliner Tractor, calculated by dividing EMFAC2011 calculated total daily emissions in Santa Barbara County in 2017 by total miles in Santa Barbara County

^b Freightliner tractor calculated by dividing EMFAC2011 calculated total daily CO emissions from 2017 model year T7 tractors in Santa Barbara County in 2017 by total miles in Santa Barbara County

^c Freightliner tractor is 2010 and later model year standard from Table D-1a of 2011 Carl Moyer Program Guidelines - <http://www.arb.ca.gov/msprog/moyer/guidelines/current.htm>

^d Freightliner tractor calculated from (1/diesel-equivalent mpg) x diesel fuel heating value (Btu/gal) / natural gas heating value (Btu/scf) x natural gas sulfur content (grains/100 scf) / 100 / 7,000 (grains/lb) x 453.6 (g/lb) x 2 (g SO₂/g S)

^e Freightliner tractor calculated from (1/diesel-equivalent mpg) x diesel fuel heating value (Btu/gal) / natural gas heating value (Btu/scf) x natural gas CO₂ EF (kg/scf) x 1,000 (g/kg)

^f Freightliner Tractor from Table 13.6 of 2013 Climate Action Registry Default Emission Factors, downloaded from <http://www.theclimaterestry.org/downloads/2013/01/2013-Climate-Registry-Default-Emissions-Factors.pdf>

^g Emission factor for gasoline calculated from 0.0416 x NO_x emission factor; emission factor for diesel calculated as 0.3316 [g/gal] / mileage [mpg]; see: http://www.arb.ca.gov/msei/emfac2011-faq.htm#emfac2011_web_db_qstrn07

Table 16

Off-Site Motor Vehicle Exhaust Emissions with CSSR

Vehicle	Use	Daily Emissions (lb/day) ^a								
		CO	ROC	NOx	SOx	PM10	PM2.5	CO ₂	CH ₄	N ₂ O
Freightliner Tractors	Compost to North County	1.17	0.37	0.46	0.01	0.03	0.03	1,139.38	1.98	0.18
Freightliner Tractors	Recycleables to POLA	12.13	3.85	4.78	0.07	0.30	0.30	11,783.58	20.44	1.82
Tractor/Trailer	CSSR from SCRTS to Tajiguas instead of Gold Coast	-0.61	-0.13	-3.65	-0.01	-0.09	-0.06	-880.47	-0.01	-0.03
Pick-up Trucks (Ford 250 XL)	Miscellaneous	0.54	0.10	1.57	0.00	0.06	0.04	220.21	0.01	0.01
Worker Commuting	From the North	16.68	1.47	1.73	0.02	0.23	0.10	1,498.16	0.12	0.07
Worker Commuting	From the South	0.80	0.07	0.08	0.00	0.01	0.00	72.06	0.01	0.00
Total		30.71	5.73	4.98	0.09	0.54	0.41	13,832.92	22.54	2.05

^a Daily emissions [lb/day] = Miles/day x Emission factor [g/mi] / 453.6 [g/lb]

Vehicle	Use	Op. Days/yr	Annual Emissions (lb/year) ^a								
			CO	ROC	NOx	SOx	PM10	PM2.5	CO ₂	CH ₄	N ₂ O
Freightliner Tractors	Compost to North County	311	364.69	115.68	143.82	2.13	9.07	9.07	354,346.90	614.66	54.71
Freightliner Tractors	Recycleables to POLA	311	3,771.65	1,196.36	1,487.37	21.99	93.77	93.77	3,664,692.89	6,356.89	565.85
Tractor/Trailer	CSSR from SCRTS to Tajiguas instead of Gold Coast	311	-189.68	-41.25	-1,134.46	-2.75	-29.39	-18.15	-273,825.41	-2.25	-9.48
Pick-up Trucks (Ford 250 XL)	Miscellaneous	311	167.22	30.62	489.43	0.69	18.90	11.14	68,483.80	1.67	2.37
Worker Commuting	From the North	311	5,186.04	458.22	536.82	5.70	72.33	31.44	465,928.30	37.72	22.33
Worker Commuting	From the South	311	249.44	22.04	25.82	0.27	3.48	1.51	22,410.66	1.81	1.07
Total			9,549.37	1,781.67	1,548.80	28.03	168.16	128.77	4,302,037.13	7,010.50	636.86

^a Annual emissions [lb/year] = Daily emissions [lb/day] x Operating days/year

Off-Site Motor Vehicle Fugitive PM Emissions

Emission Factors for Vehicles on Off-Site Paved Roads

Parameter	Value	Comments
Road silt loading (g/m ²)	0.1	CalEEMod default
Onroad vehicles average weight (tons)	2.4	CalEEMod Default for Santa Barbara County
PM10 emission factor (lb/mile)	6.61E-04	0.0022 x (silt loading [g/m ²]) ^{0.91} x (average vehicle weight) ^{1.62} from AP-42 Section 13.2.1, Paved Roads(01/11)
PM2.5 emission factor (lb/mile)	1.62E-04	0.00054 x (silt loading [g/m ²]) ^{0.91} x (average vehicle weight) ^{1.62} from AP-42 Section 13.2.1, Paved Roads(01/11)

Vehicle	Use	Miles/Day	Op. Days/yr	Daily Emissions (lb/day) ^a		Annual Emissions (lb/year) ^b	
				PM10	PM2.5	PM10	PM2.5
Freightliner Tractors	Compost to North County	456	311	0.30	0.07	93.75	23.01
Freightliner Tractors	Recycleables to POLA	4,716	311	3.12	0.77	969.55	237.88
Tractor/Trailer	CSSR from SCRTS to Tajiguas instead of Gold Coast	-238	311	-0.16	-0.04	-48.93	-12.01
Pick-up Trucks (Ford 250 XL)	Miscellaneous	200	311	0.13	0.03	41.12	10.09
Worker Commuting	From the North	2,183	311	1.44	0.35	448.80	110.16
Worker Commuting	From the South	105	311	0.07	0.02	21.59	5.30
Total				4.91	1.20	1,525.88	374.53

^a Daily emissions [lb/day] = Miles/day x Emission factor [lb/mi]

^b Annual emissions [lb/year] = Daily emissions [lb/day] x Operating days/year

Table 17 On-Site Fugitive PM Emissions without CSSR

On-Site Motor Vehicle Fugitive PM Emissions without CSSR

Vehicle	Use	Route	Weight (tons) ^a	Miles/Day	Annual Op. (Days/year)	Emission Factors (lb/mi) ^b		Control Efficiency (%) ^c	Emissions (lb/day) ^d		Emissions (lb/year) ^e	
						PM10	PM2.5		PM10	PM2.5	PM10	PM2.5
Freightliner Tractor	Compost Export	MRF-Compost	13.75	3.61	311	0.19	0.05	86	0.10	0.02	30.10	7.60
Freightliner Tractor	Compost Export	MRF-Entrance	13.75	8.92	311	0.19	0.05	86	0.24	0.06	74.42	18.78
Freightliner Tractor	Recycleables to POLA	MRF-Entrance	13.75	28.99	311	0.19	0.05	86	0.78	0.20	241.86	61.04
Ford F350 XL	Utility truck and trailer	MRF-Compost	7	5.41	311	0.10	0.02	86	0.07	0.02	22.68	5.72
Ford F350 XL	Utility truck and trailer	MRF-Entrance	7	13.38	311	0.10	0.02	86	0.18	0.05	56.07	14.15

^a Freightliner tractor + trailer = average of 40,000 lbs loaded and 15,000 lbs empty.

Ford F350 XL based on specification of 14,000 lbs gross vehicle weight rating

^b Emission factor [lb/mi] = [k x (silt loading [g/m²])^{0.91} (weight [tons])^{1.03} (1 - P/4N)]

from AP-42, Section 13.2.1 (Paved Roads), Equation 2 (1/11)

k = 0.0022 for PM10 P= 40 days
0.00054 for PM2.5

silt loading = 7.4 g/m² from AP-42, Section 13.2.1 (Paved Roads), Table 13.2.1-3 (1/11)

^c Based on hourly watering at 0.18 gal/sq. yd. and 15 mph speed limit, from Appendix E.7, page 3, of the Draft EIR for the Tajiguas Landfill Expansion Project, Santa Barbara County No. 01-EIR-5.

^d Emissions [lb/day] = Emission factor [lb/mi] x Miles/day x (1 - control efficiency [%] / 100)

^e Emissions [lb/year] = Emissions [lb/day] x Days/year

Material Transfers without CSSR

Material	Transfer	Moisture (%) ^a	Daily Amount (tons) ^b	Annual Op. (Days/year)	Emission Factors (lb/ton) ^c		Emissions (lb/day) ^{d,1}		Emissions (lb/year) ^e	
					PM10	PM2.5	PM10	PM2.5	PM10	PM2.5
Digestate	Into Truck	4.8	288	208	3.70E-04	5.60E-05	1.07E-04	1.61E-05	0.02	0.00
Digestate	Onto Windrow	4.8	288	208	3.70E-04	5.60E-05	1.07E-01	1.61E-02	22.17	3.36
Windrow	Windrow turning	4.8	15,363	52	3.70E-04	5.60E-05	5.68E+00	8.60E-01	295.21	44.70
Compost	Into Screen	4.8	83	311	3.70E-04	5.60E-05	3.06E-02	4.63E-03	9.52	1.44
Compost	Out of Screen	4.8	83	311	3.70E-04	5.60E-05	3.06E-02	4.63E-03	9.52	1.44
Compost	Onto Storage Pile	4.8	83	311	3.70E-04	5.60E-05	3.06E-02	4.63E-03	9.52	1.44
Compost	Into Export Truck	4.8	83	311	3.70E-04	5.60E-05	3.06E-02	4.63E-03	9.52	1.44
MSW	Into MRF Facility	4.8	800	311	3.70E-04	5.60E-05	2.96E-04	4.48E-05	0.09	0.01
MSW	Into AD Facility	4.8	240	311	3.70E-04	5.60E-05	8.87E-05	1.34E-05	0.03	0.00

^a Maximum moisture content of materials used to develop emission factor equation.

^b For digestate, 60,000 tpy / 208 op. days/yr; for windrow turning, 15,363 tons / op. day; for compost, 25,760 tpy / 311 op. days/yr

^c Emission factor [lb/ton] = k x 0.0032 x (wind speed [mph] / 5)^{1.3} / (material moisture [%] / 2)^{1.4}

from AP-42, Section 13.2.4, Aggregate Handling and Storage Piles (11/06)

k = 0.35 for PM10
0.053 for PM2.5

Wind speed = 5.47 mph, from Table 9, Appendix E.8 of the Draft EIR for the Tajiguas Landfill Expansion Project, Santa Barbara County No. 01-EIR-5

^d Emissions [lb/day] = Emission factor [lb/ton] x Daily amount [tons]

^e Emissions [lb/year] = Emissions [lb/day] x Days/year

¹ PM10 and PM2.5 emissions from buildings controlled by dust collectors with 99.9 percent control efficiency

Table 17 On-Site Fugitive PM Emissions without CSSR

Screening

Material	Daily Amount (tons) ^a	Annual Op. (Days/year)	Emission Factors (lb/ton) ^b		Emissions (lb/day) ^c		Emissions (lb/year) ^d	
			PM10	PM2.5	PM10	PM2.5	PM10	PM2.5
Compost	83	311	0.00074	0.00005	6.13E-02	4.14E-03	1.91E+01	1.29E+00

^a For digestate, 60,000 tpy / 208 op. days/yr; for compost, 25,760 tpy / 311 op. days/yr

^b From AP-42, Section 11.19, Crushed Stone Processing and Pulverized Mineral Processing (08/04),

Table 11.19.2-2 for controlled screening

^c Emissions [lb/day] = Emission factor [lb/ton] x Daily amount [tons]

^d Emissions [lb/year] = Emissions [lb/day] x Days/year

Chipper/Grinder

Material	Hourly Amount (tph)	Operating Time (hr/day)	Annual Op. (Days/year)	Emission Factors (lb/ton) ^a		Emissions (lb/hr) ^b		Emissions (lb/day) ^c		Emissions (lb/year) ^d	
				PM10	PM2.5	PM10	PM2.5	PM10	PM2.5	PM10	PM2.5
Wood	45.5	1.5	311	0.0144	0.0144	0.66	0.66	0.98	0.98	305.65	305.65

^a From Bay Area Air Quality Management District Permit Handbook, Section 11.3,

http://hank.baaqmd.gov/pmt/handbook/rev02/PH_00_05_11_13.pdf. PM2.5 assumed to be equal to PM10.

^b Emissions [lb/hr] = Emission factor [lb/ton] x Hourly amount [tph]

^c Emissions [lb/day] = Hourly emissions [lb/hr] x Daily operating time [hr/day]

^d Emissions [lb/year] = Emissions [lb/day] x Days/year

**Table 18 On-Site Fugitive PM Emissions with CSSR
On-Site Motor Vehicle Fugitive PM Emissions with CSSR**

Vehicle	Use	Route	Weight (tons) ^a	Miles/Day	Annual Op. (Days/year)	Emission Factors (lb/mi) ^b		Control Efficiency (%) ^c	Emissions (lb/day) ^d		Emissions (lb/year) ^e	
						PM10	PM2.5		PM10	PM2.5	PM10	PM2.5
Freightliner Tractor	Compost Export	MRF-Compost	13.75	3.61	311	0.19	0.05	86	0.10	0.02	30.10	7.39
Freightliner Tractor	Compost Export	MRF-Entrance	13.75	8.92	311	0.19	0.05	86	0.24	0.06	74.42	18.78
Freightliner Tractor	Recycleables to POLA	MRF-Entrance	13.75	40.14	311	0.19	0.05	86	1.08	0.27	334.88	84.51
Tractor/Trailer	CSSR Import	MRF-Entrance	13.75	15.61	311	0.19	0.05	86	0.42	0.11	130.23	32.87
Ford F350 XL	Utility truck and trailer	MRF-Compost	7	5.41	311	0.10	0.02	86	0.07	0.02	22.68	5.72
Ford F350 XL	Utility truck and trailer	MRF-Entrance	7	13.38	311	0.10	0.02	86	0.18	0.05	56.07	14.15

^a Freightliner tractor + trailer and tractor/trailer = average of 40,000 lbs loaded and 15,000 lbs empty.
 Ford F350 XL based on specification of 14,000 lbs gross vehicle weight rating
^b Emission factor [lb/mi] = [k x (silt loading [g/m²])^{0.51} (weight [tons])^{1.02}](1 - P/4N)
 from AP-42, Section 13.2.1 (Paved Roads), Equation 2 (1/11)
 k = 0.0022 for PM10 P= 40 days
 0.00054 for PM2.5
 silt loading = 7.4 g/m² from AP-42, Section 13.2.1 (Paved Roads), Table 13.2.1-3 (1/11)
^c Based on hourly watering at 0.18 gal/sq. yd. and 15 mph speed limit, from Appendix E.7, page 3, of the Draft EIR for the Tajiguas Landfill Expansion Project, Santa Barbara County No. 01-EIR-5.
^d Emissions [lb/day] = Emission factor [lb/mi] x Miles/day x (1 - control efficiency [%] / 100)
^e Emissions [lb/year] = Emissions [lb/day] x Days/year

Material Transfers with CSSR

Material	Transfer	Moisture (%) ^a	Daily Amount (tons) ^b	Annual Op. (Days/year)	Emission Factors (lb/ton) ^c		Emissions (lb/day) ^{d,1}		Emissions (lb/year) ^e	
					PM10	PM2.5	PM10	PM2.5	PM10	PM2.5
Digestate	Into Truck	4.8	288	278	3.70E-04	5.60E-05	1.07E-04	1.61E-05	0.03	0.00
Digestate	Onto Windrow	4.8	288	278	3.70E-04	5.60E-05	1.07E-01	1.61E-02	29.63	4.49
Windrow	Windrow turning	4.8	15,363	52	3.70E-04	5.60E-05	5.68E+00	8.60E-01	295.21	44.70
Compost	Into Screen	4.8	83	311	3.70E-04	5.60E-05	3.06E-02	4.63E-03	9.52	1.44
Compost	Out of Screen	4.8	83	311	3.70E-04	5.60E-05	3.06E-02	4.63E-03	9.52	1.44
Compost	Onto Storage Pile	4.8	83	311	3.70E-04	5.60E-05	3.06E-02	4.63E-03	9.52	1.44
Compost	Into Export Truck	4.8	83	311	3.70E-04	5.60E-05	3.06E-02	4.63E-03	9.52	1.44
MSW	Into MRF Facility	4.8	800	311	3.70E-04	5.60E-05	2.96E-04	4.48E-05	0.09	0.01
MSW	Into AD Facility	4.8	240	311	3.70E-04	5.60E-05	8.87E-05	1.34E-05	0.03	0.00

^a Maximum moisture content of materials used to develop emission factor equation.
^b For digestate, 60,000 tpy / 208 op. days/yr; for windrow turning, 15,363 tons / op. day; for compost, 25,760 tpy / 311 op. days/yr
^c Emission factor [lb/ton] = k x 0.0032 x (wind speed [mph] / 5)^{1.3} / (material moisture [%] / 2)^{1.4}
 from AP-42, Section 13.2.4, Aggregate Handling and Storage Piles (11/06)
 k = 0.35 for PM10
 0.053 for PM2.5
 Wind speed = 5.47 mph, from Table 9, Appendix E.8 of the Draft EIR for the Tajiguas Landfill Expansion Project, Santa Barbara County No. 01-EIR-5
^d Emissions [lb/day] = Emission factor [lb/ton] x Daily amount [tons]
^e Emissions [lb/year] = Emissions [lb/day] x Days/year
¹ PM10 and PM2.5 emissions from buildings controlled by dust collectors with 99.9 percent control efficiency

Table 18 On-Site Fugitive PM Emissions with CSSR

Screening

Material	Daily Amount (tons) ^a	Annual Op. (Days/year)	Emission Factors (lb/ton) ^b		Emissions (lb/day) ^c		Emissions (lb/year) ^d	
			PM10	PM2.5	PM10	PM2.5	PM10	PM2.5
Compost	83	311	0.00074	0.00005	6.13E-02	4.14E-03	1.91E+01	1.29E+00

^a For digestate, 60,000 tpy / 208 op. days/yr; for compost, 25,760 tpy / 311 op. days/yr

^b From AP-42, Section 11.19, Crushed Stone Processing and Pulverized Mineral Processing (08/04), Table 11.19.2-2 for controlled screening

^c Emissions [lb/day] = Emission factor [lb/ton] x Daily amount [tons]

^d Emissions [lb/year] = Emissions [lb/day] x Days/year

Chipper/Grinder

Material	Hourly Amount (tph)	Operating Time (hr/day)	Annual Op. (Days/year)	Emission Factors (lb/ton) ^a		Emissions (lb/hr) ^b		Emissions (lb/day) ^c		Emissions (lb/year) ^d	
				PM10	PM2.5	PM10	PM2.5	PM10	PM2.5	PM10	PM2.5
Wood	45.5	1.5	311	0.0144	0.0144	0.66	0.66	0.98	0.98	305.65	305.65

^a From Bay Area Air Quality Management District Permit Handbook, Section 11.3, http://hank.baaqmd.gov/pmt/handbook/rev02/PH_00_05_11_13.pdf. PM2.5 assumed to be equal to PM10.

^b Emissions [lb/hr] = Emission factor [lb/ton] x Hourly amount [tph]

^c Emissions [lb/day] = Hourly emissions [lb/hr] x Daily operating time [hr/day]

^d Emissions [lb/year] = Emissions [lb/day] x Days/year

Table 19 Windrow ROC Emissions

Item	Value	Comment
Digestate production (ton/yr)	73,590	AD design capacity
Digestate production (ton/day)	201.62	Annual / 365 days/year
Fraction food waste	0.481	Mustang estimate
Fraction green waste	0.519	Mustang estimate
Digestate from food waste (ton/day)	96.98	
Digestate from green waste (ton/day)	104.64	
Food waste EF (lb VOC/ton)	37.1	From SJVAPCD Compost VOC Emission Factors, Sept. 2010 ^a
Green waste EF (lb VOC/ton)	5.71	From SJVAPCD Compost VOC Emission Factors, Sept. 2010 ^a
VOC from food waste (lb/day)	3,597.87	
VOC from green waste (lb/day)	597.49	
Total VOC (lb/day)	4,195	
Reduction from digestion process	0.97	See note b
VOC after reduction from digestion (lb/day)	125.86	
Reduction from Best Available Control Technologies	0.90	See note c
VOC after BMP reductions (lb/day)	12.59	
VOC after BMP reductions (lb/hour)	0.52	Daily / 24 hours/day
VOC after BMP reductions (lb/yr)	4,594	

^a From Compost VOC Emission Factors, San Joaquin Valley Air Pollution Control District, September 2010. Available at: <http://valleyair.org/Workshops/postings/2010/9-22-10-rule4566/SJVAPCD%20Compost%20VOC%20EF%20Report%209-15-10.pdf>
 Food waste emission factor from Appendix A, Table 6.1 for AgBag windrow
 Green waste emission factor from Table 1

^b From Bay Area Air Quality Management District engineering evaluation for Zero Waste Energy proposed anaerobic digestion facility

^c Best Available Control Technologies:
 1. 20% inert, dry wood chip blending
 2. Interactive pile management (i.e., turning)
 3. 20 minutes irrigation after turning
 4. Large pile size
 5. Finished compost blanket pseudo biofilter

References for emission reductions include:

Advice from Bekon based on 20 facilities operating in Europe

Comparison of Mitigation Measures for Reduction of Emissions from Greenwaste Composting prepared from SJVAPCD 2009: http://valleyair.org/busind/pto/emission_factors/Criteria/Criteria/Composting/FINAL-COMPOST-STUDY-REPORT.pdf

Greenwaste Compost Air Emissions Review (Modesto Compost Facility) prepared from CIWMB June 2008:

<http://www.calrecycle.ca.gov/publications/Documents/Organics%5C44207009.pdf>

Greenwaste Compost Site Emissions Reductions Prepared for San Joaquin Valley Technology Advancement Program May 2013:

http://www.valleyair.org/grant_programs/TAP/documents/C-15636-ACP/C-15636_ACP_FinalReport.pdf

Table 20

Biofilter ROC Emissions

Item	Value	Comment
Digestate production (ton/yr)	73,590	AD design capacity
Digestate production (ton/day)	201.62	Annual / 365 days/year
Fraction food waste	0.481	Mustang estimate
Fraction green waste	0.519	Mustang estimate
Digestate from food waste (ton/day)	96.98	
Digestate from green waste (ton/day)	104.64	
Food waste EF (lb VOC/ton-composting cycle)	37.1	From SJVAPCD Compost VOC Emission Factors, Sept. 2010 ^a
Green waste EF (lb VOC/ton-composting cycle)	5.71	From SJVAPCD Compost VOC Emission Factors, Sept. 2010 ^a
Food waste EF (lb VOC/ton-day)	0.618	For one day of 60-day composting cycle
Green waste EF (lb VOC/ton-day)	0.095	For one day of 60-day composting cycle
VOC from food waste (lb/day)	59.96	
VOC from green waste (lb/day)	9.96	
Total VOC (lb/day)	70	
Reduction from biofilter	0.95	
VOC after biofilter (lb/day)	3.50	
VOC after biofilter (lb/hour)	0.15	Daily / 24 hours/day
VOC after biofilter (lb/yr)	1,276	

^a From Compost VOC Emission Factors, San Joaquin Valley Air Pollution Control District, September 2010. Available at: <http://valleyair.org/Workshops/postings/2010/9-22-10-rule4566/SJVAPCD%20Compost%20VOC%20EF%20Report%209-15-10.pdf>
 Food waste emission factor from Appendix A, Table 6.1 for AgBag windrow
 Green waste emission factor from Table 1

Biofilter	m ³ / min	Fract.	Emiss. (lb/day)	Emiss. (g/s)
Tipping Area	1,461	0.329128	0.04794	0.0060409
ADF	1,428	0.321694	0.04686	0.00590445
Recycling Area	1,550	0.349178	0.05087	0.00640889
Total	4,439	1	0.14567	

Table 21a

AD Flare Toxic Air Contaminant Emissions from Biogas Combustion

Compound	CAS Number	Emission Factor (lb/MMscf)	Emission Factor Source ^a	Hourly Emission Rate (lb/hr) ^b	Annual Emission Rate (lb/yr) ^c	ADFLARE
Indeno(1,2,3-cd)pyrene	193-39-5	5.60E-02	CATEF	9.52E-04	2.50E-01	
Manganese	7439-96-5	2.92E-03	Source Test	4.96E-05	1.30E-02	
Naphthalene	91-20-3	1.75E-04	Source Test	2.97E-06	7.80E-04	
Nickel	7440-02-0	1.43E-03	Source Test	2.43E-05	6.37E-03	
Perylene	198-55-0	7.48E-05	CATEF	1.27E-06	3.34E-04	
Phenanthrene	85-01-8	9.85E-04	Source Test	1.67E-05	4.39E-03	
Pyrene	129-00-0	3.04E-05	Source Test	5.18E-07	1.36E-04	
Toluene	108-88-3	1.09E+02	CATEF	1.85E+00	4.86E+02	
Trichloroethene	79-01-6	1.13E+00	CATEF	1.92E-02	5.04E+00	
Vinyl Chloride	75-01-4	7.64E-02	CATEF	1.30E-03	3.41E-01	
Xylene (m,p)	1330-20-7	4.61E-01	CATEF	7.84E-03	2.06E+00	
Xylene (o)	95-47-6	3.35E-01	CATEF	5.70E-03	1.49E+00	
Zinc	7440-66-6	4.28E+00	CATEF	7.28E-02	1.91E+01	
1,1,1-Trichloroethane	71-55-6	3.37E-01	CATEF	5.73E-03	1.50E+00	
1,1-Dichloroethane	75-34-3	4.37E-01	CATEF	7.43E-03	1.95E+00	
1,2-Dichloroethane	107-06-2	1.35E+00	CATEF	2.30E-02	6.02E+00	
1,4-Dioxane	123-91-1	4.55E-03	Source Test	7.74E-05	2.03E-02	
2-Methylnaphthalene	91-57-6	9.56E-05	Source Test	1.62E-06	4.26E-04	
Acenaphthene	83-32-9	7.04E-06	Source Test	1.20E-07	3.14E-05	
Acenaphthylene	208-96-8	1.09E-04	Source Test	1.85E-06	4.86E-04	
Acetaldehyde	75-07-0	6.53E-01	CATEF	1.11E-02	2.91E+00	
Acetonitrile	75-05-8	7.96E+00	CATEF	1.35E-01	3.55E+01	
Acrolein	107-02-8	9.33E-02	CATEF	1.59E-03	4.16E-01	
Acrylonitrile	107-13-1	4.50E-03	Source Test	7.65E-05	2.01E-02	
Anthracene	120-12-7	1.10E-05	Source Test	1.88E-07	4.92E-05	
Arsenic	7440-38-2	5.91E-02	Source Test	1.00E-03	2.63E-01	
Benzene	71-43-2	8.59E-01	CATEF	1.46E-02	3.83E+00	
Benzo(a)anthracene	56-55-6	5.60E-02	CATEF	9.52E-04	2.50E-01	
Benzo(a)pyrene	50-32-8	5.60E-02	CATEF	9.52E-04	2.50E-01	
Benzo(b)fluoranthene	205-99-2	5.60E-02	CATEF	9.52E-04	2.50E-01	
Benzo(e)pyrene	192-97-2	7.48E-05	CATEF	1.27E-06	3.34E-04	
Benzo(g,h,i)perylene	191-24-2	5.60E-02	CATEF	9.52E-04	2.50E-01	
Benzo(k)fluoranthene	207-08-9	5.60E-02	CATEF	9.52E-04	2.50E-01	
Cadmium	7440-43-9	1.43E-03	Source Test	2.43E-05	6.37E-03	
Carbon Tetrachloride	56-23-5	3.76E-02	CATEF	6.39E-04	1.68E-01	
Chlorobenzene	108-90-7	8.69E-01	CATEF	1.48E-02	3.88E+00	
Chloroform	67-66-3	5.60E-02	CATEF	9.52E-04	2.50E-01	
Chromium (Hex)	18540-29-9	1.21E-05	Source Test	2.07E-07	5.42E-05	
Chromium (Total)	7440-47-3	4.64E-03	Source Test	7.90E-05	2.07E-02	
Chrysene	218-01-9	6.51E-06	Source Test	1.11E-07	2.90E-05	
Copper	7440-50-8	4.86E+00	CATEF	8.26E-02	2.17E+01	
Dibenz(a,h)anthracene	53-70-3	5.60E-02	CATEF	9.52E-04	2.50E-01	
Dichloromethane	75-09-2	4.29E-01	CATEF	7.29E-03	1.91E+00	
Fluoranthene	206-44-0	1.40E-05	Source Test	2.38E-07	6.24E-05	
Fluorene	86-73-7	2.84E-04	Source Test	4.82E-06	1.27E-03	
Formaldehyde	50-00-0	1.77E-01	Source Test	3.01E-03	7.89E-01	
HCl	7647-01-0	1.61E-03	Source Test	2.75E-05	7.20E-03	
HF	7664-39-3	2.15E-01	Source Test	3.65E-03	9.58E-01	

Hourly Biogas flow rate = 17,002 scfh

Annual biogas flow rate ^A 36,926

Annual biogas flow rate ^v 4,422,382

Total Annual biogas flow 4,459,308

Assumed to be biogas flow to one AD CHP engine

Assumed to be 1/16 of biogas flow to two engines x annual

Assumed to be biogas flow to one engine x hours/year engi

^a CATEF = Maximum emission factors from California Air Toxics Emission Factors <http://www.arb.ca.gov/app/emsm> for flare fired on landfill gas based on assumption that biogas composition is similar to landfill gas

Source Test = September 9-11 2010 source tests on Santa Maria Landfill flare combusting LFG. Non-detects set t

^b Hourly emission rate [lb/hr] = Emission factor [lb/MMscf] x Biogas flow rate [scfh] / 10⁶ [scf/MMscf]

^b Annual emission rate [lb/yr] = Emission factor [lb/MMscf] x Annual biogas flow rate [scf/yr] / 10⁶ [scf/MMscf]

Table 21b

Flare Toxic Air Contaminant Emissions from Biogas Combustion

Compound	CAS Number	Emission Factor (lb/MMscf)	Emission Factor Source ^a	Hourly Emission Rate (lb/hr) ^b	Annual Emission Rate (lb/yr) ^c
Indeno(1,2,3-cd)pyrene	193-39-5	5.60E-02	CATEF	1.27E-03	1.11E+00
Manganese	7439-96-5	2.92E-03	Source Test	6.60E-05	5.78E-02
Naphthalene	91-20-3	1.75E-04	Source Test	3.95E-06	3.46E-03
Nickel	7440-02-0	1.43E-03	Source Test	3.23E-05	2.83E-02
Perylene	198-55-0	7.48E-05	CATEF	1.69E-06	1.48E-03
Phenanthrene	85-01-8	9.85E-04	Source Test	2.23E-05	1.95E-02
Pyrene	129-00-0	3.04E-05	Source Test	6.88E-07	6.03E-04
Toluene	108-88-3	1.09E+02	CATEF	2.46E+00	2.16E+03
Trichloroethene	79-01-6	1.13E+00	CATEF	2.55E-02	2.24E+01
Vinyl Chloride	75-01-4	7.64E-02	CATEF	1.73E-03	1.51E+00
Xylene (m,p)	1330-20-7	4.61E-01	CATEF	1.04E-02	9.13E+00
Xylene (o)	95-47-6	3.35E-01	CATEF	7.57E-03	6.63E+00
Zinc	7440-66-6	4.28E+00	CATEF	9.67E-02	8.47E+01
1,1,1-Trichloroethane	71-55-6	3.37E-01	CATEF	7.62E-03	6.67E+00
1,1-Dichloroethane	75-34-3	4.37E-01	CATEF	9.88E-03	8.65E+00
1,2-Dichloroethane	107-06-2	1.35E+00	CATEF	3.05E-02	2.67E+01
1,4-Dioxane	123-91-1	4.55E-03	Source Test	1.03E-04	9.01E-02
2-Methylnaphthalene	91-57-6	9.56E-05	Source Test	2.16E-06	1.89E-03
Acenaphthene	83-32-9	7.04E-06	Source Test	1.59E-07	1.39E-04
Acenaphthylene	208-96-8	1.09E-04	Source Test	2.46E-06	2.16E-03
Acetaldehyde	75-07-0	6.53E-01	CATEF	1.48E-02	1.29E+01
Acetonitrile	75-05-8	7.96E+00	CATEF	1.80E-01	1.58E+02
Acrolein	107-02-8	9.33E-02	CATEF	2.11E-03	1.85E+00
Acrylonitrile	107-13-1	4.50E-03	Source Test	1.02E-04	8.91E-02
Anthracene	120-12-7	1.10E-05	Source Test	2.49E-07	2.19E-04
Arsenic	7440-38-2	5.91E-02	Source Test	1.34E-03	1.17E+00
Benzene	71-43-2	8.59E-01	CATEF	1.94E-02	1.70E+01
Benzo(a)anthracene	56-55-6	5.60E-02	CATEF	1.27E-03	1.11E+00
Benzo(a)pyrene	50-32-8	5.60E-02	CATEF	1.27E-03	1.11E+00
Benzo(b)fluoranthene	205-99-2	5.60E-02	CATEF	1.27E-03	1.11E+00
Benzo(e)pyrene	192-97-2	7.48E-05	CATEF	1.69E-06	1.48E-03
Benzo(g,h,i)perylene	191-24-2	5.60E-02	CATEF	1.27E-03	1.11E+00
Benzo(k)fluoranthene	207-08-9	5.60E-02	CATEF	1.27E-03	1.11E+00
Cadmium	7440-43-9	1.43E-03	Source Test	3.23E-05	2.83E-02
Carbon Tetrachloride	56-23-5	3.76E-02	CATEF	8.50E-04	7.44E-01
Chlorobenzene	108-90-7	8.69E-01	CATEF	1.96E-02	1.72E+01
Chloroform	67-66-3	5.60E-02	CATEF	1.27E-03	1.11E+00
Chromium (Hex)	18540-29-9	1.21E-05	Source Test	2.75E-07	2.41E-04
Chromium (Total)	7440-47-3	4.64E-03	Source Test	1.05E-04	9.20E-02
Chrysene	218-01-9	6.51E-06	Source Test	1.47E-07	1.29E-04
Copper	7440-50-8	4.86E+00	CATEF	1.10E-01	9.62E+01
Dibenz(a,h)anthracene	53-70-3	5.60E-02	CATEF	1.27E-03	1.11E+00
Dichloromethane	75-09-2	4.29E-01	CATEF	9.70E-03	8.49E+00
Fluoranthene	206-44-0	1.40E-05	Source Test	3.16E-07	2.77E-04
Fluorene	86-73-7	2.84E-04	Source Test	6.41E-06	5.62E-03
Formaldehyde	50-00-0	1.77E-01	Source Test	4.00E-03	3.51E+00
HCl	7647-01-0	1.61E-03	Source Test	3.65E-05	3.20E-02
HF	7664-39-3	2.15E-01	Source Test	4.86E-03	4.25E+00

Hourly LFG flow rate = 22,602 scfh

Assumed to be LFG flow to one CHP engine

Annual biogas flow rate = 19,799,207

Assumed to be LFG flow to one engine x hours/year engines

Total Annual biogas flow = 19,799,207

^a CATEF = Maximum emission factors from California Air Toxics Emission Factors <http://www.arb.ca.gov/app/emsinv> for flare fired on landfill gas
Source Test = September 9-11 2010 source tests on Santa Maria Landfill flare combusting LFG. Non-detects set to

^b Hourly emission rate [lb/hr] = Emission factor [lb/MMscf] x LFG flow rate [scfh] / 10⁶ [scf/MMscf]

^c Annual emission rate [lb/yr] = Emission factor [lb/MMscf] x Annual LFG flow rate [scf/yr] / 10⁶ [scf/MMscf]

Table 22

CHP Engine Toxic Air Contaminant Emissions from Biogas/LFG Combustion
ADCHP1, ADCHP2 MRFCHP1-2 PAPERDRY

Compound	CAS Number	Emission Factor (lb/MMscf) ^a	Hourly Emission Rate per Engine (lb/hr) ^b	Annual Emission Rate per Engine (lb/yr) ^c	Hourly Emission Rate (lb/hr) ^b	Annual Emission Rate (lb/yr) ^c	Hourly Emission Rate (lb/hr) ^b	Annual Emission Rate (lb/yr) ^c
Benzene	71-43-2	9.48E-03	1.61E-04	1.34E+00	2.14E-04	1.82E+00	4.29E-04	3.65E+00
Benzo(a)anthracene	56-55-6	1.60E-06	2.72E-08	2.26E-04	3.62E-08	3.08E-04	7.23E-08	6.16E-04
Benzo(a)pyrene	50-32-8	2.70E-07	4.59E-09	3.82E-05	6.10E-09	5.19E-05	1.22E-08	1.04E-04
Benzo(b)fluoranthene	205-99-2	4.88E-07	8.30E-09	6.90E-05	1.10E-08	9.39E-05	2.21E-08	1.88E-04
Benzo(k)fluoranthene	207-08-9	2.70E-07	4.59E-09	3.82E-05	6.10E-09	5.19E-05	1.22E-08	1.04E-04
Carbon Tetrachloride	56-23-5	1.14E-04	1.94E-06	1.61E-02	2.58E-06	2.19E-02	5.15E-06	4.39E-02
Chloroform	67-66-3	1.13E-04	1.92E-06	1.60E-02	2.55E-06	2.17E-02	5.11E-06	4.35E-02
Chrysene	218-01-9	5.87E-06	9.98E-08	8.31E-04	1.33E-07	1.13E-03	2.65E-07	2.26E-03
Dibenz(a,h)anthracene	53-70-3	2.70E-07	4.59E-09	3.82E-05	6.10E-09	5.19E-05	1.22E-08	1.04E-04
Ethylene Dibromide	106-93-4	1.12E-04	1.90E-06	1.58E-02	2.53E-06	2.15E-02	5.06E-06	4.31E-02
Ethylene Dichloride	106-93-4	5.08E-03	8.64E-05	7.19E-01	1.15E-04	9.77E-01	2.30E-04	1.95E+00
Formaldehyde	50-00-0	1.49E+00	2.53E-02	2.11E+02	3.37E-02	2.87E+02	6.74E-02	5.73E+02
Hydrochloric Acid	7647-01-0	2.07E+00	3.52E-02	2.93E+02	4.68E-02	3.98E+02	9.36E-02	7.97E+02
Indeno(1,2,3-cd)pyrene	193-39-5	2.70E-07	4.59E-09	3.82E-05	6.10E-09	5.19E-05	1.22E-08	1.04E-04
Methyl Chloroform	71-55-6	1.11E-04	1.89E-06	1.57E-02	2.51E-06	2.14E-02	5.02E-06	4.27E-02
Methylene Chloride	75-09-2	1.30E-04	2.21E-06	1.84E-02	2.94E-06	2.50E-02	5.88E-06	5.00E-02
Napthalene	91-20-3	7.38E-04	1.25E-05	1.04E-01	1.67E-05	1.42E-01	3.34E-05	2.84E-01
Perchloroethylene	127-18-4	5.84E-04	9.93E-06	8.26E-02	1.32E-05	1.12E-01	2.64E-05	2.25E-01
Trichloroethylene	79-01-6	1.49E-03	2.53E-05	2.11E-01	3.37E-05	2.87E-01	6.74E-05	5.73E-01
Vinyl Chloride	75-01-4	1.63E-04	2.77E-06	2.31E-02	3.68E-06	3.14E-02	7.37E-06	6.27E-02

Fuel flow rate = 17,002 scfh Engine specification at 100% load 22,602 scfh Engine specification at 100% load
 141,488,324 scf/year Hourly biogas [scfh] x Annual op. hours [hr/year] 192,395,044 scf/year Hourly LFG [scfh] x Annual op. hours [hr/year]

^a Santa Barbara County Air Pollution Control District approved emission factors for landfill gas-fired IC engines with oxidation catalyst

^b Hourly emission rate [lb/hr] = Emission factor [lb/MMscf] x biogas/LFG flow rate [scfh] / 10⁶ [scf/MMscf]
 Molar volume [scf/lb-mole] x (1 - Engine destruction efficiency [%] / 100) x (1 - Oxidation catalyst efficiency [%] / 100)

^c Annual emission rate [lb/yr] = Emission factor [lb/MMscf] x annual biogas/LFG flow rate [scf/year] / 10⁶ [scf/MMscf]

CHP Engine Ammonia Emissions from SCR Ammonia Slip, Each Engine

Item	AD Value	Comments	MRF Value
Ammonia concentration	5	ppm @ 15% oxygen	5
Ammonia molecular weight	17	lb/lb-mole	17
Fd	11,370	scf/MMBtu, SCR system vendor estimate	11,370
Molar volume	385.5	scf/lb-mole	385.5
Engine heat input	9.88	MMBtu/hr, manufacturer's specification	12.32
Ammonia hourly emissions	8.77E-02	lb/hr = Ammonia concentration [ppm] x Molecular weight [lb/lb-mole] x 10 ⁻⁶ / Molar volume [scf/lb-mole] x [20.9 / (20.9 - percent oxygen)] x Fd [scf/MMBtu] x Heat input [MMBtu/hr]	1.09E-01
Ammonia annual emissions	7.30E+02	lb/yr = Hourly emissions [lb/hr] x Annual biogas production [scf/year] / Hourly biogas flow rate [scfh]	9.31E+02

hr/year]

Table 23 Diesel Exhaust Particulate Matter Emissions

Table 23-A

MRF Facility Biofilter for Tipping Area (7:00 a.m. - 11:00 p.m.)

Equipment	Operating Days per Year	Operating Hours per Day	Hourly Emissions (lb/hr)	Annual Emissions (lb/yr)	
Caterpillar M322D Material Handler	311	16	2.07E-06	1.03E-02	
CAT 966 M Loader	311	16	7.44E-06	3.70E-02	
CAT 938 K Loader	311	16	2.02E-06	1.01E-02	
Tennant 800 Sweeper	311	16	6.53E-07	3.25E-03	
Total			1.22E-05	6.06E-02	BF_TIP

Table 23-B

MRF Facility Biofilter for Tipping Area (11:00 p.m. - 7:00 a.m.)

Equipment	Operating Days per Year	Operating Hours per Day	Hourly Emissions (lb/hr)	Annual Emissions (lb/yr)	
Tennant 800 Sweeper	311	8	6.53E-07	1.62E-03	
Total			6.53E-07	1.62E-03	BF_TIP

Hourly Night Factor
Annual Night Factor
0.05 0.03

Table 23-C

MRF Facility Biofilter for Recycling Area (7:00 a.m. - 11:00 p.m.)

Equipment	Operating Days per Year	Operating Hours per Day	Hourly Emissions (lb/hr)	Annual Emissions (lb/yr)	
CAT 2P-6000 Forklift	311	16	1.62E-06	8.07E-03	
Tennant 800 Sweeper	311	16	6.53E-07	3.25E-03	
Total			2.27E-06	1.13E-02	BFRECYC

Table 23-D

MRF Facility Biofilter for Recycling Area (11:00 p.m. - 7:00 a.m.)

Equipment	Operating Days per Year	Operating Hours per Day	Hourly Emissions (lb/hr)	Annual Emissions (lb/yr)	
Tennant 800 Sweeper	311	8	6.53E-07	1.62E-03	
Total			6.53E-07	1.62E-03	BFRECYC

Table 23-E

AD Facility Biofilter (8:00 a.m. - 4:00 p.m.)

Equipment	Operating Days per Year	Operating Hours per Day	Hourly Emissions (lb/hr)	Annual Emissions (lb/yr)	
CAT 938 M Loader	208	8	4.04E-06	6.73E-03	
Total			4.04E-06	6.73E-03	BF_ADF

Table 23-F

Outside MRF Facility Building (11:00 a.m. - 5:00 p.m.)

Equipment	Operating Days per Year	Operating Hours per Day	Hourly Emissions (lb/hr)	Annual Emissions (lb/yr)	
Tennant M30 Scrubber-Sweeper	311	6	8.24E-04	1.54E+00	
Total			8.24E-04	1.54E+00	MRFSWP1 & 2 7.684E-01

Table 23-G

Outside AD Facility Building (11:00 a.m. - 5:00 p.m.)

Equipment	Operating Days per Year	Operating Hours per Day	Hourly Emissions (lb/hr)	Annual Emissions (lb/yr)	
Tennant M30 Scrubber-Sweeper	311	6	8.24E-04	1.54E+00	
Total	0	0	8.24E-04	1.54E+00	ADSWEEP

Table 23-H

Composting Area (8:00 a.m. - 4:00 p.m.)

Equipment	Operating Days per Year	Operating Hours per Day	Hourly Emissions (lb/hr)	Annual Emissions (lb/yr)	
CAT 938 K Loader	311	8	2.02E-06	5.03E-03	
Backhus A55 Windrow Turner	52	8	3.07E-03	1.28E+00	
Total					COMP MAT WINDROW

Table 23-I

Motor Vehicles (8:00 a.m. - 2:00 p.m.)

Segment	Operating Hours per Day	Hourly Emissions (lb/hr)	Annual Emissions (lb/yr)	
MRF-Compost	6	4.82E-05	8.99E-02	
MRF-Entrance	6	7.58E-04	1.41E+00	
Total				MRFCOMP MRFENTRY

Table 23-J

Emergency Generator

Segment	Operating Hours per Day	Hourly Emissions (lb/hr)	Annual Emissions (lb/yr)	
150 kW Generator	6	1.1E-02	5.3E-01	
Total				EMGEN

Table 24 Diesel Exhaust Emissions of TACs with Acute Effects

**Table 24-A
MRF Facility Biofilter (7:00 a.m. - 11:00 p.m.)**

Compound	CAS Number	Emission Factor (lb/1,000 gal) ^a	Emissions (lb/hour)
Benzene	71-43-2	0.1863	2.53E-03
Formaldehyde	50-00-0	1.7261	2.35E-02
Acetaldehyde	75-07-0	0.7833	1.07E-02
Acrolein	107-02-8	0.0339	4.61E-04
1,3-Butadiene	106-99-0	0.2174	2.96E-03
Toluene	108-88-3	0.1054	1.43E-03
Xylenes	1330-20-7	0.0424	5.77E-04
Hydrogen chloride	7647-01-0	0.1863	2.53E-03
Arsenic	7440-38-2	0.0016	2.18E-05
Copper	7440-50-8	0.0041	5.58E-05
Mercury	7439-97-6	0.0020	2.72E-05
Nickel	7440-02-0	0.0039	5.30E-05

BF_TIP

Hourly fuel use = 13.6 gal/hr

^a From Ventura County Air Pollution Control District AB 2588 Emission Factors for Diesel Fuel Internal Combustion.
<http://www.vcapcd.org/pubs/Engineering/AirToxics/combem.pdf>
 Only includes TACs with acute reference exposure levels.

**Table 24-B
MRF Recycling Area Biofilter (7:00 a.m. - 11:00 p.m.) - BFRECYC**

Compound	CAS Number	Emission Factor (lb/1,000 gal) ^a	Emissions (lb/hour)
Benzene	71-43-2	0.1863	1.21E-03
Formaldehyde	50-00-0	1.7261	1.12E-02
Acetaldehyde	75-07-0	0.7833	5.09E-03
Acrolein	107-02-8	0.0339	2.20E-04
1,3-Butadiene	106-99-0	0.2174	1.41E-03
Toluene	108-88-3	0.1054	6.85E-04
Xylenes	1330-20-7	0.0424	2.76E-04
Hydrogen chloride	7647-01-0	0.1863	1.21E-03
Arsenic	7440-38-2	0.0016	1.04E-05
Copper	7440-50-8	0.0041	2.67E-05
Mercury	7439-97-6	0.0020	1.30E-05
Nickel	7440-02-0	0.0039	2.54E-05

Hourly fuel use = 6.5 gal/hr

^a From Ventura County Air Pollution Control District AB 2588 Emission Factors for Diesel Fuel Internal Combustion.
<http://www.vcapcd.org/pubs/Engineering/AirToxics/combem.pdf>
 Only includes TACs with acute reference exposure levels.

Table 24 Diesel Exhaust Emissions of TACs with Acute Effects

**Table 24-C
AD Facility Biofilter (8:00 a.m. - 4:00 p.m.) -BFADF**

Compound	CAS Number	Emission Factor (lb/1,000 gal) ^a	Emissions (lb/hour)
Benzene	71-43-2	0.1863	1.21E-03
Formaldehyde	50-00-0	1.7261	1.12E-02
Acetaldehyde	75-07-0	0.7833	5.09E-03
Acrolein	107-02-8	0.0339	2.20E-04
1,3-Butadiene	106-99-0	0.2174	1.41E-03
Toluene	108-88-3	0.1054	6.85E-04
Xylenes	1330-20-7	0.0424	2.76E-04
Hydrogen chloride	7647-01-0	0.1863	1.21E-03
Arsenic	7440-38-2	0.0016	1.04E-05
Copper	7440-50-8	0.0041	2.67E-05
Mercury	7439-97-6	0.0020	1.30E-05
Nickel	7440-02-0	0.0039	2.54E-05

BFADF

Hourly fuel use = 7 gal/hr

^a From Ventura County Air Pollution Control District AB 2588 Emission Factors for Diesel Fuel Internal Combustion.
<http://www.vcapcd.org/pubs/Engineering/AirToxics/combem.pdf>
 Only includes TACs with acute reference exposure levels.

**Table 24-D
Outside MRF and AD Facility Building (11:00 a.m. - 5:00 p.m.)**

Compound	CAS Number	Emission Factor (lb/1,000 gal) ^a	ADSWEEP Emissions (lb/hour)	MRFSWP1	MRFSWP2
Benzene	71-43-2	0.1863	1.21E-03	6.055E-04	6.055E-04
Formaldehyde	50-00-0	1.7261	1.12E-02	5.610E-03	5.610E-03
Acetaldehyde	75-07-0	0.7833	5.09E-03	2.546E-03	2.546E-03
Acrolein	107-02-8	0.0339	2.20E-04	1.102E-04	1.102E-04
1,3-Butadiene	106-99-0	0.2174	1.41E-03	7.066E-04	7.066E-04
Toluene	108-88-3	0.1054	6.85E-04	3.426E-04	3.426E-04
Xylenes	1330-20-7	0.0424	2.76E-04	1.378E-04	1.378E-04
Hydrogen chloride	7647-01-0	0.1863	1.21E-03	6.055E-04	6.055E-04
Arsenic	7440-38-2	0.0016	1.04E-05	5.200E-06	5.200E-06
Copper	7440-50-8	0.0041	2.67E-05	1.333E-05	1.333E-05
Mercury	7439-97-6	0.0020	1.30E-05	6.500E-06	6.500E-06
Nickel	7440-02-0	0.0039	2.54E-05	1.268E-05	1.268E-05

Hourly fuel use = 4 gal/hr

^a From Ventura County Air Pollution Control District AB 2588 Emission Factors for Diesel Fuel Internal Combustion.
<http://www.vcapcd.org/pubs/Engineering/AirToxics/combem.pdf>
 Only includes TACs with acute reference exposure levels.

Table 24 Diesel Exhaust Emissions of TACs with Acute Effects

**Table 24-E
Composting Area (8:00 a.m. - 4:00 p.m.)
Cat 938 K Loader**

Compound	CAS Number	Emission Factor (lb/1,000 gal) ^a	Emissions (lb/hour)
Benzene	71-43-2	0.1863	5.03E-04
Formaldehyde	50-00-0	1.7261	4.66E-03
Acetaldehyde	75-07-0	0.7833	2.11E-03
Acrolein	107-02-8	0.0339	9.15E-05
1,3-Butadiene	106-99-0	0.2174	5.87E-04
Toluene	108-88-3	0.1054	2.85E-04
Xylenes	1330-20-7	0.0424	1.14E-04
Hydrogen chloride	7647-01-0	0.1863	5.03E-04
Arsenic	7440-38-2	0.0016	4.32E-06
Copper	7440-50-8	0.0041	1.11E-05
Mercury	7439-97-6	0.0020	5.40E-06
Nickel	7440-02-0	0.0039	1.05E-05

COMPMAT

Hourly fuel use = 2.7 gal/hr

^a From Ventura County Air Pollution Control District
AB 2588 Emission Factors for Diesel Fuel Internal
Combustion.
<http://www.vcapcd.org/pubs/Engineering/AirToxics/combem.pdf>
Only includes TACs with acute reference exposure levels.

**Table 24-F
Composting Area (8:00 a.m. - 4:00 p.m.)
Vermeer CT1010 TX Windrow Turner**

Compound	CAS Number	Emission Factor (lb/1,000 gal) ^a	Emissions (lb/hour)
Benzene	71-43-2	0.1863	2.24E-03
Formaldehyde	50-00-0	1.7261	2.07E-02
Acetaldehyde	75-07-0	0.7833	9.40E-03
Acrolein	107-02-8	0.0339	4.07E-04
1,3-Butadiene	106-99-0	0.2174	2.61E-03
Toluene	108-88-3	0.1054	1.26E-03
Xylenes	1330-20-7	0.0424	5.09E-04
Hydrogen chloride	7647-01-0	0.1863	2.24E-03
Arsenic	7440-38-2	0.0016	1.92E-05
Copper	7440-50-8	0.0041	4.92E-05
Mercury	7439-97-6	0.0020	2.40E-05
Nickel	7440-02-0	0.0039	4.68E-05

WINDROW

Compounds from WINDROW Organic TAC tab	Hourly Emission Rate (lb/hr)
Isopropyl alcohol	2.22E-01
Methyl alcohol	6.71E-02
Naphthalene	2.62E-03
Acetaldehyde	7.34E-04
NH3	1,779.46

Hourly fuel use = 12 gal/hr

^a From Ventura County Air Pollution Control District
AB 2588 Emission Factors for Diesel Fuel Internal
Combustion.
<http://www.vcapcd.org/pubs/Engineering/AirToxics/combem.pdf>
Only includes TACs with acute reference exposure levels.

Table 24 Diesel Exhaust Emissions of TACs with Acute Effects

**Table 24-G
On-Site Motor Vehicles (8:00 a.m. - 2:00 p.m.)
Entrance to/from MRF**

Compound	CAS Number	Emission Factor (lb/1,000 gal) ^a	Emissions (lb/hour)	MRFENTRY
Benzene	71-43-2	0.1863	1.10E-04	
Formaldehyde	50-00-0	1.7261	1.02E-03	
Acetaldehyde	75-07-0	0.7833	4.64E-04	
Acrolein	107-02-8	0.0339	2.01E-05	
1,3-Butadiene	106-99-0	0.2174	1.29E-04	
Toluene	108-88-3	0.1054	6.25E-05	
Xylenes	1330-20-7	0.0424	2.51E-05	
Hydrogen chloride	7647-01-0	0.1863	1.10E-04	
Arsenic	7440-38-2	0.0016	9.49E-07	
Copper	7440-50-8	0.0041	2.43E-06	
Mercury	7439-97-6	0.0020	1.19E-06	
Nickel	7440-02-0	0.0039	2.31E-06	

Hourly fuel use = 0.59 gal/hr

^a From Ventura County Air Pollution Control District
AB 2588 Emission Factors for Diesel Fuel Internal
Combustion.
<http://www.vcapcd.org/pubs/Engineering/AirToxics/combem.pdf>
Only includes TACs with acute reference exposure levels.

**Table 24-H
On-Site Motor Vehicles (8:00 a.m. - 2:00 p.m.)
MRF to/from Compost**

Compound	CAS Number	Emission Factor (lb/1,000 gal) ^a	Emissions (lb/hour)	MRFCOMP
Benzene	71-43-2	0.1863	1.20E-05	
Formaldehyde	50-00-0	1.7261	1.11E-04	
Acetaldehyde	75-07-0	0.7833	5.05E-05	
Acrolein	107-02-8	0.0339	2.18E-06	
1,3-Butadiene	106-99-0	0.2174	1.40E-05	
Toluene	108-88-3	0.1054	6.79E-06	
Xylenes	1330-20-7	0.0424	2.73E-06	
Hydrogen chloride	7647-01-0	0.1863	1.20E-05	
Arsenic	7440-38-2	0.0016	1.03E-07	
Copper	7440-50-8	0.0041	2.64E-07	
Mercury	7439-97-6	0.0020	1.29E-07	
Nickel	7440-02-0	0.0039	2.51E-07	

Hourly fuel use = 0.06 gal/hr

^a From Ventura County Air Pollution Control District
AB 2588 Emission Factors for Diesel Fuel Internal Combustion.
<http://www.vcapcd.org/pubs/Engineering/AirToxics/combem.pdf>
Only includes TACs with acute reference exposure levels.

Table 24 Diesel Exhaust Emissions of TACs with Acute Effects

**Table 24-I
Emergency Generator (0.5 hours/day, 26 hrs/year)**

Compound	CAS Number	Emission Factor (lb/1,000 gal) ^a	Emissions (lb/hour)
Benzene	71-43-2	0.1863	1.05E-03
Formaldehyde	50-00-0	1.7261	9.75E-03
Acetaldehyde	75-07-0	0.7833	4.43E-03
Acrolein	107-02-8	0.0339	1.92E-04
1,3-Butadiene	106-99-0	0.2174	1.23E-03
Toluene	108-88-3	0.1054	5.96E-04
Xylenes	1330-20-7	0.0424	2.40E-04
Hydrogen chloride	7647-01-0	0.1863	1.05E-03
Arsenic	7440-38-2	0.0016	9.04E-06
Copper	7440-50-8	0.0041	2.32E-05
Mercury	7439-97-6	0.0020	1.13E-05
Nickel	7440-02-0	0.0039	2.20E-05

EMGEN

Hourly fuel use = 11.30 gal/hr

^a From Ventura County Air Pollution Control District
AB 2588 Emission Factors for Diesel Fuel Internal
Combustion.
<http://www.vcapcd.org/pubs/Engineering/AirToxics/combem.pdf>
Only includes TACs with acute reference exposure levels.

Table 25

AD NH3 Emissions

Item	Value	Comment
Digestate production (ton/yr)	73,590	AD design capacity
Digestate production (ton/day)	201.62	Annual / 365 days/year
Fraction food waste	0.481	Mustang estimate
Fraction green waste	0.519	Mustang estimate
Digestate from food waste (ton/day)	96.98	
Digestate from green waste (ton/day)	104.64	
Food waste EF (lb NH3/ton)	14.20	From SJVAPCD Compost VOC Emission Factors, Sept. 2010 ^a
Green waste EF (lb NH3/ton)	2.37	From SJVAPCD Compost VOC Emission Factors, Sept. 2010 ^a
Food waste EF (lb VOC/ton-day)	0.237	For one day of 60-day composting cycle
Green waste EF (lb VOC/ton-day)	0.040	For one day of 60-day composting cycle
NH3 from food waste (lb/day)	22.95	
NH3 from green waste (lb/day)	4.13	
Total NH3 (lb/day)	27	
Reduction from biofilter	0.95	
NH3 after biofilter (lb/day)	1.35	
VOC after biofilter (lb/hour)	0.06	Daily / 24 hours/day
VOC after biofilter (lb/yr)	494	

^a From Compost VOC Emission Factors, San Joaquin Valley Air Pollution Control District, September 2010. Available at: <http://valleyair.org/Workshops/postings/2010/9-22-10-rule4566/SJVAPCD%20Compost%20VOC%20EF%20Report%209-15-10.pdf>
Food waste emission factor from Appendix A, Table 6.1 for AgBag windrow
Green waste emission factor from Table 1

Table 26 TOTAL AD Biofilter Organic Toxic Air Contaminant Emissions

Compound	CAS Number	ROC Mass Fraction ^a	Hourly Emission Rate (lb/hr) ^b	Annual Emission Rate (lb/yr) ^c	BF TIP		BF ADF		BF RECYC	
					Hourly Emission Rate (lb/hr) ^b	Annual Emission Rate (lb/yr) ^c	Hourly Emission Rate (lb/hr) ^b	Annual Emission Rate (lb/yr) ^c	Hourly Emission Rate (lb/hr) ^b	Annual Emission Rate (lb/yr) ^c
Isopropyl alcohol	67-63-0	0.423	6.16E-02	5.40E+02	2.03E-02	1.78E+02	9.91E-03	8.68E+01	2.15E-02	1.89E+02
Methyl alcohol	67-56-1	0.128	1.86E-02	1.63E+02	6.13E-03	5.37E+01	3.00E-03	2.63E+01	6.51E-03	5.70E+01
Naphthalene	91-20-3	0.005	7.28E-04	6.38E+00	2.40E-04	2.10E+00	1.17E-04	1.03E+00	2.54E-04	2.23E+00
Acetaldehyde	75-07-0	0.001	2.04E-04	1.79E+00	6.71E-05	5.88E-01	3.28E-05	2.87E-01	7.12E-05	6.24E-01
H2S	7783064	0.300	4.37E-02	3.83E+02	1.44E-02	1.26E+02	7.03E-03	6.16E+01	1.53E-02	1.34E+02
Ammonia	NH3		5.64E-02	4.94E+02	1.86E-02	1.63E+02	9.08E-03	7.95E+01	1.97E-02	1.73E+02

Hourly ROC Emissions = 0.15 lb/hr

Annual ROC Emissions = 1,276.09 lb/yr

^a From Anuj Kumer, et. al, Volatile organic compound emissions from green waste composting: Characterization and ozone formation, Atmos. Environ., 45 (2011) 1841-1848.

^b Hourly emission rate [lb/hr] = Hourly ROC emission rate [lb/hr] x Mass Fraction

^c Annual emission rate [lb/yr] = Annual ROC emission rate [lb/yr] x Mass Fraction

Biofilter	m ³ /min	Fract.
Tipping Area	1,461	0.329
ADF	1,428	0.322
Scrub	1,550	0.349
Total	4,439	1.000

Table 27
Windrow NH3 Emissions

Item	Value	Comment
Digestate production (ton/yr)	73,590	AD design capacity
Digestate production (ton/day)	201.62	Annual / 365 days/year
Fraction food waste	0.481	Mustang estimate
Fraction green waste	0.519	Mustang estimate
Digestate from food waste (ton/day)	96.98	
Digestate from green waste (ton/day)	104.64	
Food waste EF (lb NH3/ton)	14.20	From SJVAPCD Compost VOC Emission Factors, Sept. 2010 ^a
Green waste EF (lb NH3/ton)	2.37	From SJVAPCD Compost VOC Emission Factors, Sept. 2010 ^a
NH3 from food waste (lb/day)	1,377.08	
NH3 from green waste (lb/day)	247.99	
Total NH3 (lb/day)	1,625	
Reduction from digestion process	0.97	See note b
NH3 after reduction from digestion (lb/day)	48.75	
Reduction from Best Available Control Technologies	0.90	See note c
NH3 after BMP reductions (lb/day)	4.88	
NH3 after BMP reductions (lb/hour)	0.20	Daily / 24 hours/day
NH3 after BMP reductions (lb/yr)	1,779	

^a From Compost VOC Emission Factors, San Joaquin Valley Air Pollution Control District, September 2010. Available at: <http://valleyair.org/Workshops/postings/2010/9-22-10-rule4566/SJVAPCD%20Compost%20VOC%20EF%20Report%209-15-10.pdf>
Food waste emission factor from Appendix A, Table 6.1 for AgBag windrow
Green waste emission factor from Table 1

^b From Bay Area Air Quality Management District engineering evaluation for Zero Waste Energy proposed anaerobic digestion facility

^c Best Available Control Technologies:
1. 20% inert, dry wood chip blending
2. Interactive pile management (i.e., turning)
3. 20 minutes irrigation after turning
4. Large pile size
5. Finished compost blanket pseudo biofilter

References for emission reductions include:

Advice from Bekon based on 20 facilities operating in Europe

Comparison of Mitigation Measures for Reduction of Emissions from Greenwaste Composting prepared from SJVAPCD 2009:
http://valleyair.org/busind/pto/emission_factors/Criteria/Criteria/Composting/FINAL-COMPOST-STUDY-REPORT.pdf

Greenwaste Compost Air Emissions Review (Modesto Compost Facility) prepared from CIWMB June 2008:

<http://www.calrecycle.ca.gov/publications/Documents/Organics%5C44207009.pdf>

Greenwaste Compost Site Emissions Reductions Prepared for San Joaquin Valley Technology Advancement Program May 2013:

http://www.valleyair.org/grant_programs/TAP/documents/C-15636-ACP/C-15636_ACP_FinalReport.pdf

Table 28
Composting Windrow Fugitive Organic Toxic Air Contaminant Emissions

Compound	CAS Number	ROC Mass Fraction ^a	Hourly Emission Rate (lb/hr) ^b	Annual Emission Rate (lb/yr) ^c
Isopropyl alcohol	67-63-0	0.423	2.22E-01	1.94E+03
Methyl alcohol	67-56-1	0.128	6.71E-02	5.88E+02
Naphthalene	91-20-3	0.005	2.62E-03	2.30E+01
Acetaldehyde	75-07-0	0.001	7.34E-04	6.43E+00

Hourly ROC Emissions = 0.52 lb/hr

Annual ROC Emissions = 4,593.91 lb/yr

^a From Anuj Kumer, et. al, Volatile organic compound emissions from green waste composting: Characterization and ozone formation, Atmos. Environ., 45 (2011) 1841-1848.

^b Hourly emission rate [lb/hr] = Hourly ROC emission rate [lb/hr] x Mass Fraction

^c Annual emission rate [lb/yr] = Annual ROC emission rate [lb/yr] x Mass Fraction

Table 29-A

MRF Criteria Pollutant Daily Emissions Summary with CSSR

Source	Emissions (lb/day)					
	CO	ROC	NOx	SOx	PM10	PM2.5
Onsite						
MRF Facility Equipment	48.18	2.22	13.21	0.07	0.00	0.00
Diesel Fuel Storage Tank		0.02				
Material Handling Fugitive PM					0.00	0.00
Onsite Total	48.18	2.24	13.21	0.07	0.00	0.00
Offsite						
Motor Vehicle Exhaust	28.03	5.17	2.84	0.08	0.44	0.34
Motor Vehicle Fugitive PM					4.39	1.08
Offsite Total	28.03	5.17	2.84	0.08	4.83	1.42
Total	76.21	7.42	16.06	0.15	4.83	1.42

Table 29-B

MRF Criteria Pollutant Annual Emissions Summary with CSSR

Source	Emissions (ton/year)					
	CO	ROC	NOx	SOx	PM10	PM2.5
Onsite						
MRF Facility Equipment	7.49	0.35	2.05	0.01	0.00	0.00
Diesel Fuel Storage Tank		0.01				
Material Handling Fugitive PM					0.00	0.00
Onsite Total^a	7.49	0.35	2.05	0.01	0.00	0.00
Offsite						
Motor Vehicle Exhaust	4.36	0.80	0.44	0.01	0.07	0.05
Motor Vehicle Fugitive PM					0.68	0.17
Offsite Total	4.36	0.80	0.44	0.01	0.75	0.22
Total	11.85	1.16	2.50	0.02	0.75	0.22

Table 30
MRF Greenhouse Gas Annual Emissions Summary with CSSR

Source	Emissions (MT/year) ^a			
	CO ₂	CH ₄	N ₂ O	CO ₂ e ^b
Onsite				
MRF Facility Equipment	1,122.79	0.06	0.03	1,132.90
Onsite Total	1,122.79	0.06	0.03	1,132.90
Offsite				
Motor Vehicle Exhaust	1,747.41	2.90	0.26	1,898.09
Offsite Total	1,747.41	2.90	0.26	1,898.09
Total	2,870.20	2.96	0.29	3,030.99

^a Metric ton = 1,000 kilograms = pounds x 453.6 g/lb / 1,000,000 g/MT

^b CO₂e = CO₂-equivalent = CO₂ + 25 x CH₄ + 298 x N₂O

Table 31

MRF Equipment Exhaust Emissions

Equipment	Horsepower	Number	Hours/Day	Fuel Use (gal/hr)	Emission Stds.	Emission Factors (g/bhp-hr) ^a					Emission Factor [g/gal]		
						CO	ROC ^b	NOx ^b	PM10 ^c	PM2.5 ^c	CO ₂ ^d	CH ₄ ^e	N ₂ O ^e
Materials Recovery Facility Building													
Caterpillar M322D Material Handler	173	1	16	2.7	Tier 4	3.7	0.14	0.3	0.015	0.015	10,210	0.58	0.26
CAT 966 M Loader	311	2	16	3.1	Tier 4	2.7	0.14	0.3	0.015	0.015	10,210	0.58	0.26
CAT 938 K Loader	169	1	16	2.7	Tier 4	3.7	0.14	0.3	0.015	0.015	10,210	0.58	0.26
CAT 2P-6000 Forklift	61	3	16	1.5	Tier 4	3.7	0.18	3.33	0.02	0.02	10,210	0.58	0.26
Tennant 800 Sweeper	65	1	24	4	Tier 4	3.7	0.18	3.33	0.02	0.02	10,210	0.58	0.26

^a Emission factors assumed the same as emission standards.

^b Where standard is for NMHC+NOx (Volvo L20F, Toyota forklifts and Tennant sweeper), emissions assumed to be 5 percent ROC and 95 percent NOx, from Table D-25 of 2011 Carl Moyer Program Guidelines - <http://www.arb.ca.gov/msprog/moyer/guidelines/current.htm>

^c PM10 and PM2.5 assumed to be same as PM emission standards.

^d From Table C-1 of Title 40, Code of Federal Regulations, Subpart 98 for No. 2 distillate fuel oil.

^e CH₄ and N₂O from Table 13.7 of 2013 Climate Action Registry Default Emission Factors, downloaded from <http://www.theclimateregistry.org/downloads/2013/01/2013-Climate-Registry-Default-Emissions-Factors.pdf>

Equipment	Load Factor ^c	Emission Rates Each Unit (lb/hr)								
		CO ^a	ROC ^a	NOx ^a	SOx ^b	PM10 ^{a,d}	PM2.5 ^{a,d}	CO ₂ ^e	CH ₄ ^e	N ₂ O ^e
Materials Recovery Facility Building										
Caterpillar M322D Material Handler	0.3618	0.511	0.019	0.041	0.00056	2.07E-06	2.07E-06	60.77	3.45E-03	1.55E-03
CAT 966 M Loader	0.3618	0.670	0.035	0.074	0.00065	3.72E-06	3.72E-06	69.78	3.96E-03	1.78E-03
CAT 938 K Loader	0.3618	0.499	0.019	0.040	0.00056	2.02E-06	2.02E-06	60.77	3.45E-03	1.55E-03
CAT 2P-6000 Forklift	0.201	0.100	0.005	0.090	0.00031	5.41E-07	5.41E-07	33.76	1.92E-03	8.60E-04
Tennant 800 Sweeper	0.4556	0.242	0.011	0.217	0.00083	1.31E-06	1.31E-06	90.04	5.11E-03	2.29E-03

Diesel Fuel Density = 6.943 lb/gal

Diesel Fuel Sulfur = 15 ppmw

^a Emission Rate [lb/hr] = Emission Factor [g/bhp-hr] x Engine Horsepower [hp] x Load Factor [unitless] / 453.6 [g/lb]

^b Emission Rate [lb/hr] = Fuel Use [gal/hr] x Fuel Density [lb/gal] x Fuel Sulfur [ppmw] x 10⁻⁶ x 2 [lb SO₂/lb S]

^c From OFFROAD 2011 model

^d PM10 and PM2.5 emissions from buildings controlled by dust collectors with 99.9 percent control efficiency

^e Emission rate [lb/hr] = Fuel use [gal/hr] x Emission factor [g/gal] / 453.6 [lb/gal]

Table 31

MRF Equipment Exhaust Emissions

Equipment	Daily Emissions (lb/day) ^a								
	CO	ROC	NOx	SOx	PM10	PM2.5	CO ₂	CH ₄	N ₂ O
Materials Recovery Facility Building									
Caterpillar M322D Material Handler	8.17	0.31	0.66	0.01	3.31E-05	3.31E-05	972.38	0.06	0.02
CAT 966 M Loader	21.43	1.11	2.38	0.02	1.19E-04	1.19E-04	2,232.87	0.13	0.06
CAT 938 K Loader	7.98	0.30	0.65	0.01	3.24E-05	3.24E-05	972.38	0.06	0.02
CAT 2P-6000 Forklift	4.80	0.23	4.31	0.01	2.59E-05	2.59E-05	1,620.63	0.09	0.04
Tennant 800 Sweeper	5.80	0.27	5.21	0.02	3.13E-05	3.13E-05	2,160.85	0.12	0.06
Total	48.18	2.22	13.21	0.07	0.00	0.00	7,959.12	0.45	0.20

^a Daily Emissions [lb/day] = Hourly Emissions [lb/hr-unit] x Number Units x Operating Time [hr/day]

Equipment	Days/Year	Annual Emissions (lb/year) ^a								
		CO	ROC	NOx	SOx	PM10	PM2.5	CO ₂	CH ₄	N ₂ O
Materials Recovery Facility Building										
Caterpillar M322D Material Handler	311	2,540.53	96.13	205.99	2.80	0.01	0.01	3.02E+05	17.18	7.70
CAT 966 M Loader	311	6,665.46	345.62	740.61	6.43	0.04	0.04	6.94E+05	39.45	17.68
CAT 938 K Loader	311	2,481.79	93.91	201.23	2.80	0.01	0.01	3.02E+05	17.18	7.70
CAT 2P-6000 Forklift	311	1,492.99	70.61	1,341.67	4.66	0.01	0.01	5.04E+05	28.63	12.83
Tennant 800 Sweeper	311	1,803.01	85.28	1,620.27	6.22	0.01	0.01	6.72E+05	38.18	17.11
Total		14,983.77	691.54	4,109.76	22.91	0.08	0.08	2.48E+06	140.61	63.03

^a Annual Emissions [lb/year] = Daily Emissions [lb/day] x Operating Days [days/year]

Table 32 MRF Off-Site Motor Vehicle Exhaust Emissions with CSSR

Vehicle	Use	Fuel	One-Way Trips/Day	Mileage (mpg) ^b	One-Way Trip Dist. (mi)	Miles/Day
Freightliner Tractors	Recycleables to POLA ^a	CNG	36	6	131	4,716
Tractor/Trailer	CSSR from SCRTS to Tajiguas instead of Gold Coast ^c	Diesel	14	6	-17	-238
Worker Commuting	From the North ^d	Gasoline	56	22	37	2,072
Worker Commuting	From the South ^d	Gasoline	6	22	15	90

^a Round trips/day = 126,000 tons/yr / 311 op. days/yr / 22 tons/trip = 18.4 one-way trips/day x 2 = 36.8 one-way trips/day rounded to 36
^b Except for Freightliner Tractor, calculated by dividing EMFAC2011 calculated total daily fuel use in Santa Barbara County in 2017 by total miles in Santa Barbara County
Mileage for Freightliner Tractor is diesel-equivalent, Mustang estimate
^c Round trips are from Project Traffic Study. Mileage is difference between SCRTS to Tajiguas (22 mi.) and SCRTS to Gold Coast (39 mi.)
^d Trips/day are from Project Traffic Study

Vehicle	Use	EMFAC Vehicle Class	Emission Factors (g/mi)								
			CO ^{a,b}	ROC ^{a,c}	NOx ^{a,c}	SOx ^{a,d}	PM10 ^{a,e}	PM2.5 ^{a,e}	CO ₂ ^{a,f}	CH ₄ ^{a,f}	N ₂ O ^{1,g}
Freightliner Tractors	Recycleables to POLA	N/A	1.17E+00	3.70E-01	4.60E-01	6.80E-03	2.90E-02	2.90E-02	1.13E+03	1.97E+00	1.75E-01
Tractor/Trailer	CSSR from SCRTS to Tajiguas instead of Gold Coast	T7 tractor	1.16E+00	2.53E-01	6.95E+00	1.69E-02	1.80E-01	1.11E-01	1.68E+03	1.38E-02	5.81E-02
Worker Commuting	From the North	LDT1	3.46E+00	3.06E-01	3.59E-01	3.81E-03	4.83E-02	2.10E-02	3.11E+02	2.52E-02	1.49E-02
Worker Commuting	From the South	LDT1	3.46E+00	3.06E-01	3.59E-01	3.81E-03	4.83E-02	2.10E-02	3.11E+02	2.52E-02	1.49E-02

Diesel Fuel HV = 128,450 Btu/gal
Natural Gas HV = 1,020 Btu/scf
Natural Gas S = 0.5 grains/100 scf
Diesel Fuel Density = 6.943 lb/gal
Diesel Fuel Sulfur = 15 ppmw
Natural Gas CO₂ EF = 0.054 Kg/scf from Table 13.1 of 2013 Climate Action Registry Default Emission Factors, downloaded from <http://www.theclimaterestry.org/downloads/2013/01/2013-Climat-Registry-Default-Emissions-Factors.pdf>

^a Except for Freightliner Tractor, calculated by dividing EMFAC2011 calculated total daily emissions in Santa Barbara County in 2017 by total miles in Santa Barbara County
^b Freightliner tractor calculated by dividing EMFAC2011 calculated total daily CO emissions from 2017 model year T7 tractors in Santa Barbara County in 2017 by total miles in Santa Barbara County
^c Freightliner tractor is 2010 and later model year standard from Table D-1a of 2011 Carl Moyer Program Guidelines - <http://www.arb.ca.gov/msprog/moyer/guidelines/current.htm>
^d Freightliner tractor calculated from (1/diesel-equivalent mpg) x diesel fuel heating value (Btu/gal) / natural gas heating value (Btu/scf) x natural gas sulfur content (grains/100 scf) / 100 / 7,000 (grains/lb) x 453.6 (g/lb) x 2 (g SO₂/g S)
^e Freightliner tractor calculated from (1/diesel-equivalent mpg) x diesel fuel heating value (Btu/gal) / natural gas heating value (Btu/scf) x natural gas CO₂ EF (kg/scf) x 1,000 (g/kg)
^f Freightliner Tractor from Table 13.6 of 2013 Climate Action Registry Default Emission Factors, downloaded from <http://www.theclimaterestry.org/downloads/2013/01/2013-Climat-Registry-Default-Emissions-Factors.pdf>
^g Emission factor for gasoline calculated from 0.0416 x NOx emission factor; emission factor for diesel calculated as 0.3316 [g/gal] / mileage [mpg]; see: http://www.arb.ca.gov/msei/emfac2011-faq.htm#emfac2011_web_db_qstr07

Table 32 MRF Off-Site Motor Vehicle Exhaust Emissions with CSSR

Vehicle	Use	Daily Emissions (lb/day) ^a								
		CO	ROC	NOx	SOx	PM10	PM2.5	CO ₂	CH ₄	H ₂ O
Freightliner Tractors	Recycleables to POLA	12.13	3.85	4.78	0.07	0.30	0.30	11,783.58	20.44	1.82
Tractor/Trailer	CSSR from SCRTS to Tajiguas instead of Gold Coast	-0.61	-0.13	-3.65	-0.01	-0.09	-0.06	-880.47	-0.01	-0.03
Worker Commuting	From the North	15.83	1.40	1.64	0.02	0.22	0.10	1,421.98	0.12	0.07
Worker Commuting	From the South	0.69	0.06	0.07	0.00	0.01	0.00	61.77	0.01	0.00
Total		28.03	5.17	2.84	0.08	0.44	0.34	12,386.86	20.55	1.86

^a Daily emissions [lb/day] = Miles/day x Emission factor [g/mi] / 453.6 [g/lb]

Vehicle	Use	Op. Days/yr	Annual Emissions (lb/year) ^a								
			CO	ROC	NOx	SOx	PM10	PM2.5	CO ₂	CH ₄	N ₂ O
Freightliner Tractors	Recycleables to POLA	311	3,771.65	1,196.36	1,487.37	21.99	93.77	93.77	3,664,692.89	6,356.89	565.85
Tractor/Trailer	CSSR from SCRTS to Tajiguas instead of Gold Coast	311	-189.68	-41.25	-1,134.46	-2.75	-29.39	-18.15	-273,825.41	-2.25	-9.48
Worker Commuting	From the North	311	4,922.35	434.92	509.53	5.41	68.65	29.84	442,237.03	35.80	21.20
Worker Commuting	From the South	311	213.81	18.89	22.13	0.24	2.98	1.30	19,209.14	1.56	0.92
Total			8,718.13	1,608.92	884.57	24.89	136.02	106.75	3,852,313.65	6,391.99	578.48

^a Annual emissions [lb/year] = Daily emissions [lb/day] x Operating days/year

Off-Site Motor Vehicle Fugitive PM Emissions

Emission Factors for Vehicles on Off-Site Paved Roads

Parameter	Value	Comments
Road silt loading (g/m ²)	0.1	CalEEMod default
Onroad vehicles average weight (tons)	2.4	CalEEMod Default for Santa Barbara County
PM10 emission factor (lb/mile)	6.61E-04	0.0022 x (silt loading [g/m ²]) ^{0.91} x (average vehicle weight) ^{1.02} from AP-42 Section 13.2.1, Paved Roads(01/11)
PM2.5 emission factor (lb/mile)	1.62E-04	0.00054 x (silt loading [g/m ²]) ^{0.91} x (average vehicle weight) ^{1.02} from AP-42 Section 13.2.1, Paved Roads(01/11)

Vehicle	Use	Miles/Day	Op. Days/yr	Daily Emissions (lb/day) ^a		Annual Emissions (lb/year) ^b	
				PM10	PM2.5	PM10	PM2.5
Freightliner Tractors	Recycleables to POLA	4,716	311	3.12	0.77	969.55	237.98
Tractor/Trailer	CSSR from SCRTS to Tajiguas instead of Gold Coast	-238	311	-0.16	-0.04	-48.93	-12.01
Worker Commuting	From the North	2,072	311	1.37	0.34	425.98	104.56
Worker Commuting	From the South	90	311	0.06	0.01	18.50	4.54
Total				4.39	1.08	1,365.11	335.07

^a Daily emissions [lb/day] = Miles/day x Emission factor [lb/mi]

^b Annual emissions [lb/year] = Daily emissions [lb/day] x Operating days/year

Table 33 MRF On-Site Fugitive PM Emissions with CSSR

Material Transfers with CSSR

Material	Transfer	Moisture (%) ^a	Daily Amount (tons)	Annual Op. (Days/year)	Emission Factors (lb/ton) ^b		Emissions (lb/day) ^{c,e}		Emissions (lb/year) ^d	
					PM10	PM2.5	PM10	PM2.5	PM10	PM2.5
MSW	Into MRF Facility	28	930	311	3.84E-04	5.82E-05	3.57E-04	5.41E-05	0.11	0.02

^a From Table 9, Appendix E.8 of the Draft EIR for the Tajiguas Landfill Expansion Project, Santa Barbara County No. 01-EIR-5

^b Emission factor [lb/ton] = $k \times 0.0032 \times (\text{wind speed [mph]} / 5)^{1.3} / (\text{material moisture [%]} / 2)^{1.4}$
 from AP-42, Section 13.2.4, Aggregate Handling and Storage Piles (11/06)
 k = 0.35 for PM10
 0.053 for PM2.5

Wind speed = 5.47 mph, from Table 9, Appendix E.8 of the Draft EIR for the Tajiguas Landfill Expansion Project, Santa Barbara County No. 01-EIR-5

^c Emissions [lb/day] = Emission factor [lb/ton] x Daily amount [tons]

^d Emissions [lb/year] = Emissions [lb/day] x Days/year

^e PM10 and PM2.5 emissions from buildings controlled by dust collectors with 99.9 percent control efficiency

Table 34

Motor Vehicle Emission Factors in Santa Barbara County for 2017

Vehicle Class	Fuel		Emission Factors (g/mi) ^a										Mileage (mpg)
			CO	ROG	NOx	SOx	PM10	PM2.5	CO ₂	TOG	CH ₄	N ₂ O	
LDA	GAS	LDAGAS	1.48E+00	1.31E-01	1.48E-01	3.26E-03	4.68E-02	1.97E-02	2.51E+02	1.45E-01	1.31E-02	6.14E-03	26.09
LDA	DSL	LDADSL	1.55E-01	2.65E-02	4.71E-01	3.31E-03	6.34E-02	3.49E-02	2.71E+02	3.01E-02	1.45E-03	1.14E-02	29.10
LDT1	GAS	LDT1GAS	3.46E+00	3.06E-01	3.59E-01	3.81E-03	4.83E-02	2.10E-02	3.11E+02	3.33E-01	2.52E-02	1.49E-02	22.32
LDT1	DSL	LDT1DSL	2.53E-01	5.47E-02	6.14E-01	3.38E-03	8.97E-02	5.91E-02	2.78E+02	6.23E-02	2.99E-03	1.16E-02	28.49
LDT2	GAS	LDT2GAS	2.46E+00	2.27E-01	3.47E-01	4.46E-03	4.73E-02	2.01E-02	3.69E+02	2.49E-01	2.11E-02	1.44E-02	19.08
LDT2	DSL	LDT2DSL	1.81E-01	3.17E-02	5.51E-01	3.32E-03	6.82E-02	3.94E-02	2.82E+02	3.60E-02	1.73E-03	1.14E-02	28.99
LHD1	GAS	LHD1GAS	5.86E+00	7.03E-01	1.13E+00	1.00E-02	4.85E-02	2.12E-02	9.44E+02	7.56E-01	4.55E-02	4.70E-02	8.48
LHD1	DSL	LHD1DSL	1.22E+00	2.23E-01	3.57E+00	5.02E-03	1.39E-01	8.12E-02	4.99E+02	2.54E-01	1.22E-02	1.73E-02	19.17
LHD2	GAS	LHD2GAS	3.94E+00	5.03E-01	9.78E-01	9.99E-03	4.73E-02	2.01E-02	9.44E+02	5.43E-01	4.03E-02	4.07E-02	8.51
LHD2	DSL	LHD2DSL	1.16E+00	2.07E-01	3.36E+00	5.02E-03	1.47E-01	8.38E-02	4.99E+02	2.36E-01	1.13E-02	1.73E-02	19.19
MCV	GAS	MCVGAS	2.85E+01	3.62E+00	1.35E+00	2.17E-03	4.55E-02	1.84E-02	1.55E+02	3.90E+00	2.41E-01	5.61E-02	39.15
MDV	GAS	MDVGAS	3.37E+00	2.87E-01	5.09E-01	5.66E-03	4.73E-02	2.01E-02	4.85E+02	3.20E-01	3.14E-02	2.11E-02	15.03
MDV	DSL	MDVDSL	1.47E-01	2.63E-02	4.04E-01	3.32E-03	6.53E-02	3.66E-02	2.94E+02	2.99E-02	1.43E-03	1.14E-02	29.00
MH	GAS	MHGAS	5.38E+00	2.11E-01	8.76E-01	6.86E-03	4.71E-02	1.98E-02	6.44E+02	2.48E-01	2.33E-02	3.64E-02	12.41
MH	DSL	MHDSL	7.31E-01	2.32E-01	7.05E+00	1.15E-02	3.36E-01	2.37E-01	1.14E+03	2.64E-01	1.27E-02	3.95E-02	8.40
Motor Coach	DSL	Motor CoachDSL	1.31E+00	2.74E-01	6.55E+00	1.74E-02	2.16E-01	1.27E-01	1.73E+03	3.12E-01	1.50E-02	6.00E-02	5.52
OBUS	GAS	OBUSGAS	1.62E+01	1.21E+00	2.67E+00	7.40E-03	4.65E-02	1.93E-02	6.77E+02	1.29E+00	8.25E-02	1.19E-01	11.49
PTO	DSL	PTODSL	7.94E-01	2.26E-01	9.79E+00	2.05E-02	6.43E-02	5.92E-02	2.05E+03	2.58E-01	1.24E-02	7.08E-02	4.68
SBUS	GAS	SBUSGAS	7.34E+00	6.16E-01	1.05E+00	7.64E-03	4.68E-02	1.96E-02	7.14E+02	6.70E-01	1.01E-01	4.37E-02	11.14
SBUS	DSL	SBUSDSL	8.65E-01	2.48E-01	1.18E+01	1.34E-02	8.77E-01	4.33E-01	1.33E+03	2.82E-01	1.35E-02	4.61E-02	7.20
T6 Ag	DSL	T6 AgDSL	1.07E+00	3.24E-01	4.79E+00	1.15E-02	3.11E-01	2.14E-01	1.15E+03	3.69E-01	1.77E-02	3.97E-02	8.36
T6 Public	DSL	T6 PublicDSL	3.34E-01	8.46E-02	6.51E+00	1.18E-02	1.81E-01	9.45E-02	1.18E+03	9.63E-02	4.62E-03	4.07E-02	8.15
T6 CAIRP heavy	DSL	T6 CAIRP heavyDSL	4.46E-01	1.22E-01	3.30E+00	1.14E-02	1.85E-01	9.85E-02	1.13E+03	1.39E-01	6.69E-03	3.92E-02	8.45
T6 CAIRP small	DSL	T6 CAIRP smallDSL	5.60E-01	1.54E-01	1.93E+00	1.13E-02	2.10E-01	1.22E-01	1.13E+03	1.76E-01	8.43E-03	3.90E-02	8.51
T6 OOS heavy	DSL	T6 OOS heavyDSL	4.46E-01	1.22E-01	3.30E+00	1.14E-02	1.85E-01	9.85E-02	1.13E+03	1.39E-01	6.69E-03	3.92E-02	8.45
T6 OOS small	DSL	T6 OOS smallDSL	5.60E-01	1.54E-01	1.93E+00	1.13E-02	2.10E-01	1.22E-01	1.13E+03	1.76E-01	8.43E-03	3.90E-02	8.51
T6 instate construction heavy	DSL	T6 instate construction heavyDSL	4.61E-01	1.31E-01	6.42E+00	1.15E-02	1.96E-01	1.09E-01	1.15E+03	1.49E-01	7.17E-03	3.97E-02	8.35
T6 instate construction small	DSL	T6 instate construction smallDSL	8.12E-01	2.31E-01	3.47E+00	1.14E-02	2.70E-01	1.76E-01	1.13E+03	2.63E-01	1.26E-02	3.92E-02	8.47
T6 instate heavy	DSL	T6 instate heavyDSL	4.62E-01	1.30E-01	5.77E+00	1.15E-02	1.95E-01	1.07E-01	1.14E+03	1.48E-01	7.12E-03	3.96E-02	8.37
T6 instate small	DSL	T6 instate smallDSL	7.62E-01	2.16E-01	3.16E+00	1.13E-02	2.59E-01	1.66E-01	1.13E+03	2.46E-01	1.18E-02	3.91E-02	8.48
T6 utility	DSL	T6 utilityDSL	3.86E-01	9.17E-02	3.53E+00	1.17E-02	1.74E-01	8.79E-02	1.16E+03	1.04E-01	5.01E-03	4.03E-02	8.24
T6TS	GAS	T6TSGAS	1.29E+01	1.02E+00	1.95E+00	7.24E-03	4.70E-02	1.98E-02	6.67E+02	1.09E+00	5.04E-02	8.10E-02	11.76
T7 Ag	DSL	T7 AgDSL	1.86E+00	4.07E-01	8.81E+00	1.71E-02	2.86E-01	2.08E-01	1.71E+03	4.63E-01	2.22E-02	5.91E-02	5.61
T7 CAIRP	DSL	T7 CAIRPDSL	1.74E+00	3.60E-01	4.50E+00	1.76E-02	1.81E-01	1.12E-01	1.75E+03	4.10E-01	1.97E-02	6.06E-02	5.47
T7 CAIRP construction	DSL	T7 CAIRP constructionDSL	1.74E+00	3.60E-01	4.50E+00	1.76E-02	1.81E-01	1.12E-01	1.75E+03	4.10E-01	1.97E-02	6.06E-02	5.47
T7 NNOOS	DSL	T7 NNOOSDSL	1.69E+00	3.39E-01	2.95E+00	1.77E-02	1.63E-01	9.53E-02	1.78E+03	3.86E-01	1.85E-02	6.10E-02	5.44
T7 NOOS	DSL	T7 NOOSDSL	1.89E+00	3.87E-01	4.66E+00	1.78E-02	1.82E-01	1.13E-01	1.78E+03	4.41E-01	2.12E-02	6.15E-02	5.39
T7 other port	DSL	T7 other portDSL	2.45E+00	5.29E-01	7.87E+00	1.73E-02	2.09E-01	1.38E-01	1.72E+03	6.02E-01	2.89E-02	5.96E-02	5.56
T7 POLA	DSL	T7 POLADSL	2.62E+00	5.58E-01	7.87E+00	1.76E-02	2.09E-01	1.38E-01	1.75E+03	6.36E-01	3.05E-02	6.07E-02	5.46
T7 Public	DSL	T7 PublicDSL	1.38E+00	2.76E-01	1.54E+01	2.01E-02	1.67E-01	9.92E-02	2.00E+03	3.14E-01	1.51E-02	6.93E-02	4.79
T7 Single	DSL	T7 SingleDSL	8.53E-01	1.83E-01	8.92E+00	1.71E-02	1.59E-01	9.17E-02	1.70E+03	2.08E-01	1.00E-02	5.90E-02	5.62
T7 single construction	DSL	T7 single constructionDSL	8.46E-01	1.82E-01	9.18E+00	1.71E-02	1.59E-01	9.21E-02	1.70E+03	2.07E-01	9.93E-03	5.90E-02	5.62
T7 SWCV	DSL	T7 SWCVDSL	1.05E+00	2.13E-01	1.23E+01	1.84E-02	1.61E-01	9.40E-02	1.83E+03	2.43E-01	1.17E-02	6.33E-02	5.24
T7 tractor	DSL	T7 tractorDSL	1.16E+00	2.53E-01	6.95E+00	1.69E-02	1.80E-01	1.11E-01	1.68E+03	2.88E-01	1.38E-02	5.81E-02	5.71
T7 tractor construction	DSL	T7 tractor constructionDSL	1.25E+00	2.69E-01	7.90E+00	1.71E-02	1.81E-01	1.12E-01	1.70E+03	3.06E-01	1.47E-02	5.90E-02	5.62
T7 utility	DSL	T7 utilityDSL	1.90E+00	3.60E-01	9.58E+00	1.99E-02	1.48E-01	8.14E-02	1.98E+03	4.10E-01	1.97E-02	6.86E-02	4.83
T7IS	GAS	T7ISGAS	4.33E+01	1.28E+00	5.91E+00	6.63E-03	4.58E-02	1.87E-02	5.63E+02	1.45E+00	1.01E-01	2.46E-01	12.82
UBUS	GAS	UBUSGAS	1.85E+01	3.27E+00	4.52E+00	7.86E-03	4.83E-02	2.11E-02	7.11E+02	3.48E+00	1.30E-01	1.88E-01	10.83
UBUS	DSL	UBUSDSL	2.17E+00	4.67E-01	1.26E+01	2.36E-02	1.08E+00	5.78E-01	2.35E+03	5.32E-01	2.55E-02	8.14E-02	4.07
All Other Buses	DSL	All Other BusesDSL	5.08E-01	1.42E-01	5.35E+00	1.15E-02	1.98E-01	1.10E-01	1.14E+03	1.62E-01	7.78E-03	3.95E-02	8.39

^a CO, ROG, NOx, SO₂, PM10, PM2.5, TOG and CO₂ calculated by dividing total daily emissions in Santa Barbara County for 2017 by total miles, and mileage calculated by dividing total daily fuel use by total miles from EMFAC2011 online data (<http://www.arb.ca.gov/emfac/>). CH₄ for gasoline-fueled vehicles calculated by dividing total daily emissions in Santa Barbara County for 2017 by total miles calculated with EMFAC2011-LDV (http://www.arb.ca.gov/msei/emfac2011_ldv.htm). CH₄ for diesel-fueled vehicles calculated as 0.048 x TOG (http://www.arb.ca.gov/msei/emfac2011-faq.htm#emfac2011_web_db_qstn07). N₂O for gasoline-fueled vehicles calculated as 0.046 x NOx, and N₂O for diesel-fueled vehicles calculated as 0.3316 grams/gallon (see http://www.arb.ca.gov/msei/emfac2011-faq.htm#emfac2011_web_db_qstn07)

Appendix B Existing Landfill Sources Emissions Calculations

Table 1
Gasoline Dispensing Emissions
<http://www.sbcpd.org/eng/dl/appforms/apcd-25T.pdf>

SBCAPCD Approved Emission Factors

Phase	lb/1000 gal	lb/yr	lb/hr
Loading	0.15	0.557	6.354E-05
Breathing	0.25	0.928	1.059E-04
Refueling	0.42	1.559	1.779E-04
Spillage	0.42	1.559	1.779E-04
Total	1.24	4.602	5.253E-04

Annual Throughput: 3711 gal/yr

% Benzene 0.3 0.1
 0.003 0.01

Benzene Emissions for Modeling

Phase	lb/yr	lb/hr
Loading	1.670E-03	1.906E-07
Breathing	2.783E-03	3.177E-07
Refueling	4.676E-03	5.338E-07
Spillage	1.559E-02	1.779E-06

Modeling Parameters

Process	Release Height (ft)	Stack Temp (deg F)	Stack Vel (ft/min)	Stack Dia (ft)	σ_{Zint} (ft)	σ_{Yint} (ft)
Loading	12	65	0.000463	0.167	--	--
Breathing	12	60	0.000771	0.167	--	--
Refueling	3.28	--	--	--	6.1	9.16
Spillage	0	--	--	--	6.1	9.16

Modeling Parameters

Process	Release Height (m)	Stack Temp (deg K)	Stack Vel (m/s)	Stack Dia (m)	σ_{Zint} (m)	σ_{Yint} (m)	Source ID
Loading	3.658	291.483	2.350E-06	0.051	--	--	GASLOAD
Breathing	3.658	288.706	3.917E-06	0.051	--	--	GASBREAT
Refueling	1.000	--	--	--	1.859	2.792	GASREFU
Spillage	0.000	--	--	--	1.859	2.792	GASSPILL

Table 2
LFG Fugitive Emissions

Item	Units	Value	Comments
CH ₄ Production	MT/yr	8,565	From GHG Analysis ^a
CH ₄ Production	cu. ft./yr	4.55E+08	cu. ft. = MT x 10 ⁶ g/MT / 453.6 g/lb / 16 lb/lb-mole x 385.5 cf/lb-mole
LFG Production	cu. ft./yr	909,889,632.94	Default 50% CH ₄ from LandGEM Model
NMOC Concentration	ppmv as hexane	4,000	Default from LandGEM Model
NMOC Production	cu. ft./yr	3,639,558.53	cu. ft NMOC = cu. ft. LFG x ppmv NMOC x 10 ⁻⁶
NMOC Production	lb/yr	811,937.83	lb/yr = ppmv x 10 ⁻⁶ x 86 lb/lb-mole / 385.5 cu. ft./lb-mole
LFG Collection Efficiency	unitless	0.68	From GHG Analysis ^b
LFG Fugitive Emissions	cu. ft./yr	291,164,683	LFG fugitive emissions = LFG production x (1 - Collection efficiency)
LFG Fugitive NMOC Emissions	lb/yr	2.60E+05	Controlled = Uncontrolled x (1 - Collection efficiency)
LFG Fugitive NMOC Emissions	cu. ft./yr	1,164,658.73	Controlled = Uncontrolled x (1 - Collection efficiency)

^a Modeled using Equation HH-1 from 40 CFR 98, Subpart HH

^b Calculated using Equation HH-3 from 40 CFR 98, Subpart HH

103,869 SCFhr Estimated total LFG Production
 86,236 SCFhr Estimated Max LFG Flow rate to the engine & flare
 83.0% Potential landfill gas collection efficiency

Table 3
Landfill Gas TAC Concentrations

Compound	CAS Number	Molecular Weight	LFG Concentration (ppm) ^a					Selected Value ^b
			AP-42, Table 2.4-1	2009 Tajiguas Sample	2011 Tajiguas Sample	2012 Tajiguas Sample	2013 Tajiguas Sample	
1,1,1-Trichloroethane	71556	133.4	2.43E-01	2.00E-02	2.00E-02	4.00E-02	4.00E-02	4.00E-02
1,1,2,2-Tetrachloroethane	79345	167.86	5.35E-01	3.00E-02	3.00E-02	6.00E-02	6.00E-02	6.00E-02
1,1,2-Trichloroethane	79005	133.4	1.58E-01			6.00E-02	6.00E-02	6.00E-02
1,1-Dichloroethane	75343	98.96	2.08E+00	3.40E-02	3.00E-02	6.00E-02	6.00E-02	6.00E-02
1,1-Dichloroethene (1,1-Dichloroethylene)	75354	97	1.60E-01	4.00E-02	4.00E-02	6.00E-02	6.00E-02	6.00E-02
1,2-Dibromoethane (Ethylene dibromide)	106934	187.88	4.80E-03					4.80E-03
1,2-Dichloroethane (Ethylene dichloride)	107062	98.96	1.59E-01	3.00E-02	3.00E-02	6.00E-02	6.00E-02	6.00E-02
1,3-Butadiene (Vinyl ethylene)	106990	54.1	1.66E-01					1.66E-01
1,4-Dioxane (1,4-Diethylene dioxide)	123911	88.12	8.29E-03					8.29E-03
2-Butanone (Methyl ethyl ketone)	78933	72.11	4.01E+00	4.39E+00	4.72E+00	5.44E+00	3.86E+00	5.44E+00
2-Propanol (Isopropyl alcohol)	67630	60.1	1.80E+00	4.40E+00	1.00E+00	2.00E-01	2.00E-01	4.40E+00
Acetaldehyde	75070	44.06	7.74E-02					7.74E-02
Acrylonitrile	107131	53.06		1.50E-01	2.00E-01	3.00E-01	3.00E-01	3.00E-01
Benzene	71432	78.12	2.40E+00			5.09E-01	4.60E-01	5.09E-01
Benzyl chloride	100447	126.58	1.81E-02					1.81E-02
Bromomethane (Methyl bromide)	74839	94.95	2.10E-02					2.10E-02
Carbon disulfide	75150	76.13	1.47E-01	2.00E-01	2.00E-01	2.00E-01	2.00E-01	2.00E-01
Carbon tetrachloride	56235	153.81	7.98E-03	3.00E-02	3.00E-02	4.00E-02	4.00E-02	4.00E-02
Chlorobenzene	108907	112.56	4.84E-01	3.20E-02	4.40E-02	6.00E-02	7.20E-02	7.20E-02
Chloroethane (Ethyl chloride)	75003	64.52	3.95E+00	9.10E-02	4.00E-02	4.30E-02	6.00E-02	9.10E-02
Chloroform	67663	119.38		2.00E-02	2.00E-02	4.00E-02	4.00E-02	4.00E-02
Dichlorobenzene	106467	147.01	9.40E-01	1.68E-01	4.38E-01	5.00E-01	6.47E-01	6.47E-01
Dichloromethane (Methylene chloride)	75092	84.94	6.15E+00	5.70E-02	4.20E-02	6.00E-02	6.00E-02	6.00E-02
Ethylbenzene	100414	106.17	4.86E+00	3.26E+00	4.88E+00	5.28E+00	5.26E+00	5.28E+00
Formaldehyde	50000	30.03	1.17E-02					1.17E-02
Hydrogen sulfide	7783064	34.08	2.00E+01	7.39E+01	6.72E+01	9.40E+01	8.80E+01	9.40E+01
Methyl tert-butyl ether (MTBE)	1634044	88.15	1.18E-01					1.18E-01
Naphthalene	91203	128.18	1.07E-01					1.07E-01
Styrene (Vinylbenzene)	100425	104.16	4.11E-01					4.11E-01
Tetrachloroethylene (Perchloroethylene)	127184	165.82	2.03E+00	1.57E-01	1.14E-01	1.16E-01	1.02E-01	1.57E-01
Toluene (Methyl benzene)	108883	92.13	2.95E+01			3.80E+00	3.90E+00	3.90E+00
Trichloroethylene (Trichloroethene)	79016	131.38	8.28E-01	8.50E-02	5.50E-02	4.00E-02	6.10E-02	8.50E-02
Trichloromethane (Chloroform)	67663	119.37	7.08E-02	2.00E-02	2.00E-02	4.00E-02	4.00E-02	4.00E-02
Vinyl acetate	108054	86.09	2.48E-01					2.48E-01
Vinyl chloride (Chloroethene)	75014	62.5	1.42E+00	1.27E-01	7.50E-02	1.33E-01	8.60E-02	1.33E-01
Xylenes (o-, m-, p-, mixtures)	1330207	106.16	9.23E+00	8.52E+00	1.30E+01	1.40E+01	1.47E+01	1.47E+01

^a Values for Tajiguas samples are results from analysis of Tajiguas LI 92.35

131.63

^b Selected value is maximum value measured in Tajiguas samples or value from AP-42 if compound was not measured in Tajiguas samples.

Table 4
Landfill Gas Fugitive TAC Emissions

Compound	CAS Number	Molecular Weight	LFG Concentration (ppm) ^a	Hourly Emission Rate (lb/hr) ^b	Annual Emission Rate (lb/yr) ^c	LFG FUG
1,1,1-Trichloroethane	71556	133.40	4.00E-02	4.60E-04	4.03E+00	
1,1,2,2-Tetrachloroethane	79345	167.86	6.00E-02	8.68E-04	7.61E+00	
1,1,2-Trichloroethane	79005	133.40	6.00E-02	6.90E-04	6.05E+00	
1,1-Dichloroethane	75343	98.96	6.00E-02	5.12E-04	4.48E+00	
1,1-Dichloroethene (1,1-Dichloroethylene)	75354	97.00	6.00E-02	5.02E-04	4.40E+00	
1,2-Dibromoethane (Ethylene dibromide)	106934	187.88	4.80E-03	7.78E-05	6.81E-01	
1,2-Dichloroethane (Ethylene dichloride)	107062	98.96	6.00E-02	5.12E-04	4.48E+00	
1,3-Butadiene (Vinyl ethylene)	106990	54.10	1.66E-01	7.74E-04	6.78E+00	
1,4-Dioxane (1,4-Diethylene dioxide)	123911	88.12	8.29E-03	6.30E-05	5.52E-01	
2-Butanone (Methyl ethyl ketone)	78933	72.11	5.44E+00	3.38E-02	2.96E+02	
2-Propanol (Isopropyl alcohol)	67630	60.10	4.40E+00	2.28E-02	2.00E+02	
Acetaldehyde	75070	44.06	7.74E-02	2.94E-04	2.58E+00	
Acrylonitrile	107131	53.06	3.00E-01	1.37E-03	1.20E+01	
Benzene	71432	78.12	5.09E-01	3.43E-03	3.00E+01	
Benzyl chloride	100447	126.58	1.81E-02	1.98E-04	1.73E+00	
Bromomethane (Methyl bromide)	74839	94.95	2.10E-02	1.72E-04	1.51E+00	
Carbon disulfide	75150	76.13	2.00E-01	1.31E-03	1.15E+01	
Carbon tetrachloride	56235	153.81	4.00E-02	5.30E-04	4.65E+00	
Chlorobenzene	108907	112.56	7.20E-02	6.99E-04	6.12E+00	
Chloroethane (Ethyl chloride)	75003	64.52	9.10E-02	5.06E-04	4.43E+00	
Chloroform	67663	119.38	4.00E-02	4.12E-04	3.61E+00	
Dichlorobenzene	106467	147.01	6.47E-01	8.20E-03	7.18E+01	
Dichloromethane (Methylene chloride)	75092	84.94	6.00E-02	4.39E-04	3.85E+00	
Ethylbenzene	100414	106.17	5.28E+00	4.83E-02	4.23E+02	
Formaldehyde	50000	30.03	1.17E-02	3.03E-05	2.65E-01	
Hydrogen sulfide	7783064	34.08	9.40E+01	2.76E-01	2.42E+03	
Methyl tert-butyl ether (MTBE)	1634044	88.15	1.18E-01	8.97E-04	7.86E+00	
Naphthalene	91203	128.18	1.07E-01	1.18E-03	1.04E+01	
Styrene (Vinylbenzene)	100425	104.16	4.11E-01	3.69E-03	3.23E+01	
Tetrachloroethylene (Perchloroethylene)	127184	165.82	1.57E-01	2.24E-03	1.97E+01	
Toluene (Methyl benzene)	108883	92.13	3.90E+00	3.10E-02	2.71E+02	
Trichloroethylene (Trichloroethene)	79016	131.38	8.50E-02	9.63E-04	8.43E+00	
Trichloromethane (Chloroform)	67663	119.37	4.00E-02	4.12E-04	3.61E+00	
Vinyl acetate	108054	86.09	2.48E-01	1.84E-03	1.61E+01	
Vinyl chloride (Chloroethene)	75014	62.50	1.33E-01	7.17E-04	6.28E+00	
Xylenes (o-, m-, p-, mixtures)	1330207	106.16	1.47E+01	1.35E-01	1.18E+03	

LFG fugitive emission rate = 291,164,682.54 cu. ft./year

Molar volume = 385.5 scf/lb-mole

^a See Table 2

^b Hourly emission rate [lb/hr] = Concentration [ppm] x 10⁻⁶ x Molecular weight [lb/lb-mole] x Fugitive LFG emission rate [scf/yr] / Molar volume [scf/lb-mole] / 8,760 [hr/year]

^c Annual emission rate [lb/yr] = Concentration [ppm] x 10⁻⁶ x Molecular weight [lb/lb-mole] x Fugitive LFG emission rate [scf/yr] / Molar volume [scf/lb-mole]

Table 5
Tajiguas Landfill Operator's Equipment Fuel, Hours & Vehicle Mileage for average working day in 2013 and assumed average working day post preferred TRRP project

TYPE	MAKE	MODEL	YEAR	MAX HORSEPOWER (HP)	Fuel Type	EQUIPMENT NUMBERS (INTERNAL COUNTY NUMBER)	EQUIPMENT HOUR/MILEAGE TOTAL FOR 2013	FUEL USED TOTAL FOR 2013	EQUIPMENT HOUR/MILEAGE PER WORKING DAY (2013) 5 FUEL DAYS + 12 DAY PER WEEK IS 307 WORKING DAYS IN ONE YEAR	EQUIPMENT HOUR/MILEAGE PER WORKING DAY WITH PREFERRED TRRP PROJECT (ASSUME 35% REDUCTION)	HOURS/ MILEAGE	FUEL USED TOTAL FOR 2013 (GAL)	FUEL USED PER WORKING DAY (GAL)	ESTIMATED DAILY FUEL USE WITH TRRP (GAL)	WORKING LOCATIONS (SEE MAP)	PM Emission Factor (g/bhp-hr or g/m ³)	Tier ^a	Load Factor	Hourly PM Emissions (lb/hr)	Annual PM Emissions (lb/yr)	Hourly Fuel Use (gal/hr)
Motor Grader	CAT	163H	1999	220	RED	163H	316	1040	1.63	0.67	HOURS	1,040	3.38	3.20	5	0.4	1	0.41	2.95E-02	1.63E+01	3.28
Motor Grader	CAT	160M	2013	213	RED	160M	463	1530.5	1.51	0.58	HOURS	1,530.5	4.99	3.24	5	0.15	4	0.41	2.89E-02	8.66E+01	3.21
Backhoe Loader	CAT	430F	2012	117	RED	430F	61	173	0.30	0.10	HOURS	173	0.56	0.37	5	0.015	4	0.37	1.45E-02	8.47E+01	1.50
Wheel Tractor Scraper	CAT	637G	2007	515	RED	637G	676	6768	2.20	1.43	HOURS	6,768	22.11	14.37	3	0.15	3	0.45	8.11E-02	5.35E+01	10.64
Wheel Tractor Scraper	CAT	637E	1998	450	RED	637E	60	842	0.20	0.13	HOURS	842	2.74	1.78	3	0.4	1	0.48	1.92E-01	7.43E+00	14.00
Wheel Tractor Scraper	CAT	637G	2004	515	RED	637E	714	8023.5	2.33	1.51	HOURS	8,024	26.14	16.99	3	0.15	2	0.48	8.17E-02	3.79E+01	11.24
Wheel Tractor Scraper	CAT	637G	2005	515	RED	637B	527	5681	1.72	1.12	HOURS	5,681	18.54	12.05	3	0.15	2	0.48	8.17E-02	2.80E+01	10.80
Trash Compactor	CAT	835H	2005	401	RED	835H	295	3034	0.96	0.62	HOURS	3,034	11.51	7.48	2	0.15	2	0.4	5.35E-02	1.02E+01	11.98
Trash Compactor	CAT	835H	2010	565	RED	8361	1512	21878.4	4.93	3.20	HOURS	21,878	71.27	46.30	2	0.15	3	0.4	7.34E-02	7.22E+01	14.47
Bulldozer	CAT	D9T	2005	464	RED	D916	534	4711.7	1.74	1.13	HOURS	4,712	15.35	9.98	2	0.15	2	0.43	6.60E-02	2.29E+01	8.82
Bulldozer	CAT	D9T	2012	464	RED	D917	1609	10945.7	5.23	3.40	HOURS	10,946	35.65	23.17	2	0.015	4	0.43	6.60E-02	6.88E+02	6.82
Bulldozer	CAT	D9R	2001	410	RED	D9C3	115	1390.5	0.37	0.24	HOURS	1,391	4.55	2.94	6-7 ^b	0.15	2	0.43	6.83E-02	4.98E+00	12.00
Bulldozer	CAT	D9R	2001	410	RED	D9C3	57.5	695.25	0.19	0.12	HOURS	695	2.26	1.47	6	0.15	2	0.43	6.92E-02	1.09E+00	6.05
Bulldozer	CAT	D9R	2001	410	RED	D9C3	57.5	695.25	0.19	0.12	HOURS	695	2.26	1.47	7	0.15	2	0.43	6.92E-02	1.09E+00	6.05
Bulldozer	CAT	D6N	2009	145	RED	D6N1	536	2487.8	3.65	1.88	HOURS	3,488	11.36	7.28	2	0.22	3	0.43	3.05E-02	1.84E+01	3.73
Bulldozer	CAT	D6M	1997	153	RED	D6M1	98	918.7	0.29	0.20	HOURS	920	1.04	0.68	2	0.274	N/A	0.43	9.91E-02	2.45E+00	3.44
Bulldozer	CAT	D6T	2013	228	RED	D6T1	33	103	0.11	0.07	HOURS	103	0.34	0.22	2	0.015	4	0.43	3.24E-03	6.95E-02	3.12
Bulldozer	CAT	D10T	2008	646	RED	D10T	484	8329	1.58	1.02	HOURS	8,329	27.13	17.63	6-7 ^b	0.15	3	0.43	6.15E-02	2.89E+01	17.21
Bulldozer	CAT	D10T	2008	646	RED	D10T	242	4164.5	0.79	0.51	HOURS	4,165	13.57	8.82	6	0.15	2	0.43	4.98E-02	7.22E+00	8.60
Bulldozer	CAT	D10T	2008	646	RED	D10T	242	4164.5	0.79	0.51	HOURS	4,165	13.57	8.82	7	0.15	2	0.43	4.98E-02	7.22E+00	8.60
Hydraulic Excavator	CAT	330D	2006	270	RED	330D	69	520.7	0.22	0.15	HOURS	521	1.70	1.10	5	0.15	3	0.38	3.99E-02	1.52E+00	7.59
Wheel Tractor Mower	CAT	M125D	2013	130	RED	M20W1	66	66	0.28	0.18	HOURS	86	0.28	0.18	5	0.015	4	0.44	1.89E-03	1.06E+01	1.00
Wheel Loader	CAT	962H	2008	388	RED	LJ051	207	631	0.67	0.44	HOURS	631	3.03	1.91	5	0.15	3	0.36	3.05E-02	4.55E+00	4.55
Wheel Loader	CAT	IT29F	1996	108	RED	IT28	175	507	0.57	0.37	HOURS	507	1.66	1.07	5	0.274	N/A	0.46	2.78E-02	3.17E+00	2.90
Tarp Machine	Tarpomatic	NA	NA	NA	RED	IT0M1	20	0	0.07	0.04	HOURS	0	0.00	0.00	2						
Tarp Machine	Tarpomatic	NA	NA	NA	RED	IT0M3	114	0	0.37	0.24	HOURS	0	0.00	0.00	2						
Generator	Vermeer Rand	G29	2007	72	RED	GEN6	149	284	0.49	0.32	HOURS	284	0.92	0.60	8	0.3	2	0.74	3.52E-02	3.41E+00	1.91
Small off road	KUBOTA	RTV900	2005	22	CLEAR	KUB1	45	12.8	0.15	0.10	HOURS	13	0.04	0.03	5	0.6	2	0.34	9.89E-03	2.89E-01	0.28
Small off road	JOHN DEERE	GATOR	2011	119	CLEAR	GAT2	59	24.7	0.19	0.12	HOURS	25	0.08	0.05	5	0.3	4	0.34	4.27E-03	1.64E+01	0.42
Water truck	INTERNATIONAL	7400WS	2011	NA	CLEAR	W111	170	614.9	0.55	0.36	HOURS	615	2.06	1.36	5	5.98E-02	On Road	N/A	1.77E-03	1.96E+01	3.82
Water truck	INTERNATIONAL	7400WS	2012	NA	CLEAR	W112	329	2370.5	1.22	1.12	HOURS	2,371	7.72	5.02	5	5.11E-02	On Road	N/A	1.89E-03	5.81E+01	4.48
Fuel Truck	FREIGHTLINER	MP106	2010	NA	CLEAR	IT2F	166	178	0.55	0.36	HOURS	178	0.57	0.37	5	5.98E-02	On Road	N/A	1.84E-03	2.62E+01	1.05
Green waste Grinder	MORBARK	6600	2008	1125	RED	HOG1	649	20581.3	2.11	1.37	HOURS	20,681	67.37	43.79	4-7	0.15	2	0.42	1.56E-01	1.01E+02	31.87
Wheel Loader	CAT	930B	2000	180	RED	LJ43	655	2038.9	1.57	1.28	HOURS	2,034	6.63	4.31	4	0.4	1	0.36	5.71E-02	2.25E+01	3.36
Wheel Loader	CAT	930B	1998	180	RED	LJ40	288	988.2	0.81	0.59	HOURS	988	3.25	2.11	4	0.4	1	0.36	5.71E-02	1.04E+01	3.57
Wheel Loader	CAT	938H	2008	197	RED	LD52	1308	7921	4.25	2.77	HOURS	2,921	9.51	6.18	4	0.15	3	0.36	2.35E-02	1.99E+01	2.24

^a Emission factors for off-road equipment are Tier emission limits for engine horsepower. Emission factors for on-road vehicles are model-year specific emission factors for calendar year 2017 at 15 mph from EMFAC2011.

^b Tier is based on engine model year and horsepower rating.

^c Default load factors from Table 3.3, Appendix D of California Emissions Estimation Model (CalEEMod).

^d Hourly Off-road Equipment PM emissions [lb/hr] = Emission factor [g/bhp-hr] x Load factor [unitless] x Engine horsepower [bhp] / 453.6 [g/lb]. Hourly On-Road Vehicle PM emissions [lb/hr] = Emission factor [g/m³] x 15 [mpk] x 453.6 [g/lb]

^e Annual PM emissions [lb/yr] = Hourly PM emissions [lb/hr] x 2013 Annual operating hours [hours/yr] x 0.65 [Post project activity / 2013 activity]

^f Hourly fuel use [gal/hr] = Annual fuel use [gal/yr] / Annual operating hours [hours/yr]

^g Emissions divided equally between Area 6 and Area 7

Table 6
Landfill Mobile Equipment DPM Emissions by Area

Area	Hourly DPM Emissions (lb/hr)	Annual DPM Emissions (lb/yr)	
2	2.72E-01	1.33E+02	TRSHFILL
3	4.36E-01	1.09E+02	SCRAPPER
4	1.38E-01	5.28E+01	GRNWASTE
5	2.01E-01	2.81E+01	LFMAINOP
6	7.51E-02	8.31E+00	
7	7.51E-02	8.31E+00	1.66E+01 AREA6N7

Table 7
Landfill Green Waste Grinder DPM Emissions
 (Area 4)

Hourly Emissions (lb/hr)	1.56E-01	
Annual Emissions (lb/yr)	1.01E+02	GWGRIND

Table 8
Diesel Equipment Exhaust Emissions of TACs with Acute Effects

Table 8-A
Area 2 (7:00 a.m. - 5:00 p.m.)

Compound	CAS Number	Emission Factor (lb/1,000 gal) ^a	Emissions (lb/hour)
Benzene	71-43-2	0.1863	9.76E-03
Formaldehyde	50-00-0	1.7261	9.04E-02
Acetaldehyde	75-07-0	0.7833	4.10E-02
Acrolein	107-02-8	0.0339	1.78E-03
1,3-Butadiene	106-99-0	0.2174	1.14E-02
Toluene	108-88-3	0.1054	5.52E-03
Xylenes	1330-20-7	0.0424	2.22E-03
Hydrogen chloride	7647-01-0	0.1863	9.76E-03
Arsenic	7440-38-2	0.0016	8.38E-05
Copper	7440-50-8	0.0041	2.15E-04
Mercury	7439-97-6	0.0020	1.05E-04
Nickel	7440-02-0	0.0039	2.04E-04

TRSHFILL

Hourly fuel use = 52.38 gal/hr

^a From Ventura County Air Pollution Control District
 AB 2588 Emission Factors for Diesel Fuel Internal Combustion.
<http://www.vcapcd.org/pubs/Engineering/AirToxics/combem.pdf>
 Only includes TACs with acute reference exposure levels.

Table 8-B
Area 3 (7:00 a.m. - 5:00 p.m.)

Compound	CAS Number	Emission Factor (lb/1,000 gal) ^a	Emissions (lb/hour)
Benzene	71-43-2	0.1863	8.59E-03
Formaldehyde	50-00-0	1.7261	7.96E-02
Acetaldehyde	75-07-0	0.7833	3.61E-02
Acrolein	107-02-8	0.0339	1.56E-03
1,3-Butadiene	106-99-0	0.2174	1.00E-02
Toluene	108-88-3	0.1054	4.86E-03
Xylenes	1330-20-7	0.0424	1.96E-03
Hydrogen chloride	7647-01-0	0.1863	8.59E-03
Arsenic	7440-38-2	0.0016	7.38E-05
Copper	7440-50-8	0.0041	1.89E-04
Mercury	7439-97-6	0.0020	9.22E-05
Nickel	7440-02-0	0.0039	1.80E-04

SCRAPPER

Hourly fuel use = 46.11 gal/hr

^a From Ventura County Air Pollution Control District
 AB 2588 Emission Factors for Diesel Fuel Internal Combustion.
<http://www.vcapcd.org/pubs/Engineering/AirToxics/combem.pdf>
 Only includes TACs with acute reference exposure levels.

Table 8-C
Area 4 (7:00 a.m. - 5:00 p.m.)

Compound	CAS Number	Emission Factor (lb/1,000 gal) ^a	Emissions (lb/hour)
Benzene	71-43-2	0.1863	1.71E-03
Formaldehyde	50-00-0	1.7261	1.58E-02
Acetaldehyde	75-07-0	0.7833	7.18E-03
Acrolein	107-02-8	0.0339	3.11E-04
1,3-Butadiene	106-99-0	0.2174	1.99E-03
Toluene	108-88-3	0.1054	9.66E-04
Xylenes	1330-20-7	0.0424	3.89E-04
Hydrogen chloride	7647-01-0	0.1863	1.71E-03
Arsenic	7440-38-2	0.0016	1.47E-05
Copper	7440-50-8	0.0041	3.76E-05
Mercury	7439-97-6	0.0020	1.83E-05
Nickel	7440-02-0	0.0039	3.57E-05

GRNWASTE

Hourly fuel use = 9.16 gal/hr

^a From Ventura County Air Pollution Control District
 AB 2588 Emission Factors for Diesel Fuel Internal
 Combustion.
<http://www.vcapcd.org/pubs/Engineering/AirToxics/combem.pdf>
 Only includes TACs with acute reference exposure levels.

Table 8-D
Area 5 (7:00 a.m. - 5:00 p.m.)

Compound	CAS Number	Emission Factor (lb/1,000 gal) ^a	Emissions (lb/hour)
Benzene	71-43-2	0.1863	6.65E-03
Formaldehyde	50-00-0	1.7261	6.16E-02
Acetaldehyde	75-07-0	0.7833	2.79E-02
Acrolein	107-02-8	0.0339	1.21E-03
1,3-Butadiene	106-99-0	0.2174	7.76E-03
Toluene	108-88-3	0.1054	3.76E-03
Xylenes	1330-20-7	0.0424	1.51E-03
Hydrogen chloride	7647-01-0	0.1863	6.65E-03
Arsenic	7440-38-2	0.0016	5.71E-05
Copper	7440-50-8	0.0041	1.46E-04
Mercury	7439-97-6	0.0020	7.14E-05
Nickel	7440-02-0	0.0039	1.39E-04

LFMAINOP

Hourly fuel use = 35.68 gal/hr

^a From Ventura County Air Pollution Control District
 AB 2588 Emission Factors for Diesel Fuel Internal
 Combustion.
<http://www.vcapcd.org/pubs/Engineering/AirToxics/combem.pdf>
 Only includes TACs with acute reference exposure levels.

Table 8-E
Area 6 (7:00 a.m. - 5:00 p.m.)

Compound	CAS Number	Emission Factor (lb/1,000 gal) ^a	Emissions (lb/hour)
Benzene	71-43-2	0.1863	2.73E-03
Formaldehyde	50-00-0	1.7261	2.53E-02
Acetaldehyde	75-07-0	0.7833	1.15E-02
Acrolein	107-02-8	0.0339	4.97E-04
1,3-Butadiene	106-99-0	0.2174	3.18E-03
Toluene	108-88-3	0.1054	1.54E-03
Xylenes	1330-20-7	0.0424	6.21E-04
Hydrogen chloride	7647-01-0	0.1863	2.73E-03
Arsenic	7440-38-2	0.0016	2.34E-05
Copper	7440-50-8	0.0041	6.01E-05
Mercury	7439-97-6	0.0020	2.93E-05
Nickel	7440-02-0	0.0039	5.71E-05

SUM Emissions (lb/hour)
5.46E-03
5.06E-02
2.30E-02
9.93E-04
6.37E-03
3.09E-03
1.24E-03
5.46E-03
4.69E-05
1.20E-04
5.86E-05
1.14E-04

AREA6N7

Hourly fuel use = 14.65 gal/hr

^a From Ventura County Air Pollution Control District
 AB 2588 Emission Factors for Diesel Fuel Internal Combustion.
<http://www.vcapcd.org/pubs/Engineering/AirToxics/combem.pdf>
 Only includes TACs with acute reference exposure levels.

Table 8-F
Area 7 (7:00 a.m. - 5:00 p.m.)

Compound	CAS Number	Emission Factor (lb/1,000 gal) ^a	Emissions (lb/hour)
Benzene	71-43-2	0.1863	2.73E-03
Formaldehyde	50-00-0	1.7261	2.53E-02
Acetaldehyde	75-07-0	0.7833	1.15E-02
Acrolein	107-02-8	0.0339	4.97E-04
1,3-Butadiene	106-99-0	0.2174	3.18E-03
Toluene	108-88-3	0.1054	1.54E-03
Xylenes	1330-20-7	0.0424	6.21E-04
Hydrogen chloride	7647-01-0	0.1863	2.73E-03
Arsenic	7440-38-2	0.0016	2.34E-05
Copper	7440-50-8	0.0041	6.01E-05
Mercury	7439-97-6	0.0020	2.93E-05
Nickel	7440-02-0	0.0039	5.71E-05

Hourly fuel use = 14.65 gal/hr

^a From Ventura County Air Pollution Control District
 AB 2588 Emission Factors for Diesel Fuel Internal Combustion.
<http://www.vcapcd.org/pubs/Engineering/AirToxics/combem.pdf>
 Only includes TACs with acute reference exposure levels.

Table 8-G
Green Waste Grinder (7:00 a.m. - 5:00 p.m.)

Compound	CAS Number	Emission Factor (lb/1,000 gal) ^a	Emissions (lb/hour)
Benzene	71-43-2	0.1863	5.94E-03
Formaldehyde	50-00-0	1.7261	5.50E-02
Acetaldehyde	75-07-0	0.7833	2.50E-02
Acrolein	107-02-8	0.0339	1.08E-03
1,3-Butadiene	106-99-0	0.2174	6.93E-03
Toluene	108-88-3	0.1054	3.36E-03
Xylenes	1330-20-7	0.0424	1.35E-03
Hydrogen chloride	7647-01-0	0.1863	5.94E-03
Arsenic	7440-38-2	0.0016	5.10E-05
Copper	7440-50-8	0.0041	1.31E-04
Mercury	7439-97-6	0.0020	6.37E-05
Nickel	7440-02-0	0.0039	1.24E-04

GWGRIND

Hourly fuel use = 31.87 gal/hr

^a From Ventura County Air Pollution Control District
 AB 2588 Emission Factors for Diesel Fuel Internal Combustion.
<http://www.vcapcd.org/pubs/Engineering/AirToxics/combem.pdf>
 Only includes TACs with acute reference exposure levels.

Table 9

Table 9-A
On-Site Motor Vehicle DPM Emissions

Vehicle	Use	Operating Hours/Day	Days/Year	Segment	Mileage (mpg)	Round-Trip Dist. (mi)	Average Round-Trips/Day	Maximum Round Trips/Day ^a	Average Miles/Day	Maximum Miles/Day	Maximum Hourly Fuel Use (gal/hr) ^b	PM10 Emission Factor (g/mi) ^c	Hourly DPM Emissions (lb/hr) ^d	Annual DPM Emissions (lb/yr) ^e
Tractor/Trailer	CSSR Import ^f	6	311	MRF-Entrance	6	2.23	7	7	15.61	15.61	0.43	3.68E-02	2.11E-04	3.94E-01
MSW Haul	MSW Haul ^g	9	309	MRF-Entrance	6	2.23	60.3	159.2	134.47	355.00	6.57	3.68E-02	3.20E-03	3.37E+00
MSW Haul	MSW Haul ^g	9	309	MRF-Trash Fill	6	0.90	60.3	159.2	54.39	143.59	2.66	3.68E-02	1.29E-03	1.36E+00
Ford F350 XL	Utility truck and trailer	6	311	MRF-Compost	14	0.90	6	6	5.41	5.41	0.06	4.90E-03	9.75E-06	1.82E-02
Ford F350 XL	Utility truck and trailer	6	311	MRF-Entrance	14	2.23	6	6	13.38	13.38	0.16	4.90E-03	2.41E-05	4.50E-02

^a Maximum round trips/day for MSW Haul = Average Round Trips/day x 2.64

^b Maximum hourly fuel use [gal/hr] = Maximum daily mileage [miles/day] / Mileage [mpg] / Operating hours/day

^c Tractor/trailer is from EMFAC2011 emission rates for T7 trucks in Santa Barbara County

at 15 mph in calendar year 2017 <http://www.arb.ca.gov/emfac/>

Ford F350 XL is from EMFAC2011 emission rates for 2017 model year light heavy-duty truck 2 in Santa Barbara County

at 45 mph in calendar year 2017 <http://www.arb.ca.gov/emfac/>

^d Hourly DPM emissions [lb/hr] = Maximum miles/day x PM10 emission factor [g/mi] / 453.6 [g/lb] / Operating hours/day

^e Annual DPM emissions [lb/yr] = Average miles/day x PM10 emission factor [g/mi] / 453.6 [g/lb] x Days/year

^f Trips/day are from Project Traffic Study.

^g Average trips/day are 2013 totals / 309 working days.

Table 9-B
On-Site Motor Vehicle DPM Emissions by Segment

Segment	Hourly DPM Emissions (lb/hr) ^d	Annual DPM ER (lb/yr) ^e	Project DPM ER (8a-2p) (lb/yr)	Total DPM Emissions (lb/yr)	
MRF-Entrance	3.44E-03	3.81E+00	1.41E+00	5.23E+00	MRFENTRY
MRF-Trash Fill	1.29E-03	1.36E+00	0	1.36E+00	HAUL
MRF-Compost	9.75E-06	1.82E-02	8.99E-02	1.08E-01	MRFCOMP

**Table 10
Diesel Motor Vehicle Exhaust Emissions of TACs with Acute Effects**

**Table 10-A
Entrance to/from MRF (7:00 a.m. - 5:00 p.m.)**

Compound	CAS Number	Emission Factor (lb/1,000 gal) ^a	Existing Emissions (lb/hour)	Project Emissions (lb/hr)	Total Emissions (lb/hr)
Benzene	71-43-2	0.1863	1.34E-03	1.10E-04	1.45E-03
Formaldehyde	50-00-0	1.7261	1.24E-02	1.02E-03	1.34E-02
Acetaldehyde	75-07-0	0.7833	5.61E-03	4.64E-04	6.08E-03
Acrolein	107-02-8	0.0339	2.43E-04	2.01E-05	2.63E-04
1,3-Butadiene	106-99-0	0.2174	1.56E-03	1.29E-04	1.69E-03
Toluene	108-88-3	0.1054	7.55E-04	6.25E-05	8.18E-04
Xylenes	1330-20-7	0.0424	3.04E-04	2.51E-05	3.29E-04
Hydrogen chloride	7647-01-0	0.1863	1.34E-03	1.10E-04	1.45E-03
Arsenic	7440-38-2	0.0016	1.15E-05	9.49E-07	1.24E-05
Copper	7440-50-8	0.0041	2.94E-05	2.43E-06	3.18E-05
Mercury	7439-97-6	0.0020	1.43E-05	1.19E-06	1.55E-05
Nickel	7440-02-0	0.0039	2.80E-05	2.31E-06	3.03E-05

MRFENTRY

Hourly fuel use = 7.17 gal/hr

^a From Ventura County Air Pollution Control District
AB 2588 Emission Factors for Diesel Fuel Internal
Combustion.
<http://www.vcapcd.org/pubs/Engineering/AirToxics/combem.pdf>
Only includes TACs with acute reference exposure levels.

**Table 10-B
MRF to/from Trash Fill (7:00 a.m. - 5:00 p.m.)**

Compound	CAS Number	Emission Factor (lb/1,000 gal) ^a	Emissions (lb/hour)
Benzene	71-43-2	0.1863	4.95E-04
Formaldehyde	50-00-0	1.7261	4.59E-03
Acetaldehyde	75-07-0	0.7833	2.08E-03
Acrolein	107-02-8	0.0339	9.01E-05
1,3-Butadiene	106-99-0	0.2174	5.78E-04
Toluene	108-88-3	0.1054	2.80E-04
Xylenes	1330-20-7	0.0424	1.13E-04
Hydrogen chloride	7647-01-0	0.1863	4.95E-04
Arsenic	7440-38-2	0.0016	4.25E-06
Copper	7440-50-8	0.0041	1.09E-05
Mercury	7439-97-6	0.0020	5.32E-06
Nickel	7440-02-0	0.0039	1.04E-05

HAUL

Hourly fuel use = 2.66 gal/hr

^a From Ventura County Air Pollution Control District
AB 2588 Emission Factors for Diesel Fuel Internal
Combustion.
<http://www.vcapcd.org/pubs/Engineering/AirToxics/combem.pdf>
Only includes TACs with acute reference exposure levels.

Table 10-C

MRF to/from Compost Area (8:00 a.m. - 2:00 p.m.)

Compound	CAS Number	Emission Factor (lb/1,000 gal) ^a	Existing Emissions (lb/hour)	Project Emissions (lb/hr)	Total Emissions (lb/hr)
Benzene	71-43-2	0.1863	1.20E-05	1.20E-05	2.40E-05
Formaldehyde	50-00-0	1.7261	1.11E-04	1.11E-04	2.22E-04
Acetaldehyde	75-07-0	0.7833	5.05E-05	5.05E-05	1.01E-04
Acrolein	107-02-8	0.0339	2.18E-06	2.18E-06	4.37E-06
1,3-Butadiene	106-99-0	0.2174	1.40E-05	1.40E-05	2.80E-05
Toluene	108-88-3	0.1054	6.79E-06	6.79E-06	1.36E-05
Xylenes	1330-20-7	0.0424	2.73E-06	2.73E-06	5.46E-06
Hydrogen chloride	7647-01-0	0.1863	1.20E-05	1.20E-05	2.40E-05
Arsenic	7440-38-2	0.0016	1.03E-07	1.03E-07	2.06E-07
Copper	7440-50-8	0.0041	2.64E-07	2.64E-07	5.28E-07
Mercury	7439-97-6	0.0020	1.29E-07	1.29E-07	2.58E-07
Nickel	7440-02-0	0.0039	2.51E-07	2.51E-07	5.03E-07

MRFCOMP

Hourly fuel use = 0.06 gal/hr

^a From Ventura County Air Pollution Control District
 AB 2588 Emission Factors for Diesel Fuel Internal
 Combustion.

<http://www.vcapcd.org/pubs/Engineering/AirToxics/combem.pdf>

Only includes TACs with acute reference exposure levels.

Table 11
IC Engine and Flare 2013 Annual LFG Combustion

Quarter	IC Engine LFG Heat Input (MMBtu) ^a	LFG Heat Value (Btu/scf) ^a	IC Engine LFG Input (scf) ^b	Flare LFG Heat Input (MMBtu) ^a	LFG Heat Value (Btu/scf) ^a	Flare LFG Input (scf) ^b
First	68,570.76	569	120,511,002	8,584.20	582	14,749,485
Second	69,161.52	524	131,987,634	335.23	524	639,752
Third	65,180.18	524	124,389,656	5,169.71	524	9,865,859
Fourth	74,705.11	524	142,567,004	516.03	524	984,790
Total	277,617.57		519,455,296	14,605.17		26,239,885

^a From quarterly emissions reports

^b LFG input [scf] = LFG heat input [MMBtu] x 10⁶ [Btu/MMBtu] / LFG heat value [Btu/scf]

**Table 12
IC Engine Toxic Air Contaminant Emissions from LFG Combustion**

Compound	CAS Number	Emission Factor (lb/MMscf) ^a	Hourly Emission Rate (lb/hr) ^b	Annual Emission Rate (lb/yr) ^c	EXISTENG
Acenaphthene	83-32-9	3.01E-04	2.07E-05	1.56E-01	
Acenaphthylene	208-96-8	1.23E-03	8.48E-05	6.39E-01	
Anthracene	120-12-7	3.71E-04	2.56E-05	1.93E-01	
Benzene	71-43-2	2.09E-01	1.44E-02	1.09E+02	
Benzo(a)anthracene	56-55-6	2.88E-04	1.98E-05	1.50E-01	
Benzo(a)pyrene	50-32-8	6.77E-04	4.67E-05	3.52E-01	
Benzo(b)fluoranthene	205-99-2	8.00E-04	5.51E-05	4.16E-01	
Benzo(g,h,i)perylene	191-24-2	8.54E-04	5.89E-05	4.44E-01	
Benzo(k)fluoranthene	207-08-9	6.77E-04	4.67E-05	3.52E-01	
Carbon Tetrachloride	56-23-5	7.89E-03	5.44E-04	4.10E+00	
Chloroform	67-66-3	6.11E-03	4.21E-04	3.17E+00	
Chrysene	218-01-9	3.42E-04	2.36E-05	1.78E-01	
Dibenz(a,h)anthracene	53-70-3	2.37E-05	1.63E-06	1.23E-02	
Ethylene Dibromide	106-93-4	9.64E-03	6.64E-04	5.01E+00	
Ethylene Dichloride	106-93-4	5.08E-03	3.50E-04	2.64E+00	
Fluoranthene	206-44-0	2.48E-03	1.71E-04	1.29E+00	
Fluorene	86-73-7	6.99E-04	4.82E-05	3.63E-01	
Formaldehyde	50-00-0	4.47E+00	3.08E-01	2.32E+03	
HCl	7647-01-0	2.07E+00	1.43E-01	1.08E+03	
Indeno(1,2,3-cd)pyrene	193-39-5	3.14E-04	2.16E-05	1.63E-01	
Methyl Chloroform	71-55-6	2.64E-02	1.82E-03	1.37E+01	
Methylene Chloride	75-09-2	4.66E-01	3.21E-02	2.42E+02	
Naphthalene	91-20-3	5.05E-02	3.48E-03	2.62E+01	
Perchloroethylene	127-18-4	1.28E-02	8.82E-04	6.65E+00	
Phenanthrene	85-01-8	5.82E-03	4.01E-04	3.02E+00	
Pyrene	129-00-0	4.66E-03	3.21E-04	2.42E+00	
Trichloroethylene	79-01-6	8.43E-03	5.81E-04	4.38E+00	
Vinyl Chloride	75-01-4	4.01E-03	2.76E-04	2.08E+00	

Hourly LFG flow rate = 68,922 scfh Maximum rated capacity from facility Title V permit
 Annual LFG flow rate 519,455,296 scf 2013 reported annual total

^a Maximum emission factors from California Air Toxics Emission Factors http://www.arb.ca.gov/app/emsinv/catef_form.html for flare fired on landfill gas

^b Hourly emission rate [lb/hr] = Emission factor [lb/MMscf] x Hourly LFG flow rate [scfh] / 10⁶ [scf/MMscf]

^c Annual emission rate [lb/yr] = Emission factor [lb/MMscf] x Annual LFG flow rate [scfh] / 10⁶ [scf/MMscf]

**Table 13
Flare Toxic Air Contaminant Emissions from LFG Combustion**

Compound	CAS Number	Emission Factor (lb/MMscf)	Emission Factor Source ^a	Hourly Emission Rate (lb/hr) ^b	Annual Emission Rate (lb/yr) ^c
Indeno(1,2,3-cd)pyrene	193-39-5	5.60E-02	CATEF	4.83E-03	1.47E+00
Manganese	7439-96-5	2.92E-03	Source Test	2.52E-04	7.66E-02
Naphthalene	91-20-3	1.75E-04	Source Test	1.51E-05	4.59E-03
Nickel	7440-02-0	1.43E-03	Source Test	1.23E-04	3.75E-02
Perylene	198-55-0	7.48E-05	CATEF	6.45E-06	1.96E-03
Phenanthrene	85-01-8	9.85E-04	Source Test	8.50E-05	2.59E-02
Pyrene	129-00-0	3.04E-05	Source Test	2.63E-06	7.99E-04
Toluene	108-88-3	1.09E+02	CATEF	9.40E+00	2.86E+03
Trichloroethene	79-01-6	1.13E+00	CATEF	9.74E-02	2.97E+01
Vinyl Chloride	75-01-4	7.64E-02	CATEF	6.59E-03	2.00E+00
Xylene (m,p)	1330-20-7	4.61E-01	CATEF	3.98E-02	1.21E+01
Xylene (o)	95-47-6	3.35E-01	CATEF	2.89E-02	8.79E+00
Zinc	7440-66-6	4.28E+00	CATEF	3.69E-01	1.12E+02
1,1,1-Trichloroethane	71-55-6	3.37E-01	CATEF	2.91E-02	8.84E+00
1,1-Dichloroethane	75-34-3	4.37E-01	CATEF	3.77E-02	1.15E+01
1,2-Dichloroethane	107-06-2	1.35E+00	CATEF	1.16E-01	3.54E+01
1,4-Dioxane	123-91-1	4.55E-03	Source Test	3.93E-04	1.19E-01
2-Methylnaphthalene	91-57-6	9.56E-05	Source Test	8.24E-06	2.51E-03
Acenaphthene	83-32-9	7.04E-06	Source Test	6.07E-07	1.85E-04
Acenaphthylene	208-96-8	1.09E-04	Source Test	9.39E-06	2.86E-03
Acetaldehyde	75-07-0	6.53E-01	CATEF	5.63E-02	1.71E+01
Acetonitrile	75-05-8	7.96E+00	CATEF	6.86E-01	2.09E+02
Acrolein	107-02-8	9.33E-02	CATEF	8.05E-03	2.45E+00
Acrylonitrile	107-13-1	4.50E-03	Source Test	3.88E-04	1.18E-01
Anthracene	120-12-7	1.10E-05	Source Test	9.52E-07	2.90E-04
Arsenic	7440-38-2	5.91E-02	Source Test	5.10E-03	1.55E+00
Benzene	71-43-2	8.59E-01	CATEF	7.41E-02	2.25E+01
Benzo(a)anthracene	56-55-6	5.60E-02	CATEF	4.83E-03	1.47E+00
Benzo(a)pyrene	50-32-8	5.60E-02	CATEF	4.83E-03	1.47E+00
Benzo(b)fluoranthene	205-99-2	5.60E-02	CATEF	4.83E-03	1.47E+00
Benzo(e)pyrene	192-97-2	7.48E-05	CATEF	6.45E-06	1.96E-03
Benzo(g,h,i)perylene	191-24-2	5.60E-02	CATEF	4.83E-03	1.47E+00
Benzo(k)fluoranthene	207-08-9	5.60E-02	CATEF	4.83E-03	1.47E+00
Cadmium	7440-43-9	1.43E-03	Source Test	1.23E-04	3.75E-02
Carbon Tetrachloride	56-23-5	3.76E-02	CATEF	3.24E-03	9.87E-01
Chlorobenzene	108-90-7	8.69E-01	CATEF	7.49E-02	2.28E+01
Chloroform	67-66-3	5.60E-02	CATEF	4.83E-03	1.47E+00
Chromium (Hex)	18540-29-9	1.21E-05	Source Test	1.05E-06	3.19E-04
Chromium (Total)	7440-47-3	4.64E-03	Source Test	4.00E-04	1.22E-01
Chrysene	218-01-9	6.51E-06	Source Test	5.61E-07	1.71E-04
Copper	7440-50-8	4.86E+00	CATEF	4.19E-01	1.28E+02
Dibenz(a,h)anthracene	53-70-3	5.60E-02	CATEF	4.83E-03	1.47E+00
Dichloromethane	75-09-2	4.29E-01	CATEF	3.70E-02	1.13E+01
Fluoranthene	206-44-0	1.40E-05	Source Test	1.21E-06	3.67E-04
Fluorene	86-73-7	2.84E-04	Source Test	2.45E-05	7.44E-03
Formaldehyde	50-00-0	1.77E-01	Source Test	1.53E-02	4.65E+00
HCl	7647-01-0	1.61E-03	Source Test	1.39E-04	4.24E-02
HF	7664-39-3	2.15E-01	Source Test	1.85E-02	5.64E+00

EXISTFLR

Hourly LFG flow rate = 86,236 scfh Maximum one minute flow rate provided by SBCAPCD
Annual LFG flow rate 26,239,885 scf 2013 reported annual total

^a CATEF = Maximum emission factors from California Air Toxics Emission Factors http://www.arb.ca.gov/app/emsinv/catef_form.html for flare fired on landfill gas based on assumption that biogas composition is similar to landfill gas

Source Test = September 9-11 2010 source tests on Santa Maria Landfill flare combusting LFG. Non-detects set to detection limit.

^b Hourly emission rate [lb/hr] = Emission factor [lb/MMscf] x Hourly LFG flow rate [scfh] / 10⁶ [scf/MMscf]

^c Annual emission rate [lb/yr] = Emission factor [lb/MMscf] x Annual LFG flow rate [scfh] / 10⁶ [scf/MMscf]

